

<u>INVITATION TO E-TENDER</u> WORKS DIRECTORATE, CENTRAL RESERVE POLICE FORCE

Level – 3, Block-7, Sec -1, East Block, R. K. Puram, New Delhi–110066, Tel/Fax: 011-26108447

E-Mail id – digwks@crpf.gov.in			Tele / Fax No. :011-26108447		
 No	. B.V(202I	3N)24-25-/S-12/WksDte-C/Cell(NIT-41)	Dated, March,2025	•••	
Τо,					
Dea	ar Sir,				
		the President of India, I invite you to online bid under NABEDA, KORAPUT, ODISHA:- Details of pro			
		P	- common of Proposition		
	1.	SPECIAL REPAIR OF GI SHEETED ROOI DAMAGED TILES FLOORING OF VARIO (TRAINING SOS' MESS & 06 NOS 60 MEN BA KORAPUT, ODISHA	OUS SEMI-PERMANENT BUILDINGS		
02.		Details of works are mentioned in Schedule- "A" a	nd "B.O.Q. of Tender".		
sub the alo	ted in the omitted through aforesaid aforesaid aforesaid be to be re	If you are in a position to quote for carrying out the p attached schedule to tender, all documents attached hough e-procurement site http://eprocure.gov.in/eprocure/ tender all the information called for, attached list of quoteuments through e-procurement site http://eprocure.govjected and will not be considered. This tender is not transferable. Thanking you.	erewith should be properly filled in, signed an app. You are further required to furnish along with stionnaire should also be answered and submitted.	nd ith ed	

Yours faithfully

Sd/-DIG (Engr), Works Dte. For and on behalf of the President of India

SCHEDULE TO TENDER (OPEN TENDER)

CENTRAL RESERVE POLICE FORCE

(Government of India, Ministry of Home Affairs) Works Directorate, CRPF

No. B.V(202BN)24-25-/S-12/WksDte-C/Cell(NIT-41)	Dated,	March, 2025

TENDER SET IS NOT TRANSFERABLE

Tender Enquiry No.	:	
Date of Publishing of Tender		As per CPP Portal
Time and date of submission/receipt of tender	:	
Time and date for opening of tender	:	

01. The intending tenderers must read the terms and condition carefully and submit their tender if they consider themselves eligible and are in possession of all the required documents, through online tender (e-procurement web site in CPP Portal) before due date & time. Tenderers are also advised to go through the Earnest Money, Payment terms and other clauses, terms and conditions of this Tender Enquiry carefully before filling the Tender Application.

Tender No	Name of work with its description and location	Category of service required / Quantity / Work Timing / Periodicity / Period	Estimated cost put to tender	Earnest Money Deposit @2 %	Procedure for deposit of Earnest Money Deposit (EMD)	Critical date
B.V(202BN) 24-25-/S- 12/WksDte- C/Cell(NIT- 41)	SPECIAL REPAIR OF GI SHEETED ROOFING, FALSE CEILING & VARIOUS DAMAGED TILES FLOORING OF VARIOUS SEMI- PERMANENT BUILDINGS (TRAINING SOS' MESS & 06 NOS 60 MEN BARRACKS) AT 202 COBRA, SUNABEDA, KORAPUT, ODISHA	As per attached Appendix- 'B' of "Schedule to tender"	Rs. 41,38,663/-	Rs 82,773/- [Note: - EMD Should be valid for 90 days from the bid submission end date of tender. If there after validity of the E.M.D require extension, the firm will be responsible to extend the same suitably till the validity of the bid]	Rs 82,773/- Original Earnest Money Deposit (EMD) shall be deposited in office of the Works Dte, level-3, East Block-7, Sec -1, , RK Puram, New Delhi before the due date of submission of bid.	As per CPP Portal

- 02. Tenders will be opened online on the given date & time at CRPF Works Dte, Level-3, East Block 07, RK Puram, Sector-1, New Delhi.
- 03. Tenderers are requested to submit their bid/tender documents online through e-procurement in CPP Portal. EMD, Tender Acceptance Letter (On firms letter head), Integrity Pact (On firms letter head) documents shall be submitted in original either by hand or by registered/speed post to CRPF Works Dte, Level-3, East Block 07, RK Puram, Sector- 1, New Delhi.
- 04. All Tender documents attached with this invitation to tender including the specifications are sacrosanct for considering any offer as complete offer. It is therefore important that Tender Acceptance Letter which is a written undertaking that all the terms and conditions of the tender are understood and accepted should be signed and submitted along with all documents as required through e-Procurement site http://eprocure.gov.in/eprocure/app.
- 05. All bidders required to submit earnest money as mentioned above along with their offer. EMD should be paid by the bidder mandatorily. If the bidder fails to submit EMD then his tender will be rejected summarily.
- 06. All bidders are required to submit their offer in **two bid system**.
- 07. The enlistment of the contractor should be valid on the last date of submission of the bid. In case only the last date of submission of bid is extended, the enlistment of contractor should be valid on the original date of submission of bid.

08. Details required to be furnished by all bidders in the bid (Composite i.e. Technical & Price or financial Bid together) are as under. The bid should contain the following: -

i) Documents to be submitted online in scanned copy on CPPP:-

1.	Tender acceptance letter (In firm's letter head)
2.	Earnest Money deposit (As per schedule to tender failing which offers will be summarily rejected).
3.	Copy of GST registration certificate.
4.	Copy of PAN Card
5.	Copy of registration of the firm/contractor with CPWD, MES, BRO, RAILWAY and ODHISA PWD or All
] .	Documents required for Enlistment as specified in the latest CPWD Enlistment Rules.
6.	Copy of certificate of registration for EPFO and certificate of registration for ESIC (Declaration, if not
	applicable) failing which offers will be summarily rejected).
7.	Satisfactorily completed as a prime contractor at least one similar work of 80% value or two works of atleast
/.	60% value or 3 works of atleast 40% value. (for non – enlisted contractors)
	Bidder has to submit on-line scanned copy of certificate of Work Order along with Work Completion
	certificate of similar nature work equal to required value during last seven years issued by not below the rank
	of Executive Engineer.
	Similar works means works that pertain to Construction/Repair/Maintenance of Buildings.
8.	Partnership Agreement of the firm if the firm is a partnership firm. (If no papers submitted with the bid it will
	be assumed that the firm is a Single/Sole Proprietary and will be fully responsible if found false at later stage)
9.	Check list as per Appendix-'B' after compliance.
10.	Information in prescribed format (as per Appendix-"F") regarding any litigation, arbitration, black listing,
	<u>debarring etc.</u> resulting from contracts executed by the bidder in the <u>last five years</u> or currently under execution
	as provided. If involved any litigation, arbitration, black listing, debarring etc., please provide details for the
	same.
11.	Bidder has to submit on-line scanned copy of an affidavit duly signed stating that the <u>near relations defined</u>
	as first blood relations, and their spouses is/are not working in CRPF.
	If working, give details for the same. (a relation shall mean wife, husband, parents, grandparents, children,
	grandchildren, brothers, sisters, uncles, aunts, cousins and their corresponding in-laws)
12.	Note:- Affidavit should not be old more than 06 months from bid submission end date. Bidder has to submit on-line scanned copy of an <u>affidavit</u> duly signed stating that <u>no retired personnel in his</u>
12.	employment is working who retired within last two years from CRPF.
	If employed, give details for the same.
	Note:- Affidavit should not be old more than 06 months from bid submission end date.
13.	Non-enlisted bidders are required to submit
	(i) Either Banker's Certificate of Rs. 41.6 Lakh (Proforma as Appendix-E)
	OR
	Net worth Certificate of Rs. 13 Lakh (proforma as Appendix-D)
	AND
	(ii) Average Annual Turnover Certificate of Rs. 41.6 Lakh (Proforma as Appendix-C) on works
	during the last three financial years from a Chartered Accountant.
	Note:- Documents should not be old more than 06 months from bid submission end date.

(ii) **Documents to be submitted in original manually or by registered/speed post** to CRPF Works Dte, Level-3, East Block – 07, RK Puram, Sector- 1, New Delhi.

1.	Tender acceptance letter (On firms letter head)
2.	Earnest Money deposit
3.	Integrity Pact (On firms letter head)

- 09. Following should be noted and kept in mind while submission of rate in price bid format of C.P.P Portal
 - i) Price should only be quoted as per price bid format / B.O.Q along with tender documents at e-procurement site http://eprocure.gov.in/eprocure/app.
 - ii) The price bid in B.O.Q format / template should not be modified and replaced by the bidder and the same should be uploaded after filling the relevant columns, else the bidder is liable to be rejected for the tender. Bidders are allowed to enter the Bidder Name and Values only.

- 10. Bidder should deposit earnest money with required validity along with their Tender. Earnest Money should be in form of <u>Account pavee Demand Draft</u>, <u>Fixed Deposit Receipt</u>, <u>Banker's Cheque</u> from any of the commercial banks in an acceptable form in favour of "THE COMMANDANT 202 CoBRA, PAYBLE AT- SBI HAL TOWNSHIP SUNABEDA, BRANCH CODE-1304]"
- 11. The tender documents are consisting of specification, schedule of quantities of works to be provided and terms and conditions of this contract to be complied with other necessary documents.

SIGNATURE OF THE TENDERER

Sd/-DIG (Engr), Works Dte For and on behalf of the President of India

TENDER ACCEPTANCE LETTER

Date:	(10 be given on Firm s/Company's Letter Head)
То,	
Subject	-Acceptance of Terms & Conditions of Tender.
Tender	Reference No:-
Name of	of Tender / Work: -
Dear Si	r,
1.	I/We have downloaded/obtained the tender document(s) for the above mentioned 'Tender/Work' from the web site(s) namely
2.	I / We hereby certify that I / we have read the entire terms and conditions of the tender documents from Page No to (including all documents like annexure(s), schedule(s), etc.) which form part of the contract agreement and I / we shall abide hereby by the terms / conditions / clauses contained therein.
3.	The corrigendum(s) issued from time to time by your department/ organizations too have also been taken into consideration, while submitting this acceptance letter.
4.	$I \ / \ We \ hereby \ unconditionally \ accept \ the \ tender \ conditions \ of \ above \ mentioned \ tender \ document(s) \ corrigendum(s) \ in \ its \ totality/entirety.$
5.	In case any provisions of this tender are found violated, then your department/ organization shall withou prejudice to any other right or remedy be at liberty to reject this tender/bid including the forfeiture of the ful said earnest money deposit absolutely.

Yours Faithfully,

(Signature of the Bidder, with Official Seal) SIGNATURE OF TENDERER

<u>Check list for tenderer</u>

(Tenderers should check following requirements for compliance before submission of the tender documents)

Sl.	Requirements to be checked by the tenderer before submission of the tender	Compliance (To be
No.	requirements to be encered by the tenderer before submission of the tender	indicated With "YES"
110.		after Compliance of
		the requirements)
1.	Whether Tenderers has submitted required Earnest Money Deposit with their bid as	the requirements)
**	specified? (As per schedule to tender failing which offers will be summarily rejected).	
2.	Whether rates have been quoted only as per price bid format / B.O.Q along with tender	
	documents?	
3.	Whether rates have been quoted inclusive of all taxes including GST (ESI and EPF	
	contributions on the part of employer in respect of this contract shall be paid by the	
	contractor. The EPF & ESIC contributions on the part of the employer paid by the	
	contractor shall be reimbursed by the department to the contractor on actual basis with	
	site of work at 202 CoBRA, SUNABEDA, KORAPUT, ODISHA. only on producing	
	original receipt of EPF & ESIC paid by the contractor to Govt. organization.	
	(It may also be noted that the quoted rates are inclusive of all taxes.)	
4.	Whether copy of GST submitted?	
5.	Whether copy of PAN Card submitted?	
6.	Whether copy of registration of the firm/contractor with CPWD, MES, BRO,	
<u> </u>	RAILWAY & ODISHA PWD submitted?	
7.	Whether copy of registration of certificate registration for EPFO and certificate of	
	registration for ESIC submitted? (Declaration, if not applicable) (Failing to submit the	
0	certificates offers will be summarily rejected).	
8.	Satisfactorily completed as a prime contractor at least one similar work of 80% value or two works of atleast 60% value or 3 works of atleast 40% value. (for non – enlisted	
	contractors)	
	Bidder has to submit on-line scanned copy of certificate of Work Order along with	
	Work Completion certificate of similar nature work equal to required value during last	
	seven years issued by not below the rank of Executive Engineer.	
	Similar works means works that pertain to Construction/Repair/Maintenance of	
	Buildings.	
9.	Non-enlisted bidders are required to submit	
	(i) Either Banker's Certificate of Rs. 41.6 Lakh (Proforma as Appendix-	
	E)	
	OR	
	Net worth Certificate of Rs. 13 Lakh (proforma as Appendix-D)	
	AND	
	(ii) Average Annual Turnover Certificate of Rs. 41.6 Lakh (Proforma as	
	Appendix-C) on works during the last three financial years from a Chartered Accountant.	
	Note:- Documents should not be old more than 06 months from bid submission end	
	date.	
10.	Tenderers should mention that Business dealing with their firms has not been banned by	
	any Govt. / private agencies.	
11.	Tenderers should mention their address for communication with Telephone/Fax	
	Number and e-mail address.	
12.	Whether all the Points under heading "Terms & Conditions", "Additional Conditions"	
	and instructions are fully abided by the contractor or not?	
13.	Whether all the requisite documents as asked in tender Schedule of inviting tender notice	
1.	have been submitted by the tenderer?	
14.	Whether the firm has enclosed valid documents if the firm is a partnership proprietary	
	in nature? (If no papers submitted with the bid it will be assumed that the firm is	
15	Single/Sole Proprietary) Whother any other relevant decuments which the firms wish to submit as a part of offer?	
15.	Whether any other relevant documents which the firms wish to submit as a part of offer?	
16. 17.	Tender acceptance letter (In firm's letter head) Integrity Pact (on firm's letter head)	
1/.	megny ract (on min s tener nead)	

Membership No. of ICAI

Date and seal

FORM OF CERTIFICATE OF ANNUAL TURNOVER ON WORKS FROM CHARTERED ACCOUNTANT

Certified that following is the annual turnover on works of the individual/firm/company as per returns filed with Income Tax Department for the past 3(three) financial years.

S. No.	Financial Year	Annual Turnover on Works in Rs. lakhs
Unique Doo	cument Identification Number (U	(DIN)
		(Signature of Chartered Accountant)
		(Name of Chartered Accountant

FORM OF CERTIFICATE OF NET WORTH FROM CHARTERED ACCOUNTANT

It is to certify that as per the audited balance sheet and profit & loss account during the financial year
, the networth of Shri/Smt/M/s(Name
& Registered Address of individual/firm/company), is Rs after considering all liabilities. It is further
certified that the networth of the individual/firm/company has not eroded by more than 50% during the last
three years ending on 31st March
Unique Document Identification Number (UDIN)

(Signature of Chartered Accountant)

(Name of Chartered Accountant)

Membership No. of ICAI

Date and seal

Appendix-"E"

FORM OF BANKER'S CERTIFICATE FROM A COMMERCIAL BANK

This is to certify that to the best of our knowledge and information Shri/Smt/M/s
having registered address, a customer of our bank, is/are respectable and can be treated as
reliable for any engagement upto a limit of Rs(Rupees
This certificate is issued without any guarantee or responsibility on the Bank or any of the officers. This
certificate is issued on the request of Shri/Smt/M/S For
obtaining Works tender in CRPF in (Name of Works).
(Signature)
For the Bank

Note:

- 1. Banker's certificates should be on the letter head of the bank, addressed to enlisting authority.
- 2. In case of partnership firm, the certificate shall include names of all partners as recorded with the bank.

Appendix-"F"

UNDERTAKING

It is stated that my firm is not involved in any kind of litigation or arbitration from contracts executed by firm and also not blacklisted or debarred by any department of central/state Government & PSU in last five years from bid submission end date.

Place :- Date :-

Signature bidder (with seal)

NOTICE INVITING TENDER

The DIG (Engr), Works Dte. invites online item rate bids for & on behalf of the President of India from approved and qualified firm/contractor with CPWD, MES, BRO, RAILWAY & ODISHA PWD for SPECIAL REPAIR OF GI SHEETED ROOFING, FALSE CEILING & VARIOUS DAMAGED TILES FLOORING OF VARIOUS SEMI-PERMANENT BUILDINGS (TRAINING SOS' MESS & 06 NOS 60 MEN BARRACKS) AT 202 CoBRA, SUNABEDA, KORAPUT, ODISHA

- 1. The enlistment of the contractors should be valid on the last date of submission of bids. In case the last date of submission of tender is extended, the enlistment of contractor should be valid on the original date of submission of bids.
- 1.1 The estimated cost put to the work is Rs. 41,38,663/- (Rupees Forty One Lakh Thirty Eight Thousand Six Hundred Sixty Three) only including all taxes.
- Agreement shall be drawn with the successful bidders on prescribed form of CPWD (or other Standard Form as
 mentioned) which is available as a Govt. of India Publication and also available on website www.cpwd.gov.in.
 Bidders shall quote his rates as per various terms and conditions of the said form which will form part of the
 agreement.
- 3. The work has to be completed by within 90 days from the date of placing of Work Order or from the first date of handing over of the site, whichever is later, in accordance with the phasing, if any, indicated in the bid documents. Site of work is within the **RESTRICTED AREA**.
- 4. The site for the work is available.
- 5. The bid document consisting of plans, specifications, the schedule of quantities of various types of items to be executed and the set of terms and conditions of the contract to be complied with and other necessary documents except Standard General Conditions of Contract Form can be seen from CPP Portal (htpp://eprocure.gov.in/eprocure/app).
- After submission of the bid the contractor can re-submit revised bid any number of times but before last time and date of submission of bid as notified.
- 7. While submitting the revised bid, contractor can revise the rate of one or more item(s) any number of times (he need not re-enter rate of all the items) but before last time and date of submission of bid as notified.
- 8. Bidder should deposit earnest money with required validity along with their Tender. Earnest Money should be in form of <u>Account payee Demand Draft</u>, <u>Fixed Deposit Receipt</u>. <u>Banker's Cheque</u> from any of the commercial banks in an acceptable form in favour of THE COMMANDANT 202 CoBRA, PAYBLE AT-SBI HAL TOWNSHIP SUNABEDA, BRANCH CODE-1304]"

The Earnest Money shall be scanned and uploaded to the e-Tendering website within the period of bid submission. The physical EMD of the scanned copy of EMD uploaded shall be deposited in original at <u>Works</u> <u>Dte</u>, <u>Sec -1</u>, <u>East Block</u>, <u>Block -7</u>, <u>RK Puram</u>, <u>New Delhi - 110066</u> failing which the tender shall be rejected.

Interested contractor who wish to participate in the bid has to make following payments in the form of Demand Draft / Pay order or Banker's Cheque of any Scheduled Bank to the e-Tendering website within the period of bid submission:

- (i) Copy of Enlistment Order and other documents as specified in the press notice shall be scanned and uploaded to the e-Tendering website within the period of bid submission. Original Demand Draft of Earnest Money Deposit (EMD) shall be deposited in the office of the Works Dte, Sec -1, East Block, Block 7, RK Puram, New Delhi 110066 before the due date of submission receipt of tender bids
 - (ii) The bid/tender submitted shall be opened as per timing specified on CPP Portal.
- 9. The bid/tender submitted shall become invalid and cost of bid shall not be refunded if:-
 - I. The bidders are found ineligible.
 - II. The bidders does not upload all the documents (including Labour Licence, GST registration, EPFO & ESIC registration, PAN card and copy of registration/enlistment) as stipulated in the bid document including the undertaking about deposition of physical EMD of the scanned copy of EMD uploaded.
 - III. Any discrepancy is noticed between the documents as uploaded at the time of submission of bid and hard copies as submitted physically in the office of tender opening authority.

- The contractor whose tender is accepted will be required to deposit PERFORMANCE SECURITY for an amount of Five percent (5%) of the value of the contract within a period of 07 (SEVEN) days after the Tender is accepted by the Competent Engineering Authority. Performance Security may be furnished in the form of an Fixed Deposit Receipt from a commercial bank in an acceptable form. Performance Security should remain Valid for a period of 180 days (six months) beyond the date of completion of all contractual obligation of the supplier including warranty obligations if any. In case the contractor fails to deposit the performance security within the stipulated period including extended period, if any, the Earnest Money deposited by the contractor shall be forfeited automatically without any notice to the contractor.
 - The contractor whose bid is accepted will also be required to furnish either copy of applicable licenses/registrations or Proof of applying for obtaining labour licenses and registration with EPFO & ESIC within the period specified in Schedule-"F". Failing to submit the above certificates / documents, offers will be summarily rejected.
- 11. The reimbursement of EPF & ESI contributions paid by the contractor on the part of employer is to be made on submission of documentary proof of payment provided the same is in order.
- 12. Intending Bidders may inspect and examine the site and its surroundings and satisfy themselves before submitting their bids as to the nature of the ground and sub-soil (so far as is practicable), the form and nature of the site, the means of access to the site, the accommodation they may require and in general shall themselves obtain all necessary information as to risks, contingencies and other circumstances which may influence or affect their bid. A bidder shall be deemed to have full knowledge of the site and no extra charge consequent on any misunderstanding or otherwise shall be allowed. The bidders shall be responsible for arranging and maintaining at his own cost all materials, tools & plants, facilities for workers and all other services required for executing the work unless otherwise specifically provided for in the contract documents. Submission of a bid by a bidders implies that he has read this notice and all other contract documents and has made himself aware of the scope and specifications of the work to be done and of conditions and rates at which stores, tools and plant, etc. will be issued to him by the Government and local conditions and other factors having a bearing on the execution of the work.
- 13. The Competent Engineering Authority on behalf of the President of India does not bind itself to accept the lowest or any other bid and reserves to itself the authority to reject any or all the bids received without the assignment of any reason. All bids in which any of the prescribed condition is not fulfilled or any condition including that of conditional rebate is put forth by the bidders shall be summarily rejected.
- 14. Canvassing whether directly or indirectly, in connection with bidders is strictly prohibited and the bids submitted by the contractors who resort to canvassing will be liable for rejection.
- 15. The competent authority on behalf of President of India reserves to himself the right of accepting the whole or any part of the bid and the bidders shall be bound to perform the same at the rate quoted.
- 16. No Engineer of Gazetted Rank or other Gazetted Officer employed in Engineering or Administrative duties in an Engineering Department of the Government of India is allowed to work as a contractor for a period of one year after his retirement from Government service, without the prior permission of the Government of India in writing. This contract is liable to be cancelled if either the contractor or any of his employees is found any time to be such a person who had not obtained the permission of the Government of India as aforesaid before submission of the bid or before submission of the bid or engagement in the contractor's service.
- 17. The bid for the works shall remain open for acceptance for a period of Ninety (90)days from the end date of submission of bids, if any bidders withdraws his bid before the said period or issue of letter of acceptance, whichever is earlier, or makes any modifications in the terms and conditions of the bid which are not acceptable to the department, then the Government shall, without prejudice to any other right or remedy, be at liberty to forfeit 100% of the said earnest money as aforesaid. Further the bidders shall not be allowed to participate in the re-bidding process of the work.
- 18. This notice inviting Bid shall form a part of the contract document. The successful bidders/contractor, on acceptance of his bid by the Accepting Authority shall within 15 days from the stipulated date of start of the work, sign the contract consisting of:
 - a) The Notice Inviting Bid, all the documents including additional conditions, specifications and drawings, if any, forming part of the bid as uploaded at the time of invitation of bid and the rates quoted online at the time of submission of bid and acceptance thereof together with any correspondence leading thereto.
 - b) Standard C.P.W.D. Form 7/8 or other Standard C.P.W.D. Form as applicable.

Sd/DIG (Engr), Works Dte
For and on behalf of the President of India

GOVERNMENT OF INDIA CENTRAL RESERVE POLICE FORCE

STATE: ODISHA Work Site : 202 CoBRA, SUNABEDA, KORAPUT, ODISHA

ITEM RATE TENDER & CONTRACT FOR WORKS

TENDER FOR THE WORK OF – SPECIAL REPAIR OF GI SHEETED ROOFING, FALSE CEILING & VARIOUS DAMAGED TILES FLOORING OF VARIOUS SEMI-PERMANENT BUILDINGS (TRAINING SOs' MESS & 06 NOS 60 MEN BARRACKS) AT 202 CoBRA, SUNABEDA, KORAPUT, ODISHA

- (i) To be submitted online through website htpp://eprocure.gov.in/eprocure/app
- (ii) To be opened in online at Works Dte, Sec -1, East Block, Block 7, RK Puram, New Delhi 110066

TENDER

I/We have read and examined the Notice Inviting Tender, Schedule A, B, C, D, E & F, Specifications applicable, Drawings & Designs, General Rules and Directions, Conditions of Contract, Clauses of Contract, Special Conditions, Schedule of Rate and other documents and Rules referred to in the conditions of contract and all other contents in the tender document for the work.

I/We hereby tender for the execution of the work specified for the President of India within the time specified in Schedule-"F", viz. Schedule of Quantities and in accordance in all respects with the Specifications, Designs, Drawings and instructions in writing referred to in Rule-1 of General Rules and Directions and in Clause-11 of the Conditions of Contract and with such materials as are provided for, by and in respects in accordance with, such conditions so far as applicable.

We agree to keep the tender open for Ninety (90) days from the date of opening of tender and not to make any modifications in its terms and conditions.

A sum of Rs. 82,773/- (Rupees Eighty Two Thousand Seven Hundred Seventy Three) only is hereby forwarded in Bank Draft/ FDR of a Scheduled Bank/ Demand Draft of a scheduled bank as earnest money. If I/We, fail to furnish the prescribed performance guarantee within prescribed period, I/We agree that the said President of India or his successors, in office shall without prejudice to any other right or remedy, be at liberty to forfeit the said earnest money absolutely. Further, if I/We fail to commence work as specified, I/ We agree that President of India or the successors in office shall without prejudice to any other right or remedy available in law, be at liberty to forfeit the said performance guarantee absolutely. The said Performance Guarantee shall be a guarantee to execute all the works referred to in the tender documents upon the terms and conditions contained or referred to those in excess of that limit at the rates to be determined in accordance with the provision contained in Clause 12.2 and 12.3 of the tender form.

Further, I/We agree that in case of forfeiture of Earnest Money or Performance Guarantee as aforesaid, I/We shall be debarred for participation in the re-tendering process of the work. I/We undertake and confirm that eligible similar work(s) has/have not been got executed through another contractor on back to back basis. Further that, if such a violation comes to the notice of Department, then I/We shall be debarred for tendering in CRPF in future forever. Also, if such a violation comes to the notice of Department before date of start of work, the Engineer-in-Charge shall be free to forfeit the entire amount of Earnest Money Deposit/Performance Guarantee

I/We hereby declare that I/We shall treat the tender documents drawings and other records connected with the work as secret/confidential documents and shall not communicate information/derived there from to any person other than a person to whom I/We am/are authorized to communicate the same or use the information in any manner prejudicial to the safety & integrity of the State.

Dated: Signature of Contractor Witness: Postal Address Address:

Occupation:

ACCEPTANCE

The above tender (as modified by you as provided in the letters mentioned hereunder) is accepte me for and on behalf of the President of India for a sum of Rs. Rupees	
	.)
The letters referred to below shall form part of this contract agreement:-	
a)	
b)	
(c)	
Dated:	

Sd/DIG (Engr), Works Dte.
For and on behalf of the President of India

SCHEDULES (A TO F)

SCHEDULE -"A"

Name of work :- SPECIAL REPAIR OF GI SHEETED ROOFING, FALSE CEILING & VARIOUS DAMAGED TILES FLOORING OF VARIOUS SEMI-PERMANENT BUILDINGS (TRAINING SOS' MESS & 06 NOS 60 MEN BARRACKS) AT 202 CoBRA, SUNABEDA, KORAPUT, ODISHA

Schedule of quantities:- As per BOQ:-

SCHEDULE - "B" :-

1.2

1.3

Estimated Cost of work: -

S.No.	Description of item.	Quantity.	Rate in figures & words at which the material will issue be charged to the contractor	Place of
(1)	(2)	(3)	(4)	(5)
		N	IL	
SCHE	DULE - "C" :-			
Tools a	and plants to be hired to the co	ntractor		
S.NO.	DESCRIPTION.	HIR	RE CHARGES PER DAY	PLACE OF ISSU
		N	IL	
CONC HYDR (HYD)	ERS, PNEUMATIC WHEE CRETE PAVER FINISHE RAULICALLY CONTROLL RAULICALLY CONTROL	LED ROLLER, FU R ,CONTINUES ED SENSORS OPE LED), BULL DO	LANTS AND MACHINERY SUJLLY AUTOMATIC CONCRETE TYPE HOT MIX PLANT, PERATED ELECTRICALLY FOR TOZERS, ROAD ROLLERS, DRI	BATCHING PLAN PAVER FINISHER THE PAVE FINISHE ILLING MACHINE
CONC HYDR (HYDR CONC MIXE CONC CONC FOR APPL	ERS, PNEUMATIC WHEE CRETE PAVER FINISHE RAULICALLY CONTROLL RAULICALLY CONTROL CRETE MOBILE WEIGH R(DIESEL), VIBRATORS (CRETE CUBE TESTING CRETE BATCHING PLANT THE WORK AS PER GO ICABLE. DULE - "D":-	LED ROLLER, FUR, CONTINUES ED SENSORS OPE LED), BULL DO BATCHERS, TRA NEEDLE AND PL MACHINE(HYDI T AND ANY OTHI OD ENGINEERIN	JLLY AUTOMATIC CONCRETE TYPE HOT MIX PLANT, PERATED ELECTRICALLY FOR TOZERS, ROAD ROLLERS, DRIANSIT MIXERS ONE BAG CANATE TYPE), TRUCKS/ TIPPERS RAULICALLY OPERATED), FER TOOLS, PLANTS AND MACKED PRACTICE/RELEVANT IS-CO	BATCHING PLANDAVER FINISHER THE PAVE FINISHE ILLING MACHINE PACITY CONCRET TOTAL STATION ULLY AUTOMATICHINERY REQUIRE
CONC HYDR (HYD) CONC MIXE CONC CONC FOR APPL SCHE Extra s	ERS, PNEUMATIC WHEE CRETE PAVER FINISHE AULICALLY CONTROLL RAULICALLY CONTROLC RETE MOBILE WEIGH R(DIESEL), VIBRATORS (CRETE CUBE TESTING CRETE BATCHING PLANTHE WORK AS PER GO ICABLE.	LED ROLLER, FUR, CONTINUES ED SENSORS OPE LED), BULL DO BATCHERS, TRA NEEDLE AND PL MACHINE(HYDI T AND ANY OTHI OD ENGINEERIN	JLLY AUTOMATIC CONCRETE TYPE HOT MIX PLANT, PERATED ELECTRICALLY FOR TOZERS, ROAD ROLLERS, DRIANSIT MIXERS ONE BAG CANATE TYPE), TRUCKS/ TIPPERS RAULICALLY OPERATED), FER TOOLS, PLANTS AND MACKED PRACTICE/RELEVANT IS-CO	BATCHING PLANDAVER FINISHER THE PAVE FINISHE ILLING MACHINE PACITY CONCRET S, TOTAL STATION ULLY AUTOMATICHINERY REQUIRE CODES WHICHEVE
CONC HYDR (HYD) CONC MIXE CONC FOR APPL SCHE Extra s	LERS, PNEUMATIC WHEE CRETE PAVER FINISHE RAULICALLY CONTROLL RAULICALLY CONTROLL CRETE MOBILE WEIGH R(DIESEL), VIBRATORS (CRETE CUBE TESTING CRETE BATCHING PLANTITHE WORK AS PER GO ICABLE. DULE - "D":- schedule for specific requirement of the control of the co	LED ROLLER, FUR, CONTINUES ED SENSORS OPE LED), BULL DO BATCHERS, TRA NEEDLE AND PL MACHINE(HYDI T AND ANY OTHI OD ENGINEERIN	JLLY AUTOMATIC CONCRETE TYPE HOT MIX PLANT, PERATED ELECTRICALLY FOR TOZERS, ROAD ROLLERS, DRIANSIT MIXERS ONE BAG CANATE TYPE), TRUCKS/ TIPPERS RAULICALLY OPERATED), FER TOOLS, PLANTS AND MACKED PRACTICE/RELEVANT IS-CO	BATCHING PLAN PAVER FINISHER THE PAVE FINISHE ILLING MACHINE PACITY CONCRET S, TOTAL STATION ULLY AUTOMATI CHINERY REQUIRE CODES WHICHEVE

Earnest Money: - Rs. 82,773/- (The EMD will be returned post receipt of Performance Guarantee)

Rs. 41,38,663/-

1.4 Performance Guarantee 5% of tendered value(It shall be valid up to the stipulated date of completion Plus 180 days beyond that) 2.5 % 1.5 Security Deposit SCHEDULE- "F":-General Rules & Directions:-DIG (Engr) Officer Inviting Tender: -Maximum percentage for quantity of items of work to be executed beyond which rates are to be determined in accordance with Clauses 12.2 & 12.3 See below **Definitions:-**Engineer-In-Charge AC Engr. or Designated by DIG(Engr.) 2(v) DIG (Engr) 2(viii) Accepting Authority 2(x)Percentage on cost of Materials and labour to Cover all overheads and **Profits** 15% 2(xi) Standard Schedule of Rates DSR **CRPF** 2(xii) Department 2(xiii) Standard CPWD contract Form CPWD form 8 & General Conditions of Contract for CPWD Works-2023 with upto-date correction slips. Clause-1:-Time allowed for submission of Performance guarantee Programme Chart 07 days (Time & Progress) and from the date of issue of letter of acceptance. (ii) Maximum allowable extension Beyond the period as provided in (i) above 10 days by DIG (Engineer) Dte. Clause-1A: - Recovery of Security Deposit as per GCC:-Applicable **Clause-2:** Authority for fixing compensation under clause 2. DIG (Engr) Clause-2A:-Whether Clause 2A shall be applicable No Clause- 3:- Applicable Clause 3A:- Applicable Clause 4 :- Applicable Clause-5:- Applicable Time allowed for execution of work 90 days Authority to decide Extension of time i) DIG (Engr) ii) Rescheduling of mile stones DIG (Engr) iii) Shifting of date of start in case of delay in handing over of site DIG (Engr) Clause-6:-Computerized Measurement Book No Clause-7A:-Whether Clause 7A shall be applicable **Applicable** Clause 8:-Completion Certificate and Completion Plans **Applicable**

Completion Plans to be Submitted by the Contractor

Applicable.

Clause-8A:-

Clause-9:- Payment of Final Bill Applicable.

Clause 9A:- Payment of Contractor's Bills to Banks Applicable.

Clause-10A:- Materials to be provided by the Contractor Applicable

Clause-10-B

(i) Secured Advance on Materials
(ii) Whether Mobilization advance will be paid
No

Clause-10C:-

Payment on Account of Increase in Prices/ Wages due to Statutory Order(s)

Not applicable.

Clause-10 CA:-

Payment due to variation in prices of materials after receipt of tender Not applicable.

Clause-10-CC:-

Payment due to Increase / Decrease in Prices/ Wages (excluding materials covered under clause 10 CA) after Receipt of Tender for Works

Not applicable

Clause 10 D:-Dismantled Material Govt. Property

The contractor shall treat all materials obtained during dismantling of a structure, excavation of the site for a work, etc. as Government's property and such materials shall be disposed off to the best advantage of Government according to the instructions in writing issued by the Engineer-in-Charge.

Clause-11:- Work to be Executed in Accordance with Specifications, Drawings, Orders etc.

The contractor shall execute the whole and every part of the work in the most substantial and workmanlike manner both as regards materials and otherwise in every respect in strict accordance with the specifications. The contractor shall also conform exactly, fully and faithfully to the design, drawings and instructions in writing in respect of the work signed by the Engineer-in-Charge and the contractor shall be furnished free of charge one copy of the contract documents together with specifications, designs, drawings and instructions as are not included in the standard specifications of Central Public Works Department specified in Schedule 'F' or in any Bureau of Indian Standard or any other, published standard or code or, Schedule of Rates or any other printed publication referred to elsewhere in the contract. The contractor shall comply with the provisions of the contract and with the care and diligence execute and maintain the works and provide all labour and materials, tools and plants including for measurements and supervision of all works, structural plans and other things of temporary or permanent nature required for such execution and maintenance in so far as the necessity for providing these, is specified or is reasonably inferred from the contract. The Contractor shall take full responsibility for adequacy, suitability and safety of all the works and methods of construction.

Clause-12:-

Authority to decide deviation/extra items(As per CPWD norms) DIG (Engr)

Clause -14: - Carrying out part DIG (Engr)

work at risk & cost of

contractor(Authority to decide)

Clause-16:- Competent Authority for

deciding reduced rates. DIG (Engr)

Clause17: <u>Contractor Liable for Damages, defects during defect liability period</u>

If the contractor or his working people or servants shall break, deface, injure or destroy any part of building in which they may be working, or any building, road, road kerb, fence, enclosure, water pipe, cables, drains, electric or telephone post or wires, trees, grass or grassland, or cultivated ground contiguous to the premises on which the work or any part is being executed, or if any damage shall happen to the work while in progress, from any cause whatever or if any defect, shrinkage or other faults appear in the work within twelve months (six months in the case of work costing Rs. Ten lacs and below except road work) after a certificate final or otherwise of its completion shall have been given by the Engineer in- Charge as aforesaid arising out of defect or improper materials or workmanship the contractor shall upon receipt of a notice in writing on that behalf make the same good at his own expense or in default the Engineer-in-Charge cause the same to be made good by other workmen and deduct the expense from any sums that may be due or at any time thereafter may become due to the contractor, or from his security deposit or the proceeds of sale thereof or of a sufficient portion thereof. The security deposit of the contractor shall not be refunded before the expiry of twelve months after the issue of the certificate final or otherwise, of completion of work. Provided that in the case of road work, if in the opinion of the Engineer-in-Charge, half of the security deposit is sufficient, to

meet all liabilities of the contractor under this contract, half of the security deposit will be refundable after six months and the remaining half after twelve months of the issue of the said certificate of completion.

In case of Maintenance and Operation works of E&M services, the security deposit deducted from contractors shall be refunded within Two months from the date of final payment or within Two months from the date of completion of the maintenance contract whichever is earlier.

Clause-18:- Tools & Plants etc.

The contractor shall provide at his own cost all materials machinery, tools & plants as specified in schedule F. In addition to this, appliances, implements, other plants, ladders, cordage, tackle, scaffolding and temporary works required for the proper execution of the work, whether original, altered or substituted and whether included in the specifications or other documents forming part of the contract or referred to in these conditions or not, or in-Charge as to any matter as to which under these conditions he is entitled to be satisfied, or which he is entitled to require together with carriage therefore to and from the work. The contractor shall also supply without charge the requisite number of persons with the means and materials, examination at any time and from time to time of the work or materials. Failing his so doing, the same may be provided by the Engineer-in-Charge at the expense of the contractor and the expenses may be deducted, from any money due to the contractor, under this contract or otherwise and/or from his security deposit or the proceeds of sale thereof, or of a sufficient portions thereof.

Clause-19:- Labour Laws to be complied Applicable.

by the contractor

Clause-19A:- No labour below the age of Eighteen Applicable.

years shall be employed on the work.

Clause-19C:- Applicable.

Clause -19D:- Applicable.

Clause -19K: Employment of skilled/semi skilled workers

The contractor shall, at all stages of work, deploy skilled/semi skilled tradesmen who are qualified and possess certificate in particular trade from CPWD Training Institute/Industrial Training Institute/ National Institute of construction Management and Research (NICMAR)/ National Academy of Construction, CIDIG or any similar reputed and recognized Institute managed/ certified by State/Central Government. The number of such qualified tradesmen. The contractor shall submit number of man days required in respect of each trade, its scheduling and the list of qualified tradesmen along with requisite certificate from recognized Institute to Engineer in charge for approval. Notwithstanding such approval, if the tradesmen are found to have inadequate skill to execute the work of respective trade, the contractor shall substitute such tradesmen within two days of written notice from Engineer in-Charge. Failure on the part of contractor to obtain approval of Engineer-in-Charge or failure to deploy qualified tradesmen will attract a compensation to be paid by contractor at the rate specified in schedule 'F' per such tradesman per day. Decision of Engineer in Charge as to whether particular tradesman possesses requisite skill and amount of compensation in case of default shall be final and binding. Provided always, that the provisions of this clause, shall not be applicable for works with estimated cost put to tender

being less than Rs. 5 crores. For work costing more than Rs. 10 Crores, and uptoRs. 50 Crores, the contractor shall arrange on site training as per National Skill Development Corporation (NSDIG) norms for at least 20% of the unskilled workers engaged in the project in co-ordination with the CPWD Regional Training Institute& National Skill Development Corporation (NSDIG) for certification at the level of skilled/semi skilled tradesmen. For works costing more than Rs. 50 Crores, the contractor shall arrange on site training as per National Skill Development Corporation (NSDIG) norms for at least 30% of the unskilled

worker engaged in the project in co-ordination with the CPWD Regional Training Institute & National Skill Development Corporation (NSDIG) for certification at the level of skilled/semi skilled tradesmen. The cost of such training as stated above shall be born by the Government. The necessary space and workers shall be provided by the contractor and no claim what so ever shall be entertained.

Clause-19L:- Contribution of EPF & ESI Applicable.

Clause-20:- Minimum wages act to Applicable.

be complied with.

Clause 21:- Work not to be sublet. Action in case of in solvency

The contract shall not be assigned or sublet without the written approval of the Engineer-in Charge. And if the contractor shall assign or sublet his contract, or attempt to do so, or become insolvent or commence any insolvency proceedings or make any composition with his creditors or attempt to do so, or if any bribe, gratuity, gift, loan, perquisite, reward or advantage pecuniary or otherwise, shall either directly or indirectly, be given, promised or offered by the contractor, or any of his servants or agent to any public officer or person in the employ of Government in any way relating to his office or employment, or if any such officer or person shall become in any way directly or indirectly interested in the contract, the Engineer-in-Charge on behalf of the President of India shall have power to adopt the course specified in Clause 3 hereof in the interest of Government and in the event of such course being adopted, the consequences specified in the said Clause 3 shall ensue.

Clause 25 Settlement of Dispute by Conciliation and Arbitration

(i)	Conciliator	 IG (Works)
(ii)	Arbitrator Appointing Authority	 IG (Works)
(iii)	Place of Arbitration	 KORAPUT/NEW DELHI

Clause 28 Action where no Specifications are specified

In the case of any class of work for which there is no such specifications as referred to in Clause 11, such work shall be carried out in accordance with the Bureau of Indian Standards Specifications. In case there are no such specifications in Bureau of Indian Standards, the work shall be carried out as per manufacturers' specifications, if not available then as per state/ District Specifications. In case there are no such specifications as required above, the work shall be carried out in all respects in accordance with the instructions and requirements of the Engineer-in-Charge.

Clause 30 Water for Works

The contractor(s) shall make his/their own arrangements for water required for the work and nothing extra will be paid for the same. This will be subject to the following conditions.

- (i) That the water used by the contractor(s) shall be fit for construction purposes to the satisfaction of the Engineer-in-Charge.
- (ii) The Engineer-in-Charge shall make alternative arrangements for supply of water at the risk and cost of contractor(s) if the arrangements made by the contractor(s) for procurement of water are in the opinion of the Engineer-in-Charge, unsatisfactory.
- (iii) WATER CHARGES:- The contractor has to make its own arrangement for water supply required for execution of the work, If water is used from CRPF campus then 1% amount of tendered cost shall be levied from contractor.
- (iv) ELECTRICITY CHARGES:- The contractor has to make its own arrangement for power supply required for execution of the work, If electricity is provided by CPRF campus then charges shall be applied on contractor as decided by Engineer-in-charge.

Clause 31 Hire of Plant & Machinery

The contractor shall arrange at his own expense all tools, plant, machinery and equipment (hereinafter referred to as T&P) required for execution of the work.

Clause 32,33,34& 35 Applicable

Clause-32 Requirement of technical representative(s) and recovery rate

Sl. No.	Minimum qualification of technical representative	Minimum Experience	Designation of Technical Staff	Nos.	Rate at which recovery shall be made from the contractor in the event of not fulfilling provision of Clause 32	
					Figure	Words
1.	Graduate or Diploma Engineer	2 or 5 years (respectively) experience of similar nature	Project planning/Quality/Billing Engineer	1 of major component	Rs. 25,000/- per month	Rupees Twenty Five Thousand per month
		of works				

Assistant Engineers retired from Govt. Services who are holding Diploma will be treated at par with Graduate Engineers.

Clause 37:- No engineer of gazetted rank or other gazetted officer employed in engineering or administrative duties in an engineering department of the Government of India shall work as a contractor or employee of a contractor for a period of one year after his retirement from government service without the previous permission of Government of India in writing. This contract is liable to be cancelled if either the contractor or any of his employees is found at any time to be such a person who had not obtained the permission of Government of India as aforesaid, before submission of the tender or engagement in the contractor's service, as the case may be.

INTEGRITY PACT

To,

DIG (Engineer), Works Branch, CRPF, Dte. New Delhi.

Sub: Submission of Tender for the work of.....

Dear Sir, I/We acknowledge that CRPF is committed to follow the principles thereof as enumerated in the Integrity Agreement enclosed with the tender/bid document.

I/We agree that the Notice Inviting Tender (NIT) is an invitation to offer made on the condition that I/We will sign the enclosed integrity Agreement, which is an integral part of tender documents, failing which I/We will stand disqualified from the tendering process. I/We acknowledge that THE MAKING OF THE BID SHALL BE REGARDED AS AN UNCONDITIONAL AND ABSOLUTE ACCEPTANCE of this condition of the NIT.

I/We confirm acceptance and compliance with the Integrity Agreement in letter and spirit and further agree that execution of the said Integrity Agreement shall be separate and distinct from the main contract, which will come into existence when tender/bid is finally accepted by CRPF. I/We acknowledge and accept the duration of the Integrity Agreement, which shall be in the line with Article 1 of the enclosed Integrity Agreement.

I/We acknowledge that in the event of my/our failure to sign and accept the Integrity Agreement, while submitting the tender/bid, CRPF shall have unqualified, absolute and unfettered right to disqualify the tenderer/bidder and reject the tender/bid is accordance with terms and conditions of the tender/ bid.

Yours faithfully

(Duly authorized signatory of the Bidder)

To be signed by the bidder and same signatory competent $\!\!\!/$ authorized to sign the relevant contract on behalf of CRPF.

INTEGRITY AGREEMENT

This Integrity Agreement is made at on thisday of 20
BETWEEN
President of India represented through COMMANDANT 202 CoBRA, SUNABEDA, KORAPUT, ODISHA.
(Name of Zone) CRPF,, (Hereinafter referred as the
(Address of Office)
'Principal/Owner', which expression shall unless repugnant to the meaning or context hereof include its successors and permitted assigns) AND
(Name and Address of the Individual/firm/Company)
through
"Bidder/Contractor" and which expression shall unless repugnant to the meaning or context hereof include its successors and permitted assigns)
Preamble WHEREAS the Principal / Owner has floated the Tender (NIT No) (hereinafte referred to as "Tender/Bid") and intends to award, under laid down organizational procedure, contract for
(Name of work)
hereinafter referred to as the "Contract". AND WHEREAS the Principal/Owner values full compliance with all relevant laws of the land, rules, regulations, economic use of resources and of fairness/transparency in its relation with its Bidder(s) and Contractor(s).
AND WHEREAS to meet the purpose aforesaid both the parties have agreed to enter into this Integrity Agreement (hereinafter referred to as "Integrity Pact" or "Pact"), the terms and conditions of which shall also be read as integral part and parcel of the Tender/Bid documents and Contract between the parties.
NOW, THEREFORE, in consideration of mutual covenants contained in this Pact, the parties hereby agree as follows and this Pact witnesses as under:
IN WITNESS WHEREOF the parties have signed and executed this Integrity Pact at the place and date first above mentioned in the presence of following witnesses:
(For and on behalf of Principal/Owner)
(For and on behalf of Bidder/Contractor) WITNESSES: 1(signature, name and address)
2 (signature, name and address)
Place:
Dated:

Instructions for online Bid submission

Instructions to the Bidders to submit the bids online through the Central Public Procurement Portal for e-Procurement at https://eprocure.gov.in/eprocure/app

- 1) Possession of valid Digital Signature Certificate (DSC) and enrolment/ registration of the contractors/bidders on the e-procurement/e-tender portal is a prerequisite for e-tendering.
- Bidder should do the enrolment in the e-Procurement site using the "Click to Enrol" option available on the home page. Portal enrolment is generally free of charge. During enrolment/registration, the bidders should provide the correct/true information including valid eMail ID. All the correspondence shall be made directly with the contractors/bidders through eMail ID provided.
- 3) Bidder need to login to the site thro" their user ID / password chosen during enrolment / registration.
- 4) Then the Digital Signature Certificate (Class II or Class III Certificates with signing key usage) issued by SIFY/TCS/n-Code/ e-Mudra or any Certifying Authority recognized by CCA India on e-Token/Smart Card, should be registered.
- 5) The DSC that is registered only should be used by the bidder and should ensure safety of the same.
- 6) Contractor/Bidder may go through the tenders published on the site and download the required tender documents/ schedules for the tenders he/she is interested.
- 7) After downloading / getting the tender document/schedules, the Bidder should go through them carefully and then submit the documents as asked, otherwise bid will be rejected.
- 8) If there are any clarifications, this may be obtained online thro" the tender site, or thro" the contact details. Bidder should take into account the corrigendum published before submitting the bids online.
- 9) Bidder then logs in to the site through the secured log in by giving the user id/password chosen during enrolment/registration and then by giving the password of the e-Token/Smart Card to access DSC.
- 10) Bidder selects the tender which he/she is interested in by using the search option & then moves it to the "my tenders" folder.
- 11) From my tender folder, he selects the tender to view all the details indicated.
- 12) It is construed that the bidder has read all the terms and conditions before submitting their offer. Bidder should go through the tender schedules carefully and upload the documents as asked; otherwise, the bid will be rejected.
- Bidder, in advance, should get ready the bid documents to be submitted as indicated in the tender document/ schedule and generally, they can be in PDF/xls/rar/zip formats. If there is more than one document, they can be clubbed together and can be provided in the requested format. Each document to be uploaded through online for the tenders should be less than 2 MB. If any document is more than 2MB, it can be reduced through zip/rar and the same can be uploaded, if permitted. Bidders Bid documents may be scanned with 100 dpi with12 black and white option. However of the file size is less than 1 MB the transaction uploading time will be very fast.
- 14) If there are any clarifications, this may be obtained through the site, or during the pre-bid meeting if any. Bidder should take into account the corrigendum published from time to time before submitting the online bids.
- The Bidders can update well in advance, the documents such as certificates, annual report details etc., under My Space option and these can be selected as per tender requirements and then send along with bid documents during bid submission. This will facilitate the bid submission process faster by reducing upload time of bids.
- Bidder should submit the EMD as specified in the tender. The original should be Posted / couriered/given in person to the Tender Inviting Authority, within the bid submission due date & time for the tender. Scanned copy of the instrument should be uploaded as part of the offer.
- While submitting the bids online, the bidder reads the terms & conditions and accepts the same to proceed further to submit the bid packets.

- The bidder has to select the payment option as offline to pay the EMD as applicable and enter details of the instruments.
- 19) The details of the DD/any other accepted instrument, physically sent, should tally with the details available in the scanned copy and the data entered during bid submission time. Otherwise submitted bid will not be acceptable.
- 20) The bidder has to digitally sign and upload the required bid documents one by one as indicated. Bidders to note that the very act of using DSC for downloading the bids and uploading their offers shall be deemed to be a confirmation that they have read all sections and pages of the bid document including General conditions of contract without any exception and have understood the entire document and are clear about the requirements of the tender requirements.
- 21) The bidder has to upload the relevant files required as indicated in the cover content. In case of any irrelevant files, the bid will be rejected.
- 22) Tenderers should submit price bid in format available Annexure in CPP Portal http://eprocure.gov.in/eprocure/app and don't change the name of downloaded Annexure. Only fill the area which is available to fill and validate by the given button in Annexure, save the file and upload the file on portal.
- 23) The bidders are requested to submit the bids through online e-tendering system to the Tender Inviting Authority (TIA) well before the bid submission end date & time (as per Server System Clock). The TIA will not be held responsible for any sort of delay or the difficulties faced during the submission of bids online by the bidders at the eleventh hour.
- After the bid submission (i.e after Clicking "Freeze Bid Submission" in the portal), the acknowledgement number, given by the system should be printed by the bidder and kept as a record of evidence for online submission of bid for the particular tender and will also act as an entry pass to participate in the bid opening date.
- 25) The time settings fixed in the server side & displayed at the top of the tender site, will be valid for all actions of requesting, bid submission, bid opening etc., in the e-tender system. The bidders should follow this time during bid submission.
- All the data being entered by the bidders would be encrypted using PKI encryption techniques to ensure the secrecy of the data. The data entered will not viewable by unauthorized persons during bid submission & not be viewable by any one until the time of bid opening.
- Any bid document that is uploaded to the server is subjected to symmetric encryption using a system generated symmetric key. Further this key is subjected to asymmetric encryption using buyers/bid openers" public keys. Overall, the uploaded tender documents become readable only after the tender opening by the authorized bid openers.

ADDITIONAL TERMS AND CONDITIONS

- (i) PAYMENT:- (a) Works are required to be executed on credit basis only and payment will be released after submission of RA bill by the contractor and scrutiny by the department.
- (b) Payment in advance or immediately cannot be made.
- (c) The Payment action will be processed on production of the following documents:
- (i) Bill in Triplicate.
- (ii) A Copy of award of work.
- (iii) A copy of Certificate issued by COMMANDANT 202 CoBRA, SUNABEDA, KORAPUT, ODISHA in consultation with Engineer-in-charge that contracted work for the period for which payment has been claimed, has carried out by the contractor satisfactory.
- (d) GST/TDS/GST-TDS/ Labour Cess and other taxes will be deducted from the Bill of Contractor by RPAO as per norms. EPF & ESIC shall be reimbursed by RPAO only on submission of proof of payment by contractor to concerned authorities.
- (e) Contractor may claim RA Bills at interval of 30 days for the work done as measured and entered in measurement book. RA bill should be checked by Insp/SI (Civil) & Engineer-in-charge and countersigned by Estate Officer before release of payment. Security Deposit of 2.5% shall be retained from the Work Done in the RA Bill which will be paid after completion of Defect Liability Period.

- (ii) MEASUREMENT: Entire work done at Site shall be recorded in measurement book duly signed by Contractor &Insp/SI (Civil) & AC(Engr). Measurements in measurement book shall be recorded jointly by contractor/authorized representative of contractor and Insp/SI Civil and 50% MB checked & signed by AC(Engr) before processing bill to Estate Officer for counter sign.
- (iii) <u>COMPLETION CERTIFICATE</u>: Upon Completion of Work, Contractor shall intimate Estate Officer in writing of completion of work. If Estate Office is completely satisfied with the work, he shall issue Completion Certificate duly signed by Engineer-in-Charge (AC Engr) within 20 days of intimation of contractor. If Minor Defects Persists, Provisional Completion Certificate can be issued subject to rectification of defects brought out by Estate Officer. A suitable time frame for rectification of such defects shall also be intimated by Estate Officer in writing beyond which DIG Engineer Dte. Shall be empowered to rectify the defects through other agency at risk and cost of the contractor. This period shall not be less than 30 days and should not exceed 180 days in any case from the date of intimation of defects. Such defects list shall be made part of Provisional Completion certificate by Estate Officer.
- (iv) <u>DISPUTE IN CONTRACT:</u> In case of any ambiguity in the provisions of the Contract Agreement, Decision of Accepting Officer shall be Final & Binding on the Contractor. GCC works-2023 (construction/maintenance) with upto date correction slips will prevail and applicable.
- (v) All materials required to be used on works shall be got approved from the Engineer-in-charge in advance. In case of doubt on any material, Engineer-in-charge has right to get the material tested from any Govt. approved labs/NABL and the charges for the same shall be borne by the contractor, upto the overall amount of Rs. 02 lakh in entire work. Beyond Rs. 02 lakh, the cost of such test shall be borne by the contractor if sample fails in the test & by CRPF if sample passes the test.
- (vi) The quoted rate should be inclusive of all taxes, levies, works contract taxes, duties etc.
- (vii)All items to be used in this work should be branded and ISI certified. In this case CPWD approved list of material for similar work may be followed. If any make is not specified, decision of Engineer-in-charge shall be final and binding.
- (viii) Payment to contractor shall be released only after submission of purchase voucher of all new items.

(ix) TERMINATION OF CONTRACT:-

In case of violation/breach of any agreed terms and conditions of contract and persistently failure/negligence to observe and perform all or any of the acts, deeds, matters or things to be observed and performed by the Contractor. Tender Accepting Authority may cancel/Terminate this contract and the performance security deposit will be forfeited.

(x) CONFLICT OF INTEREST

The bids of any tenderer may be rejected if a conflict of interest between the bidder and CRPF is detected at any stage. Tender Accepting Authority reserves the right to accept or reject the tender without assigning any reason whatsoever.

- (xi) Conditional tender is not acceptable and will be summarily rejected.
- (xii) DEFECT LIABILITY PERIOD: Defect liability period is 02 years, which will be reckoned from the date of final and complete handing/taking over of building/infrastructure. If any defects occurs/noticed during this period, then a notice in this regard will be issued to the contractor and it is the responsibility of contractor to rectify/repair the defects at his own cost. The work must be got started by the contractor within 15 days after receipt of the 1st notice. If the contractor is unable or unwilling to repair the defects, the competent authorities reserves full rights to forfeit the security deposit and may blacklisted/debarred the firm and rectify the defects at risk and cost of the contractor. Any amount on this account due to the department shall be recovered from the Contractor.
- (xiii) Payment for execution of electrical works will be done only after inspection by the BOO/electrical engineer of State Electrical Department/any Govt. electrical engineer(serving) detailed by Estate Officer/Engineer-in-charge. A completion certificate is required to be submitted by the BOO/electrical engineer of State Electrical Department/any Govt. electrical engineer(serving). Any charges if occurs that will be borne by the contractor. No payment in this regard will be done by the CRPF.
- (xvi) All credit obtained during dismantling shall be deposited with CRPF.

LIST OF MAKES

<u>MATERIALS</u>: Unless specific makes/manufacturers are specified in the tender documents all the materials to be procured by the contractor for incorporation in the work under this contract (with the exception of local materials like bricks, stone aggregate, stones, sand etc) shall be with ISI certifications mark.

<u>SAMPLES OF MATERIALS:</u> The contractor shall produce samples of all materials and shall obtain approval in writing from Engineer-in-charge before he places bulk order for the materials for incorporation in the work. The contractor shall not procure materials unless the samples are first got approved from the Engineer-in-charge.

TESTING: The contractor shall submit the manufacturer's test certificate in original along with the Test Sheet giving the result of each physical test as applicable and the chemical composition of the cement or authenticated copy thereof, duly signed by the manufacturer with each consignment clearly bringing out lot No. The Engineer-in-Charge shall record these details in the Cement Supply & Acceptance register

Following mandatory tests shall be carried out for cement procured by the Contractor:

- (i) Initial and final setting time
- (ii) Soundness test
- (iii) Compressive strength test at 3, 7 & 28 days as specified in relevant IS code.

CONCRETE

MATERIALS FOR CONCRETE:-

- I. LIME: Lime shall be eminently hydraulic lime (Class 'A') and shall conform to IS:712.
- II. <u>CEMENT:</u> Cement shall be stored in dry a place covered all round and no stacks shall be more than 15 bags high.
- III. <u>COARSE AGGREGATE:</u> Coarse aggregate shall be crushed stone aggregate and shall conform to standard specifications followed in the industry.

LIST OF APPROVED MANUFACTURERS AND MAKES

S/NO.	NAME OF PRODUCT	MAKES/BRANDS/MANUFACTURERS
1	ORDINARY PORTLAND	J.K., ACC, GRASIM, GUJARAT AMBUJA, BIRLA
	CEMENT	(VIKRAM), ULTRA- TECH, J.P.REWA, VIKRAM, SHRI CEMENT, BIRLA JUTE, KHYBER& CEMENT
		CORPORATION OF INDIA.
2	REINFORCEMENT BARS	TATA STEEL (TISCON), SAIL (EQR/ SEQR), RINL,
		JINDAL (JSW NEOSTEEL/PANTHER)
3	EXPANSION JOINTS	J.SONGS, METCO, SANFIELD (INDIA) P LTD. Z-
		TECH (INDIA) PVT. LTD.
4	ADMIXTURES FOR CONCRETE	FOSROC, SIKA, MBT, ASIAN LABORATORIES
		DURA BUILD CARE, BASF, FEVICOL, CICO
		TECHNOLOGIES LTD
5	STRUCTURAL STEEL	TATA, SAIL, RINL. ISCO, SRMB
6	WELDING ELECTRODES	ESAB, ADVANI-ORLIKON, WELD ALLOY

7	WATER PROOFING	CICO, SWC, SIKA, INPRMO BY SOMCUM INDIA,
		PIDILITE, CHESEL BY OVERSEAS WATER
		PROOFING COMPOUND
8	SYNTHETIC ENAMEL PAINT	ICI (SUPER GLOCE), NEROLAC, BERGER (LUXOL),
		JENSONS AND NICHOLSON, ASIAN PAINTS
		(APCOLITE). CICO, MBT, FOSROC
9	ANTI CARBONATION PAINTS	CICO, MBT, FOSRO
10	THERMOPLASTIC PAINTS	CBM, CMS, RELIANCE THERMOPLAST
11	RMC	RMC, ACC, BIRLA, L&T AND OTHER REPUTED
		MANUFACTURE OF RMC SUBJECTED TO
10	TD 6T DE 415/500	APPROVAL OF ENGINEER-IN-CHARGE
12	TMT FE 415/500	TISCON, ISCON, RINL, SAIL, JINDAL
13	WHITE CEMENT	BIRLA WHITE, J.K. WHITE OR EQUIVALENT.
14	PUTTY	BIRLA, J.K. PUTTY OR EQUIVALENT.
15	WASH BASIN AND WC PAN	PARRYWARE, HINDWARE, JOHNSON, CERA.
16	CLEAR GLASS	MODI GUARD, SAINT GOBAIN, AIS
17	G.I. PIPES	ATUL, B.S.T, TATA STEEL TUBES, JINDAL,
		PRAKASH SURYA, APL APOLLO, NVR GI PIPE
18	G.I. FITTINGS	FITTINGS.
19	HUBLESS CENTRIFUGALLY	UNIK, KS, AMCO, AVR, NVR, RR NECO, HEPCO
19	CAST	NECO, HEPCO
	IRON SPUN PIPES & FITTINGS	
	IS:151205	
20	DI PIPES & FITTINGS	KESORAM, ELECTROSTEEL
		122 014 21., 2220 1110 01222
21	CP BRASS FITTINGS	PARRYWARE, CONTINENTAL, JAQUAR &
		HINDWARE,CERA, JIDAL, TATA, OSWAL
22	BRASS STOP & BIB COCK	ZOLOTO, SANT, L&K, LEADER, JAINKO, KALSI
		PUMP PVT LTD,DHAWAN SANITARY (PRIMA),
		CERA
23	ALUMINIUM SECTIONS	HINDALCO, JINDAL, INDIAN ALUMINIUM CO. OR
	(ANODISING BY APPROVED	AS APPROVED BY ENGINEER-IN-CHARGE
	ANODIZING FIRM)	
24	STAINLESS STEEL KITCHEN	AMC, DIAMOND, BLUE STAR, NEELKANTH,
	SINK	NIRALI, JAYNA,PRAYAG, JINDAL
25	PLASTIC W.C. SEAT COVER	PARRYWARE, HINDWARE, CERA
26	UPVC WINDOW	FENESTA, EWIN, REHAU
27	PVC TANKS	SINTEX, SUPREME, ASTREL-3 OR LAYERED MORE
		ISI MARKED OR AS APPROVED BY ENGINEER-IN-
100	L GDD OD GV 4 GG	CHARGE.
28	MIRROR GLASS	ATUL, SAINT GOBAIN & MODI GUARD, HNG,
2.2	OD WAR GETT OF THE STATE OF	GOLDEN FISH, CERA
29	CP WASTE & FLUSH PIPES	AS APPROVED BY ENGINEER-IN-CHARGE.
30	PVC FLUSHING CISTERN.	PARRYWARE, HINDWARE, JOHNSON, CERA,
21	THE FIVED / ADJECTATE	CORAL, SPEED FLO
31	TILE FIXER / ADHESIVE	AS APPROVED BY ENGINEER-IN-CHARGE.

32	VENEERED PARTICLE BOARD	NOVAPAN, KITPLY, ANCHOR, NATIONAL, ARCHIDPLY, CENTURY PLY
33	LAMINATED PARTICLE	NOVAPAN, KITPLY, NATIONAL, ARCHIDPLY,
	BOARD / LAMINTAES	CENTURY PLY, ECOBOARD.
34	FLUSH DOOR SHUTTERS	DURO, ARCHIDPLY, KUTTY FLUSH DOOR, KITPLY
		INDUSTRIES (SWASTIK), CENTURY PLY.OR AS
		APPROVED BY ENGINEER-IN- CHARGE
35	FACTORY MADE PANELLED &	AS APPROVED BY ENGINEER-IN-CHARGE
	WIRE GAUGE WOODEN DOOR/	
	WINDOW SHUTTERS	
36	STEEL WINDOWS / PRESSED	AS APPROVED BY ENGINEER-IN-CHARGE.
	STEEL FRAMES	
37	M.S PIPE	TATA, JINDAL, BHUSHAN INDUSTRIES, PRAKASH
		STEEL TUBES, OR AS APPROVED BY ENGINEER-
		IN-CHARGE
38	PVC PIPE & FITTINGS	SUPREME, AKG, FINOLEX, PRINCE, KISAN, SFMC,
		DIPLAST, RAVINDRA. HEAVY DENSITY
39	ACRYLIC DISTEMPER	NEROLAC, BERGER (BISION ACRYLIC) ASIAN
		PAINTS (TRACTOR ACRYLIC) IST QUALITY,
		DULUX WEATHER SHIELD, ICI
40	DRY DISTEMPER	BERGER (CASTLE), JENSON & NICHOLSEN (J&N)
41	STEEL PRIMER	ICI, NEROLAC, BERGER, ASIAN PAINTS. IST
		QUALITY
42	WOOD PRIMER	ICI, NEROLAC, BERGER, ASIAN PAINTS. IST
		QUALITY
43	MOSAIC TITLES / CHEQUERED TILES	HINDUSTAN, JONSON, NITCO, MODERN, NTC, A-1
44	A) CERAMIC WALL TILES (300	B) MATT FINISH FLOOR TILES.
	X450 MM) B) MATT FINISH	KAJARIA, NITCO, SOMANY, ORIENT 1ST
	FLOOR TILES	QUALITY, JOHNSON, ASIAN
45	DASH / ANCHORING	HILTI / FISCHER
	FASTENERS	
46	NUTS / BOLTS & SCREWS	GKW, ATUL
47	FLOAT VALVE	IVC, LEADER, PRAYAG, KALSI PUMP PVT LTD,
		DHAWAN SANITARY UDYOG (PRIMA) OR AS
		APPROVED BY ENGINEER-IN-CHARGE
48	CP FITTINGS/MIXER PILLAR	KINGSTON,,JAL, SEIKO, ESS, GEM, PARKO,
	TAP WASHERS	TECHNO, GRAFFTI, ESSCO, JAQUAR, HINDWARE,
		PARRYWARE, CERA, PRAYAG, MARC OR AS
		APPROVED BY ENGINEER-IN-CHARGE
49	CP ACCESSORIES	KINGSTON,,JAL, SEIKO, ESS, GEM, PARKO,
		TECHNO, GRAFFTI, ESSCO, JAQUAR, HINDWARE,
		PARRYWARE, CERA, PRAYAG, MARC OR AS
50	CIGINGE VALVES & PER SY	APPROVED BY ENGINEER-IN-CHARGE
50	C.I SLUICE VALVES & REFLEX	ANNAPURNA OR AS APPROVED BY ENGINEER-IN-
7.1	VALVES CATE VALVES	CHARGE
51	GUN METAL GATE VALVES,	LEADER, ZOLOTO, KILBURN, CIM VALVES, SANT,
	GLOBES	KIRLOSKER, L&T OR AS APPROVED BY
		ENGINEER-IN-CHARGE

52 STONE WARE PIPES & GULLY TRAPES APPROVED BY ENGINEER-IN-CHARGE 53 GLAZED FIRE CLAY KITCHEN SINK ENGINEER-IN- CHARGE 54 VITRIFIED TILES NITCO, JOHNSON, ASIAN, MARBITO, V ORIENT BELL, KAJARIA, SOMANY	OVED BY
53 GLAZED FIRE CLAY KITCHEN PAMINI, SANFIRE, RKCP OR AS APPRO SINK ENGINEER-IN- CHARGE 54 VITRIFIED TILES NITCO, JOHNSON, ASIAN, MARBITO, V	OVED BY
SINK ENGINEER-IN- CHARGE 54 VITRIFIED TILES NITCO, JOHNSON, ASIAN, MARBITO, V	
54 VITRIFIED TILES NITCO, JOHNSON, ASIAN, MARBITO, V	ADMODA
OKIENT BELL, KAJAKIA, SOMANT	ARMORA,
55 WATER METER PRIMA (ISI), KRANTI, DASHMESH OR E	DIC
MARKED PRODUCT)13
56 GROUNTING COMPOUND ENDURA, PIDILITE OR AS APPROVED I	pv
ENGINEER-IN-CHARGE	ы
57 GLASS MOSAIC TILES ITALIA, OPIO OR AS APPROVED BY EN	IGINEER_IN_
CHARGE	OII VEEK-II V-
58 PAVER BLOCKS & CURVE NITCO PREFEB, ULTRA KK, TERRAFIR	MΔ
STONES UNISTONE, UNITILE, NTC, ISI MARKEI	*
APPROVED BY ENGINEER-	<i>31</i> 10
59 GLASS MOSAIC TILES ITALIA, OPIO OR AS APPROVED BY EN	IGINEER-IN-
CHARGE	(GII (EEIC II (
60 NON RETURN VALVE (CHECK KALSI PUMP PVT. LTD, ZOLOTO, SAKA	ARAL UNIK
VALVE)1/2" TO 1/4" OR BIS APPROVED PRODUCTS.	iru iz, orviri
61 LINE FILTER VALVE 1/2" TO 2" KALSI PUMP PVT. LTD OR BIS APPROV	/ED
PRODUCTS.	22
62 FERRULES 15 MM, 20MM & 25 DHAWAN SANITARY UDYOG (PRIMA)	OR BIS
MM APPROVED PRODUCTS	
63 STAINLESS STEEL STAIRCASE JINDAL S S LTD, ICICH INDUS, ESSAL,	DORMA OR
RAILING AS APPROVED BY ENGINEER-IN-CHAR	
64 LOCKS/LATCH/FITTINGS GODREJ, HARRISON, PLAZA, GOLDEN,	
DORMA	,
65 HYDRAULIC DOOR CLOSER / HARDWYN, GODREJ, GRACE, EVERES	T, DORMA
FLOOR SPRING	
66 FIRE CHECK DOOR NAVAIR, ROMAT, KUTTY DOOR	
67 ANODISED ALUMINUM HARDIMA, EVERITE, SIGMA (ISI MARK	KED),
HARDWARE (HEAVY DUTY) DORMA	
68 TEMPERED GLASS MODI FLAT & SAINT GOBAIN, ASHAHI	I,
GLAVERBEL	
69 POLYSTER POWDER COATING NEROLAC, BERGER, J&N	
SHADES	
70 FRICTION STAY HINGES EARL-BIHARI OR AS APPROVED BY EN	NGINEER-
IN-CHARGE	
71 NUTS, BOLTS AND SCREWS, KUNDAN PRIYA ATUL OR AS APPROV	ED BY
STEEL ENGINEER-IN-CHARGE	
72 EPDM GASKET HANU / ANAND OR AS APPROVED BY	ENGINEER-
IN-CHARGE	
73 STRUCTURAL SILICON DOW CORNING / WACKER	
74 WEATHER SILICON DOW CORNING / WACKER	
75 COPPER TUBES / PIPES RAJCO, MAX FLOW ABC	
76 COPPER FITTINGS YORKSHINE, IBP, BCONEX	
77 MINERAL FIBRE FALSE MONAD, ARM STRONG OR EQUIVALE	NT AS PER
CEILING RELEVANT IS CODE	

78	METALIC (GI) POWDER	MONAD, LUXALON, DAIKEN
/6	COATED FALSE CEILING TILE	WONAD, LUAALON, DAIKLN
79	U-PVC PIPE	FLOW GUARD, PRINCE, GREEN LINE OR BIS
19	U-FVC FIFE	APPROVED PRODUCTS HEAVY DUTY
90	C-PVC PIPE AND FITTINGS	
80	C-PVC PIPE AND FITTINGS	PEARL, ASTRAL, ASHIRVAD, AJAY INDL, PRINCE
0.1	CEL VENTE DA CED DA DIT	HEAVY DUTY
81	CEMENT BASED PAINT	M/S SNOWCEM INDIA LTD, ASIAN, BURGER,
0.2	ALLE MAIN CALIBRIC DOOR	DELUXE
82	ALUMINUM SLIDING DOOR	PILOT AND AODI. OR AS APPROVED BY
0.2	BOLT, TOWER BOLT HANDLE.	ENGINEER-IN-CHARGE
83	VITREOUS CHINA SANITARY	PARRYWARE, NEYCER,CERA, HINDWARE
	WARE	
84	CENTRIFUGALLY SAND CAST	NECO OR ANY OTHER AND FITTINGS B.I.S
	(SPUN) IRON PIPES	MARKED PRODUCT, BABULAL BAJAJ IRON
		FOUNDRY MATHURA (HIF) OR BIS APPROVED
		PRODUCTS
85	CENTRIFUGALLY CAST	ELECTRO STEEL, KESORAM (CLASS LA)
	(SPUN) PIPE	
86	APP SHEET	SALIMAR, DR FIXIT, SIKKA OR AS APPROVED BY
		ENGINEER-IN- CHARGE
87	PVC DOOR SHUTTER & FRAME	SYNTEX, RAJSHREE OR AS APPROVED BY
		ENGINEER-IN-CHARGE
88	PRE-COATED PROFILE SHEET	TATA, JSW OR EQUIVALENT
89	HDF LAMINATED BOARD	ACTION TESA, CENTURY OR AS APPROVED BY
		ENGINEER-IN- CHARGE
90	BITUMEN	HPL, COAL INDIA, IOCL OR AS APPROVED BY
		ENGINEER-IN- CHARGE
91	ACP SHEET	REYNOBOND, VIRGO ACP, ALEX PANELS,
		ALUDECOR OR AS APPROVED BY ENGINEER-IN-
		CHARGE
92	LED LIGHT FITTING &	WIPRO, C&S ELECTRIC, PHILIPS, CROMPTON,
	LUMINARIES FOR ROAD AND	BAJAJ, OSRAM
	STREET LIGHTING	
	(OUT DOOR)	
93	LED LAMPS	WIPRO, PHILIPS, CROMPTON, BAJAJ, OSRAM,
		HAVELLS
94	SMART STREET LIGHTS AND	ORIENT ELECTRIC LTD, OPULUS, HAVELLS
	CONTROL SYSTEM	
95	STREET LIGHT FITTING &	POLYCAB, HAVELLS, C&S ELECTRIC, SURYA,
	ACCESSORIES -HPSC (70/ 150/	WIPRO
	250/ 400) HPMV (80/ 125/ 250/	
	400)	
96	SOLAR STREET LIGHT	JILCO, PHILLIPS, OSRAM
	FITTINGS	
97	STREET LIGHT TIMERS	SINETRAC, INDO ASIAN, HAVELLS
98	CI PIPES & FITTINGS	JINDAL, TATA METALIKS, TATA KUBOTA
99	INTERLOCKING TILES/ PAVER	ISI MARKED GLOSSY FINISH
	BLOCKS	
L		

100	DECORATIVE PAINT (EXT &	SNOWCEM, ASIAN, BERGER, DULUX
100	INT)	SIVO WELLIN, RISH INV, BERGER, BOECH
101	CHAIN LINK FENCING /	A-1 FENCE, ARMOSTRONG WIRES, MAIMOM
101	BARBED WIRE / PUNCHED	ROGER
	TAPE CONCERTINA COIL /	ROGER
	RAZOR BLADE TAPE FENCING	
102	GALVALUME SHEET	TATA BLUE SCOPE
102	GALVALOWE SHEET	/JSW/BHUSHAN/VARDHMAN
102	NON CUIDAUTRIEIED/CLAZED	
103	NON SKID/VITRIFIED/GLAZED TILES	1ST QUALITY OF JOHNSON TILES/ NITCO/ CERA/ KAJARIA.
104		
104	CHROMIUM PLATED	JAQUAR /KOHLER/ROCA/GROHE
	BATHROOM	
	FITTINGS OF CP, CAST	
	COPPER ALLOY FANCY TYPE	
	BIB TAP, STOP VALVES AND	
	PILLAR TAP, SANITARY	
	FITTINGS, SHOWER PNAEL	
105	VITREOUS CHINA WC / WHB /	PARRYWARE /CERA/ JAQUAR
	URINAL / SOAP DISH / URINAL	
	PARTITION WALL /	
	LABORATORY SINK	
106	NON ASBESTOSFIBRE	ARMSTRONG / SAINT GOBAIN (GYPROC) /
	CEMENT BOARDAS PER IS	EVEREST /INDIA GYPSUM/
	14862	
107	ACRYLIC EMULSION /	ASIAN PAINTS (ROYAL) / BERGER (LUXOL SILK
	WEATHER PROOF PAINT	SPLENDER)/ ICI (DULUX VELVET TOUCH)
108	PLASTIC EMULSION PAINT	ACROCEM / DUROCEM / SUPER SNOWCEM /
		BERGER / ASIAN PAINT
		(GUTUCAM)
109	HOUSE WIRING CABLE (1100	HAVELLS/ RR KABEL/ FINOLEX/RPG
	VOLTS)/CABLE FOR SERVICE	
	CONNECTION/CABLE FOR	
	PANEL BARD WIRING	
110	PIANO SWITCHES/SOCKETS	ISI MARKED PRODUCTS OF LEGRAND/
	ETC.	SCHNEIDER/PHILLIPS/ANCHOR (MODULAR TYPE)
111	PVC CASING CAPPING /	FINOLEX / MODI / PRESTO PLAST / PLAZA /
	CONDUIT	KALINGA/ RICHA
112	WIRING ACCESSORIES AND	ANCHOR/ HAVELLS/ LEGRAND/ KINJAL (ISI
	FITTINGS	MARKED)/ RICHA
113	MCBS, DBS, ISOLATOR	LEGRAND /SIEMENS/ SCHNIEDER/ ABB.
114	MCCB	ABB/ LEGRAND/ SCHNEIDER/ SIEMENS
115	LT UG/SERVICE CABLE	HAVELLS/FINOLEX/KEC
116	EXHAUST FAN/CEILING FAN	CROMPTON
110	Zimiooi imvehiliito imv	GREAVES/KHAITAN/BAJAJ/HAVELLS/ORIENT
117	HEATER WATER STORAGE	CROMPTON GREAVES /BAJAJ/HAVELLS
11/	TYPE ELECTRIC GEYSER	CROWN TON ORLAVES / DAJAJ/HAVELLS
118	FALSE CEILING	ARMSTRONG/ EVEREST/GYPROC
119	EPOXY PAINT	NEROLAC OR EQUIVALENT

120	CC KERB STONE	NITCO PREFAB, K.K. MANHOLE, TERRAFIRMA,
		UNISTONE.
121	MILD STEEL TUBES	TATA, SAIL, ISCO, SRMB
122	APP MEMBRANE	ASIAN PAINTS/FOSROC/SIKA/STP
123	GLOW STUD	TATA BP/3M India or Equivalent

Raw material source to be approved by the Engineer-in-Charge.

Remarks:- Any change in the brands mentioned above and elsewhere shall be allowed only after approval of the Engineer-in-charge.

PARTICULAR SPECIFICATIONS

GENERAL

Work under this contract shall be carried out in accordance with Specifications, drawings, General Specifications and other provisions contained in CPWD Manuals and Specifications General Rules, specifications, special conditions and all preambles in the CPWD Schedule shall be deemed to be applicable to the work under this contract, unless specifically stated otherwise in these documents and in case of any conflicting provisions in CPWD schedule and in these tender documents, the provisions in these documents shall take precedence over the aforesaid provisions in the CPWD Schedule. The term "as specified" wherever appears in the tender documents and drawings, relates to relevant particular specifications and in its absence, general specifications. Where specifications for any item of work are not given in CPWD Schedule or in these particular specifications, specifications as given in relevant Indian Standard Code of Practice shall be followed. Unit rate quoted by the tenderer shall be deemed to include for any minor details/items of work and/or constructions which are obviously and fairly intended and which may not have been included in these documents but which are essential for the execution and entire completion of work. Decision of the Accepting Officer as to whether any minor detail of work and/or construction is obviously and fairly intended to be included in the contract or not, shall be final, conclusive and binding.

LOCAL MATERIALS:

Irrespective of actual distance involved, local materials such as stones, aggregates, sand, road metals etc shall conform to or superior to the specifications given here in after and to the samples kept in the office of Executing Officer. The tenderers are advised to inspect these samples. The tenderers shall be deemed to have inspected the samples and have full knowledge thereof whether they inspect them or not before quoting their tender.

SAMPLES OF MATERIALS: -

- (a) Specific requirements regarding dimensions, strength, weight and finishes, as per IS, CPWD Specification and the particular specifications given hereinafter vis-à-vis actual properties check, tests carried out, reference to test certificates and markings, etc based on which samples of each materials are approved as Conforming to relevant specification shall be recorded in the sample approval register.
- (b) The contractor shall produce samples of all materials and shall obtain approval in writing from Engineer-incharge before he places bulk order for the materials for incorporation in the work. The contractor shall not procure materials unless the samples are first got approved from the Engineer-in-charge.
- (c) Samples of approved materials shall be kept in custody of Engineer-in-Charge till completion of work.

RECORD OF MATERIALS

- (a) The quantity of all the proprietary materials (including materials and quantity of which cannot be checked after incorporation in the works) shall be recorded in measurement books and signed by the Contractor, the Engineer-in-Charge and Insp/SI (Civil) as a check to ensure that the required quantity has been brought at site for incorporation in the work.
- (b) Materials brought to site shall be stored as directed by the Engineer-in-Charge and shall be suitably marked for identification.
- (c) The contractor shall procure all the materials (where specific makes/manufacturer's specified) directly from their manufacturers or from their authorised dealers only. The contractor shall ensure that the materials are brought to site in original sealed containers/packing bearing manufacturers marking except in the case of the requirement of material(s) being less than smallest packing.

(d) The contractor shall produce to Engr-in-charge original printed and machine numbered purchase vouchers/invoices including manufacturer's test certificate (where applicable) for all the materials mentioned. Copies of orders placed on the manufacturer/authorised dealers shall also be provided by the contractor to Engr-in-Charge along with above documents. Whenever procured and brought to site of work for incorporation in the work, a Xerox copy of such vouchers/invoices shall be stamped (office stamp) and defaced in ink by the Engineer-in-Charge &Insp/SI (Civil) stating verified for materials purchased and brought to the site of work for incorporation in the subject work and signed with date before allowing payment for these materials through RA Bills.

STANDARD OF WORKMANSHIP

To determine the acceptable standard of workmanship and fittings, wiring etc, the Engr-in-charge shall order the contractor to execute certain typical portion of work (different trades) and services sufficiently in advance of other work. These shall be executed and completed under the close supervision of the Engineer-in-charge and Insp/SI(Civil).

On approval by the Engineer-in-charge of such items, these items shall signed and/or suitably identified by the Engineer-in-charge and labelled as guiding samples. The record of such inspection and passing of each stage of these samples shall be recorded by Engineer-in-charge_under his dated signatures. Work on such sample shall be progressed well ahead (minimum two stages ahead). Approved finishes/workmanship shall be followed in the work as a whole.

TESTING OF CEMENT

The Engr-in-charge shall also organize independent testing of random samples of cement (both physical and chemical properties) drawn from various lots for each consignment to cement brought out by the contractor before incorporation in the work from the National Test House, SEMT, Regional Research Laboratories, Government approved laboratories, as per IS: 3535 (Method of sampling Hydraulic cement), IS: 4031 (Method of physical test for Hydraulic Cement) and IS: 4032 (Method of chemical analysis of Hydraulic cement.)The cement shall conform to chemical requirements and physical requirements as specified in respective IS. The tests carried out as per provisions of IS codes specified herein before shall be the criteria for acceptance of cement by Engr-in-Charge &Insp/SI(Civil). If samples from a lot/lots are not within the acceptance limits of Indian standard the lot/lots shall be rejected without any claims or compensation to the contractor for the lot/lots purchased. The contractor shall replace the lot/lots with the fresh one, which shall be tested again for acceptance. The cost of all tests carried out on cement before acceptance for incorporation in the work shall be borne by the contractor whether the results are acceptable or not.

STORAGE

Cement shall be stored over dry platform at least 20cm high in such a manner as to prevent deterioration due to moisture or intrusion of foreign matter. In case of store rooms, the stock should be at least 20cm above from floors and 60 cm away from walls in addition to precautions specified in Works Manuals. Inspections shall be carried out once a day by the Engineer-in-Charge & Insp/SI(Civil). It shall be ensured by the Engineer-in-Charge that tested and untested cement are segregated and stored separately with distinct identification. The cement go-down shall be provided with two locks on each door. The key of one lock at each door shall remain with the Engineer-in-Charge or his representative and that of the other lock with the contractor's authorized representative at site of works so that cement is removed from the go-down only according to daily requirement with the knowledge of both the parties.

DOCUMENTATION

The contractor shall submit original vouchers from the supplier for the total quantity of cement supplied under each consignment to be incorporated in the work. All consignments received at the work site shall be inspected by Engrincharge &Insp/SI(Civil)along with the relevant documents before acceptance. The original vouchers and the Test Certificates shall be defaced by the Engineer-in Charge &Insp/SI(Civil) and kept on record duly authenticated and with cross-reference to the control number in the cement Supply & Acceptance Register. The cement supply & Acceptance Register will be signed by Insp/SI(Civil), Engineer-in-Charge and the Contractor. The Accepting Officer may order a Board of Officers for random check of cement and verification of connected documents. The entire quantity of all types cement shall also be suitably recorded in the Measurement Book for record purpose not to be abstracted before incorporation in the work and shall be signed by the Engineer-in-Charge, Insp/SI(Civil) and the contractor.

SCHEDULING OF SUPPLY

Schedule of procurement of cement shall be finalized by the contractor with Engr-in-charge and shall be incorporated in the CPM chart so that procurement is in accordance with the progress contemplated in the CPM prepared. The complete

requirement of cement shall be worked out before making any RA Bill payment and procurement of cement by the contractor shall be completed sufficiently in advance of the execution of work.

SAND(Coarse & Fine)

Sand for all concrete work shall be M-sand and /or Badarpur river sand (from near area or any other Sand) conforming to samples, complying with the requirement as specified in CPWD. Sand in the zone II grading may also be permitted provided mix design is done and the requisite strength of the concrete is achieved.

Note: Wherever M-sand has been specified in the tender documents, the Contractor shall be permitted to use Badarpur sand (from near area) at his own cost, if he so desire due to inadequate supply/non availability of M-Sand. No price adjustment shall be made on this account. Sample of sand shall however, be got approved from the Engr-in-charge &Insp/SI(Civil) before incorporation in the work. Other provisions in the respective clauses shall remain unchanged.

CONCRETE MIX

All mixes of concrete and mortar mentioned in this tender document shall be by volume except design mix concrete conforming to IS-456 for which all the ingredients are proportioned and mixed by weight.

STEEL AND IRON WORK

General:- All items of steel which are required for the work under this contract shall be procured supplied and incorporated in the work by the contractor under his own arrangement.

Grades and Quality

Steel supplied by the contractor shall conform to the following grades and quality. Structural steel

- (i) Structural steel wherever mentioned shall be conforming to Fe 550 Gde conforming to IS-2062.
- (ii) General purpose steel wherever mentioned shall be conforming E-165(Fe-290) conforming toIS-2062.
- (b) The contractor shall within 15 days of placing of work order indicate the source for procurement of steel to Engineer-in-charge in writing.
- (c) However, steel sections for railing, gates, fencing, guard bars, grills steel chowkats, hold fast etc, which do not constitute structural members, can be procured from main producers/secondary producer/BIS marked manufacturers or their authorized dealers at the option of contractor
- (d) The contractor shall produce original vouchers from suppliers for the total quantity of steel purchased, under each consignment and be kept on record by Engineer-in-Charge and authenticated.

Testing and Test Certificate

- (a) The contractor shall produce manufacturers test certificate in original along with the test sheet giving the result of each mechanical test as applicable and the chemical composition of the steel supplied as specified in relevant IS Codes, duly signed by the manufacturer of their authorized dealers with each consignment.
- (b) The original test certificate shall be kept on record in the office of Engineer-in-Charge(AC Engr).
- (c) Independent testing of structural steel by the Engineer-in-Charge shall be mandatory in case of procurement from secondary producers and testing charges shall be borne by the Contractor irrespective of the outcome of test results.
- (d) In both the cases at sub para (c) and (d) above, the contractor at his cost shall provide all facilities required for the testing and cost consumed in tests shall be borne by the contractor.

Minimum frequency of testing for each source and each consignment

- (a) Structural Steel: -
- (i) Tensile test: One sample(3 specimen) for each test for every 25 tonnes or part thereof.
- (ii) Bend test: One sample(3 specimen) for each test for every 10 tonnes or part thereof.

- (b) Steel for concrete reinforcement: -
- (i)Bar size less than 10mm: One sample(3 specimen) for each test for every 25 tonnes or part thereof.
- (ii)Bar size 10mm to 16mm (inclusive): One sample(3 specimen) for each test for every 35 tonnes or part thereof
- (iii) Bar size over 16mm: One sample(3 specimen) for each test for every 45 tonnes or part thereof.
- (c) Bend test and tensile test for structural steel shall be carried as per IS-226 of 1975. For high strength deformed bar tensile, bend test and rebend test shall be done as per IS-1786 of 1985. For MS bars tensile and bend test shall be carried out as per IS 432 of 1982.
- (d) Engineer-in-Charge has the right to get one more sample (3 specimen) tested if he is not satisfied with test result of the consignment.
- (e) If the test results as per manufacturer's test certificate or of independent testing of random samples are not as per criteria laid down in the relevant BIS provisions, the entire consignment which is represented by the samples shall be rejected. Such rejected materials shall be removed and replaced by the contractor at his own cost forthwith.
- (f) Cost of transportation of samples to the approved laboratory/test house and all testing charges shall be borne by the contractor.

Storage: - Steel supplied by the contractor shall be stored in accordance with the requirement of IS. Each grade and quality of steel shall be stored separately and have identification tags indicating the source, quality and grade.

Preservation and maintenance of steel: The steel brought by the contractor shall be preserve do ensure that no rusting takes place till it is incorporated in the works.

Schedule of Supply :- The contractor shall procure the steel sections, timely as required in accordance with CPM Chart, agreed between Engr-in-charge and contractor. The contractor will forego his right to demand extension of time if the supply of steel got delayed due to his failure in placing order in time to the manufacturer/supplier.

Payment :-. Payment shall allowed after production of test certificate and original paid/purchase vouchers by the contractor.

Measurement

(a) The entire quantity of steel brought to site shall be recorded in measurement book as "NOT TO BE ABSTRACTED" indicating the reference to manufacturers, source of supply voucher number and test certificate before incorporation in the work and shall be signed both by the Engineer-in-Charge and the contractor. Proper documentation/record shall be maintained as per the instructions on the subject.

Normal waste and off cuts shall be stacked neatly which shall be the property of the Contractor. Contractor shall be allowed to remove such cut pieces after inspection and certifications by the Engineer-in-Charge.

Advance on account of payment made towards these cut pieces shall be recovered from advance on account of payment immediately falling due and before removal of such cut pieces from site.

Bending and fixing of bars for concrete reinforcement including mild steel wire for binding shall be carried out all as specified in CPWD. Binding wire for reinforcement shall be mild steel wire(annealed) of size not less than 0.9mm.

Steel supply/Acceptance form:- For each consignment of steel supply/acceptance form will be filled in and jointly signed by the department Rep.(Engineer-in-Charge/SI civil/Insp Civil) and contractor and accepted/rejected by Engineer-in-Charge before incorporation in the works.

Steel Reinforcement :- Reinforcement shall be fabricated, placed in position all as specified in CPWD specifications.

Guard Bars/Grills:

MS Guard bars/grills wherever applicable and as indicated shall be provided to wooden/steel windows/ventilators as per details shown on drawings/schedule. Steel Guard bars/ steel grills shall be painted with 2 coats of synthetic enamel paint over a coat of primer as specified here-in-after.

Hold Fasts/Lugs: Flat iron hold fast/lugs shall be provided by welding as and where shown on drawings except those, to be provided to wooden chowkats, which shall be fixed with screws as per details shown on drawings. Hold fasts/lugs shall be embedded in PCC(1:3:6) bed blocks of size 220mmx220mmx75mm in one brick thick walls and 100mmx220mmx75mm in half brick thick walls..

FLOORING

General adopted for laying floors and pavements.

Floors shall be laid to levels and as directed by the Engineer-in-Charge.

Floor topping of cast-in-situ cement concrete shall be finished even and smooth using extra cement as specified in CPWD specifications.

Pozzzolana or pozzolana slag cement shall not be used for floor topping.

Floor finish over RCC slabs shall be laid all as specified.

Sub floor may not be laid in panels. The thickness of sub base concrete shall be as indicated in schedule.

CEMENT CONCRETE FLOORS:- PCC floors shall be provided as indicated in Schedule.

VITRIFIED TILES FLOORING

Where vitrified tiles specified on Schedules provide coloured vitrified tiles of size as specified in the schedule and shall be laid and jointed pointed with white cement paste & pigment. Tiles shall confirm to IS -15622-2006.

The tiles shall be first quality product procured from any of the manufacturers as listed in list of manufacturers Laying jointing and finishing shall be all as per manufactures guidance/ instructions.

The colour of tiles shall be as decided by Estate Officer and Engineer-in-Charge.

KOTA STONE SLAB FLOORING

Kota stone shall be hard, durable, regular in shape, of uniform colour and free from cracks, decay and weathering. It shall be set, jointed and pointed in neat cement slurry mixed with pigment to match with the colour of stone. The slabs used in one location shall be of uniform size and shall be laid over cement screed as indicated. Kota stone slabs shall be machine cut and true fine cut dressing on all sides up to full depth. All angles and edges shall be true, square, free from chipping and surface shall be true and plain. The joints of the tiles shall not be more than 1mm.Laying, polishing and finishing of kota stone shall be all as specified.

GLAZED CERAMIC TILE DADO

The ceramic dado shall be provided with ceramic tiles of size as specified in BOQ and shall be glazed quality colour and/or white as indicated in BOQ and conforming to relevant IS specifications.

The tiles shall be jointed and pointed with white or coloured cement to match with the colour of tiles. The tiles shall be laid over cement mortar screed as specified in BOQ.

GRANITE FLOORING/CILL

It shall be all as described on Schedule. Granite slab shall be machine cut, pre-polished, over cement screed 15mm thick in CM 1:6 over 25mm thick PCC 1:2:4 using 12.5mm aggregate over RCC slab or as per BOQ.

<u>WHITE MARBLE TILE</u>: 20mm thick makrana white marble tile shall be laid over cement screed CM 1:4,15mm thick jointed with grey cement slurry mixed with pigment to match the shades of slab used as the boarder to kota slab flooring.

CERAMIC FLOOR/WALL TILES

Where Non-skid ceramic tiles specified on Schedules provide coloured non-skid ceramic tiles of size as specified in the schedule, as per Gde B II (a) shall be laid and jointed pointed with white cement paste& pigment. Tiles shall confirm to IS – 15622-2006.

The tiles shall be first quality product procured from any of the manufacturers as listed in list of manufacturers here-in-below.

Laying jointing and finishing shall be all as per manufactures guidance/ instructions.

The colour of ceramic tiles shall be as decided by Estate Officer and Engineer-in-Charge.

PLASTERING AND POINTING GENERAL

Cement: Refer to specifications and list as mentioned above.

Fine aggregate for plastering and pointing work shall be river sand conform to IS 1542-1992and as specified in Clause 14.5 to 14.5.2 of SSR Part I. Sand shall be obtained from sources as approved by Engineer-in-Charge.

Particular attention of the contractor is invited to take note of local practices and the local availability of materials like bricks form work etc and cater for any extra quantities of mortar required for rendering smooth for extra dubbing required for touching up properly and for smooth and even surfaces.

This shall be deemed to have been included in the lump sum.

Plaster and skirting/dado shall be returned in jambs, soffits of lintels and windows cills etc.

All plastered surface shall be trowel led to a smooth and even surfaces, without using extra cement.

Thickness of cement plaster mentioned hereinafter shall be finished thickness exclusive of dubbing. Dubbing may however be done in one operation with plaster.

Plaster on external surface shall be carried out upto 15cm below ground level or as per BOQ except where plinth protection/ramp etc are provided.

All corners, angles, junctions and riser shall be truly vertical or horizontal as the case may be and shall be carefully finished. Corners around jabs of openings and junction of walls shall be finished straight and square. 12mmwide groove at the junction of wall and RCC slabs to the entire thickness of wall plaster shall be provided. Also trowel groove shall be provided at junction of walls and RCC columns or any other dissimilar material e.g. wooden chowkhats etc.

Plastering shall be carried out all as specified in Schedule 'A'.

OIL EMULSION DISTEMPER

Distemper shall be applied as specified in BoQ. Preparation of surfaces and applications of distempering shall be all as per BOQ/CPWD specifications.

Preparation of surfaces and application of interior emulsion shall be done all as per manufacturer's instructions/ as specified in BOQ. The contractor shall give 05 years Guarantee for interior emulsion on stamp paper of value for Rs.100/-

CEMENT BASED PAINT

Cement based paint shall comply with IS 5410-1992, specification for cement paint colour as required. The material shall be in powder form, free from lumps that are not friable and when mixed with required volume of water shall be suitable for use on porous surfaces of masonry, concrete, bricks and rough plaster work. Cement base painting shall be provided where indicated in BOQ and all as specified.

WHITE/COLOUR WASHING

Lime shall be fresh burnt lime (Class 'C'), white in colour conforming to IS-712, 1984. The samples of lime, blue, sodium chloride and gum shall be approved the Engineer-in-Charge before incorporation in work.

Workmanship shall be generally conforming to specification as described in Schedule.

SYNTHETIC ENAMEL PAINTING

The synthetic enamel paint shall be from any of the make/ brand listed in list of manufacturers.

Preparation of surfaces and application of synthetic enamel paint shall be done through the authorized applicator of approved manufacturer all as per manufacturer's instructions/ as specified in BOQ.

The colour scheme for building shall be got approved from Estate officer in consultation of Engineer-in Charge and the contractor shall progress the application of paint only on receipt of approval from Engineer-in-Charge.

GENERAL NOTES FOR APPLYING PUTTY, DISTEMPER, ANTIFUNGAL AND ENAMEL PAINTING

These works shall be executed using modern technics and tools to maintain the required quality work. Following smart painting tools shall be used in site.

- (a) Hand held sander / long handle sander shall be used for plaster / putty work.
- (b) Multipurpose mixer shall be used for mixing putty to get a uniform mix.
- (c) Auto roller and Airless spray shall be used for painting.
- (d) Jet washer to be used for cleaning dirt and fungus etc from external walls.

WORKMANSHIP

All wood work required to be painted shall be smoothened sized and knotted and then applied with priming coat. Stopping and filling (filler coat) shall be done after priming coat and surface rubbed down to a level and smooth surface and thereafter under coat and finishing coat applied. Where painting to wood work is specified prepare surface and apply one priming coat of pink primer, one under coat and one finishing coat of synthetic enamel paint all as specified in Schedule/BOQ.

GALVANIZED SHEET

Galvanized steel sheet, plain or corrugated shall comply with the requirement of IS 277- 2003, Specification for galvanized steel sheets, plain or corrugated. The thickness sheet shall be 0.63mm and Grade of coating shall be 275 or as per BOQ

Plain sheets shall be reasonably flat and free from twist. Corrugated sheet shall be free from twist or buckle and shall have uniform corrugation, true in depth and pitch, and parallel to the sides of the sheets. The tolerance on weight of an individual sheet shall be $\pm 10\%$ and tolerance on bundle of sheets hall be $\pm 5\%$.

GALVALUME SHEETING:-

Galvalume sheet shall be colour coated corrugated / plain sheeting as per requirement and as directed. The feed material is manufactured out of steel with minimum 550 MPa yield strength coated with hot-dip metallic zinc aluminum alloy coating zinc alume AZ-150 or equivalent (as per AS 1397). AS150 Gms/sqm total on both sides of Zn (43.5%), Al (55%) & Si (1.5%) with Regular silicon modified(SMP) polyester paint or equivalent as per AS/NZS-2728-(category 3-4) of approved colour. The colour shall have a total coating thickness of 35 microns of approved paint system or equivalent comprising of 20 microns (nom) exterior coat on top surface and 5 microns(nom) reverse coat of back surface over 5 micron (nom) primer coat on both surfaces of approved colour shade.

The sheet shall have brand marking of the manufacturer on the back of the sheet at spacingnotexc 1.5 m c/c confirming to genuinity of the material. The sheet shall be fastened with good quality fastener of suitable size as directed by Engineer –in-Charge/SI/Insp/Civil, galvanized water head, self-drilling, tapping screw as per AS 3566 class 4 (min) of approved make (Buildex, Corroshield or equivalent) and quality including EPDM/neoprene washer on each crest of sheets for connecting with purloins or as per design. All accessories shall be made from the same material which is used for main roofing/ wall cladding application .

INTERLOCKING PAVER BLOCK

Precast interlocking paver blocks shall be M 40/M-35 grade for 60/80mm thick and shall be laid over 30mm thick cushioning using 6mm and below aggregate or as per BOQ. The paver blocks shall be ISI marked having Glossy Finish. Paver blocks shall be sound and free from cracks or other defects. The tolerance in thickness shall be +3mm. Water absorption shall not be more than 6% by mass. Size, shape, pattern and colour shall be as approved Estate Officer in consultation with Engineer-in-Charge.

PRECAST PCC SOLID BLOCKS FOR MASONRY

SOLID PCC BLOCKS: PCC solid block masonry shall conform to the specifications as per IS2185 -2005.

The blocks shall have a minimum average Compressive strength of 5 N/ Sq mm (Minimum strength of individual unit 4 N/ Sq mm) conforming to C-5 grade IS 2185 -2005 when tested for 28 days cube test. The manufacture of Block, surface texture and finish, physical requirements of blocks, testing of PCC blocks, sampling etc shall be all as per IS 2185-2005 and proper record shall be maintained. The cost of blocks including transportation of block from work site to an approved laboratory for testing and cost of testing shall be borne by the contractor.

Notes:-

- (i) Trial mix shall be carried out before casting the blocks to ensure that the required strength and block density is obtained as per IS.
- (ii) Proper care shall be taken to protect the corners of PCC blocks. To achieve better consistency, contractor may use suitable plasticizers as approved by the Engineer-in-Charge without any price adjustment.

Masonry work shall be kept constantly moist for a minimum of 7 days. All concrete shall be mixed in mechanical mixer. The blocks shall be manufactured with vibratory moulding machines.. However, contractor may use machine moulds of other standard manufacturers if approved by Engineer-in-Charge. Appropriate consistency of concrete shall be used to enable de-moulding of the blocks immediately after casting. The blocks shall have sufficiently rough surface to afford a good key to the plaster and joints. The hardened blocks shall be cured in a water tank in curing yard and shall be kept continuously moist for 14 days. The curing water tank/yard must therefore be of adequate capacity/size. Curing shall be done as per IS –2185.

After curing, the blocks shall be dried for a period of 4 weeks before being used in the work. The blocks shall be allowed to complete their initial shrinkage before they are laid in wall.

Chain Link Fencing:-Mild steel galvanized chain link fencing with mesh of size 50mm x50mm nominal dia of wire 3.10mm fixed to fencing posts sing suitable bolts and nuts.

HARD CORE

The materials for hard core shall be of broken granite stone to a gauge not exceeding 63mm and shall be free from dust and impurities.

Hard core shall be of stones/ boulders (Broken to gauge) not exceeding 63mm. Hard core shall be deposited spread and leveled in layers not exceeding 15cm thick and well watered, rammed to a true surface and compacted. The thickness of the hard core specified or as indicated in the drawings is the thickness after consolidation, where thickness had not indicated, it shall be 100 mm (consolidated thickness).

FORM WORK- As per CPWD Specifications.

GENERAL

- (a) The work under these specifications consists of furnishing all labour, equipments and materials required for form work including all supporting structure for all works of cast in situ concrete as required by drawing and specification of contract.
- (b) The contractor shall submit Form and Centering layout to SI/Insp Civil for checking and final approval by Engineer-in-charge and Estate officer. The complete final approval of the plan will be obtained by the contractor before such work is started on ground. The procedure of erection and removal of forms will be decided at this stage itself. These approvals shall not relive the contractor of any responsibility for correct and complete performance of all works included in the contract. The design and engineering of the formwork as well as its construction shall be the responsibility of the contractor.

<u>DISMANTLING/ DEMOLITION/ TAKING DOWN</u>: The work of dismantling/ demolition/ taking down shall be done carefully and in a workman like manner. Any damage done by contractor or his workmen to existing sanitary fittings/ water supply fittings/ electrical fittings etc in the building while working shall be made good by him at his own expense. All the materials retrieved from demolition/ dismantling/ taking down shall become the Government property except those listed in Credit Schedule. The rates inserted by the CPWD or quoted by the contractor (whichever is more) shall be deemed to include removal or disposal of all waste materials from site of work and site shall be left clean and tidy to the entire satisfaction of Engineer-in-Charge.

SITE CLEARANCE

The contractor shall from time to time, clear away all debris and excess materials accumulated at the site. After the fixtures, etc have been fixed, contractor shall clean-up the same and remove all paints, strains and other foreign matter or discoloration leaving the same in a ready to use condition. On completion of all works, contractor shall demolish all stores, remove all surplus materials and leave the site in a broom clean condition.

<u>SETUP OF FIELD SAMPLE TEST LABORATORY:</u>- Contractor will setup a laboratory at site for testing of sample i.e. cube testing, Sand test, gravel testing, cement testing, sieve analysis, CBR test, Compressive strength machine, Los angles abrasion, Slump test, Silt test of sand etc.

ACCEPTABLE MAKES OF VARIOUS EQUIPMENTS/MATERIALS:-

The acceptable makes of various equipment/components/accessories/materials have been indicated in "Acceptable Makes" appended with the tender documents. The tenderer shall work out the cost of the offer on this basis. Alternate makes are not acceptable.

Sd/-DIG (Engr), Works Dte For and on behalf of the President of India

Schedule- "A"

SI, NO.	Nomenclature of items	Quantity	Unit
1	Dismantling roofing including ridges, hips, valleys and gutters etc., and stacking the material within 50 metres lead of: G.S. Sheet	1036.70	Sqm
2	Providing corrugated G.S. sheet roofing including vertical / curved surface fixed with polymer coated J or L hooks, bolts and nuts 8 mm diameter with bitumen and G.I. limpet washers or with G.I. limpet washers filled with white lead, including a coat of approved steel primer and two coats of approved paint on overlapping of sheets complete (up to any pitch in horizontal/ vertical or curved surfaces), excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required: 1.00 mm thick with zinc coating not less than 275 gm/m ²	1036.70	Sqm
3	Providing ridges or hips of width 60 cm overall width plain G.S. sheet fixed with polymer coated J or L hooks, bolts and nuts 8 mm dia G.I. limpet and bitumen washers complete: 0.80 mm thick with zinc coating not less than 275 gm/m ²	253.60	meter
4	Providing valleys of 90 cm wide overall in plain G.S. sheet fixed with polymer coated J, or L hooks, bolts and nuts 8 mm dia G.I. limpet and bitumen washers complete: 1.60 mm thick with zinc coating not less than 350 gm/m ²	76.80	meter
5	Providing and fixing of 40 cm overall width plain G.S. sheet fixed with polymer coated J or L hooks, bolts and nuts, G.l. limpet and bitumen washer complete, bent to shape and fixed in wall with cement mortar 1:3 (1 cement: 3 coarse sand): 1.00 mm thick with zinc coating not less than 275 gm/m ² : Centered velleyes between whole inner sloped are and gumbad at middle.	38.80	meter
6	Providing and fixing 15 cm wide, 45 cm overall semi-circular plain G.S. sheet gutter with iron brackets 40x3mm size, bolts, nuts and washers etc., including making necessary connections with rain water pipes complete: 0.80 mm thick with zinc coating not less than 275 gm/m ² : For rainwater supply from inner sloped area /velleys	38.80	meter
7	Providing reinforced by organic fibres and/or inorganic synthetic fibres cement 6 mm thick corrugated sheets (as per IS: 14871) roofing up to any pitch and fixing with polymer coated J, or L hooks, bolts and nuts 8 mm dia. G.I. plain and bitumen washers or with self drilling fastener and EPDM washers etc. complete (excluding the cost of purlins, rafters and trusses), including	160.00	G.
8	cutting sheets to size and shape wherever required	168.00 45.40	Sqm
9	Providing and fixing wind ties of 40x 6 mm flat iron section. Providing and fixing ridges and hips in fibre cement reinforced by organic fibres and/or inorganic synthetic fibres roofing with suitable fixing accessories or self drilling fastener and	43.40	meter
	EPDM washer etc. complete: Plain wing adjustable ridges	28.00	meter
10	Providing and fixing insulating board ceiling of approved quality with necessary nails etc. complete (frame work to be paid separately): White face insulating board	405.00	Sqm
11	Providing and fixing flat pressed 3 layer medium density particle board or graded particle board (Grade I) IS: 3087 marked, in ceiling with necessary nails etc. complete (frame work to be paid separately): 12 mm thick	868.00	Sqm
12	Providing and fixing tiled false ceiling of specified materials of size 595x595 mm in true horizontal level, suspended on inter locking metal grid of hot dipped galvanized steel sections (galvanized @120 grams/ sqm, both side inclusive) consisting of main "T" runner with suitably spaced joints to get required length and of size 24x38 mm made from 0.30 mm thick (minimum) sheet, spaced at 1200mm center to center and cross "T" of size 24x25 mm made of 0.30 mm thick (minimum) sheet, 1200 mm long spaced between main "T" at 600 mm center to center to form a grid of 1200x600 mm and secondary cross "T" of length 600 mm and size 24x25 mm made of 0.30 mm thick (minimum) sheet to be interlocked at middle of the 1200x600 mm panel to form grids of 600x600 mm and wall angle of size 24x24x0.3 mm and laying false ceiling tiles of approved texture in the grid including, required cutting/making, opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc. Main "T" runners to be suspended from ceiling using GI slotted cleats of size 27 x 37 x 25 x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm GI adjustable rods with galvanised butterfly level clips of size 85 x 30 x 0.8 mm spaced at 1200 mm center to center along main T, bottom exposed width of 24 mm of all T-sections shall be pre-painted with polyester paint, all complete for all heights as per specifications, drawings and as directed by Engineer-in-charge: 12.5 mm thick fully Perforated Gypsum Board tile made from plasterboard having glass fibre conforming to IS: 2095 part I, of size 595x595 mm, having perforation of 9.7x9.7 mm at 19.4 mm c/c	100.00	sqm

no the back side, having an NRC (Noise Reduction Coefficient) of 0.79, with 50 mm resin bonded glass wool backing Renewal of old putty of glass panes of nominal thickness 5 mm (weight not less than 12.5 kg/kgm) Providing and fixing pressed steel door frames conforming to 18: 4351, manufactured from commercial mild steel sheet of 1.60 mm thickness, including hings, annh, lock jamb, bead and if required angle threshold of mild steel angle of section 50x25 mm, or base ties of 1.60 mm, pressed mild steel welded or rigidly fixed together by mechanical means, including M.S., pressed but thinges 2.5 mm thick with mortar guards, lock strike-plate and shock absorbers as specified and applying a cost of approved steel primer after pre-treatment of the surface as directed by Engineer-in-charge: Profile P. Fixing with adjustable lugge and 10 cach jamb 140.00 meter Providing and fixing carbon steel galvanised (minimum coating 5 micron) dash fastener of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame, concrete massoury, etc. as per direction of Engineer-in-charge: 10 x 60 mm Providing and fixing carbon steel galvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams 120.00 cach Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. Fixing of old wind tie with new fittings including parinting two or more coats with anticorrosive bitumastic paint of approved brand. & manufacturer over and including priming coat of ready mixed zine chromate yellow primer of approved brand. Dismantling tile work in floors and roofs laid in cement mortar 1:4 (1 Cement: 4 coars sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and manufacturery of the manufacturery, of 18 quality conforming to 18: 15622,		with contar bardars of 49 mm and the side bardars of 20 mm. bested with non-month		
Bonded glass wood backing Complete Com		with center borders of 48 mm and the side borders of 30 mm, backed with non woven tissue on the back side boying an NPC (Noise Reduction Coefficient) of 0.79 with 50 mm resin		
providing and Existing pressed steel door frames conforming to IS: 4351, manufactured from commercial mild steel sheet of 1.0 mm thickness, including hinges, jamb, lock jamb, bead and required angle threshold of mild steel angle of section 50x25 mm, or base ties of 1.60 mm, pressed timel steel sheet of 1.60 mm thickness, including hinges, jamb, lock jamb, bead and required angle threshold of mild steel angle of section 50x25 mm, or base ties of 1.60 mm, pressed but thinges 2.5 mm thick with mortar guards, lock strike-plate and shock absorbers as specified and applying a court of approved steel primer after pre-treatment of the surface as directed by Engineer-in-charge: Profile B: Fixing with adjustable lugs with split end tail to each jamb 140.00 meter of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame, concrete/ msourcy, etc. as per direction of Engineer-in-charge: 10 x 60 mm and 1.4 mm aperture on both six 6.2 mm charge 10 x 60 mm and 1.4 mm appriature on bridge strength 480 N/mm2), counter sunk head, comprising of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame, concrete/ msourcy, etc. as per direction of Engineer-in-charge: 10 x 60 mm and 1.4 mm aperture on both six 6.2 mm charge 10 x 60 mm and 1.4 mm aperture on both six 6.2 mm charge 10 x 60 mm and 1.4 mm aperture on both six 6.2 mm charge 10 x 60 mm and 1.4 mm aperture on both six 6.2 mm charge 10 x 60 mm and 1.4 mm aperture on both six 6.2 mm charge 10 x 60 mm and 1.4 mm aperture on both six 6.2 mm charge 10 x 60 mm and 1.4 mm aperture on both six 6.2 mm charge 10 x 60 mm and 1.4 mm aperture on both six 6.2 mm charge 10 x 60 mm and 1.4 mm aperture on both six 6.2 mm charge 10 x 60 mm and 1.4 mm aperture on both six 6.2 mm charge 10 x 60 mm and 1.4 mm aperture on both six 6.2 mm charge 10 x 60 mm and 1.4 mm aperture on both six 6.2 mm charge 10 x 60 mm and 1.4 mm aperture on both six 6.2 mm charge 10 x 60 mm and 1.5 mm and 1.4 mm aperture on both six 6.2 mm and 1.5 mm and 1.5 mm and 1.				
19 putty: Float glass panes of nominal thickness 5 mm (weight not less than 12.5kg/sqm) 17.3.5 sqm 17.3.5 sqm 18 Renewal of old putty of glass panes 18 Providing and fixing pressed steel door frames conforming to 1S: 4351, manufactured from commercial mild steel sheet of 1.60 mm thickness, including linges, jamb, lock jamb, bead and if required angle threshold of mild steel angle of section 50x25 mm, or base ties of 1.60 mm, pressed mild steel welded or rigidly fixed together by mechanical means, including M.S. pressed but thinges 2.5 mm thick with mortar guards, lock strike-plate and shock absorbers as specificd and applying a cost of approved steel primer after pre-treatment of the surface as directed by Engineer-in-charge: Profile B: Fixing with adjustable lugs with split end tail to each jamb 140.00 meter 16 Providing and fixing carbon steel galvanised (minimum coating 5 micron) dash fastener of 10 mm dia obuble threaded 6.8 grade (yield strength 480 N/mm2), counter sunk head, comprising of 10 mm dia opolymathe PA 6 grades sleeve, including drilling of hole in firme, concrete massomy, etc. as per direction of Fingineer-in-charge: 10 x 60 mm 19 Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams 18 Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. 20 page 19 Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. 21 Eixing of Iol wind the with new Fittings including painting two or more coats with anticorrosive bitumustic paint of approved brand. 8c manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. 22 bitumustic paint of approved brand 8c manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. 23 bitumustic paint of approved brand 8c manufacturer) with water absorption less				
Renewal of old patty of glass panes Providing and fixing pressed steel door frames conforming to 18: 4351, manufactured from commercial mild steel sheet of 1.60 mm thickness, including thinges, jamh, lock jamh, bead and if required angle threshold of mild steel angle of section 50x25 mm, or base ties of 1.60 mm, pressed mild steel whether or nightly fixed together by mechanical means, including M.S. pressed but thinges 2.5 mm thick with mortar guards, lock strike-plate and shock absorbers as specified and applying a coat of approved steel primer after pret-treatment of the surface as directed by Engineer-in-charge: Profife B: Fixing with adjustable lugs with split end tail to each jamb Providing and fixing ordinon steel galvanised (minimum conting 5 micron) dash fastener of 10 mm dia obolbe threaded 6.8 grade (yield strength 480 N/mm2), counter sunk head, comprising of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame, concreter masonry, etc. as per direction of Engineer-in-charge: 10 x 60 mm Providing & fixing fly proof wire gauze to windows, clerestory windows & doors with M.S. Flat 15x3 mm and nuts & bolts complete: Galvanised M.S. Wire gauze with Ood.3 mm dia wire and 1.4 mm aperture on both sides Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc complete: 200 mm weighing not less than 120 grams Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. The providing and fixing oxided by the manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of files 10 mm to 25 mm Providing and laying greatified floor tiles in different	13		17 25	g d to
Providing and fixing pressed steel door frames conforming to 18: 451, manufactured from commercial mild steel sheet of 1.60 mm thickness, including hinges, jamb, lock jamb, bead and if required angle threshold of mild steel angle of section 59x25 mm, or base ties of 1.60 mm, pressed mild steel welded or rigidly fixed together by mechanical means, including M.S., pressed but thinges 2.5 mm thick with mortar guards, lock strike-plean and shock absorbers as specified and applying a coat of approved steel primer after pre-treatment of the surface as directed by Engineer-in-charge: Profile IP. Fixing with adjustable lugs with split and tail to each jamb providing and fixing carbon steel galvanised (minimum coating 5 micron) dash fastener of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame, concrete maxomy, etc. as per direction of Engineer-in-charge: 10 x 60 mm Providing & fixing fly prore wire gauze to windows, clerestory windows & doors with M.S. Plat 15x3 mm and nuts & bolts complete: Galvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. Fixing of old wind it ewith new Fittings including painting two or more coats with anticorrosive bitumastic paint of approved brand & manufacturer over and including priming coat of ready mixed gine chromate yellow primer of approved brand & manufacturer over and including painting two or more (chickness to be specified by the manufacturer) of 1st quality conforming to 18: 15622, of approved make, in colours White, 1vory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 14 (1 Coment: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching prigments etc., complete	1.4			
commercial mild steel sheet of 1,60 mm thickness, including hinges, jamb, lock jamb, bead and if required angle threshold of mild steel angle of section 50x25 mm, or base ties of 1,60 mm, pressed but hinges 2.5 mm thick with morat guards, lock strike-plate and shock absorbers as specified and applying a coat of approved steel primer after pre-treatment of the surface as directed by Engineer-in-charge: Profile B: Fixing with adjustable lugs with split end tail to each jamb Providing and fixing carbon steel galvanased (minimum coating 5 microv) dash fastener of 10 mm dia double threaded 6.8 gaade (yield strength 480 N/mm2), counter sunk head, comprising of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame, concrete masonry, etc. as per direction of Engineer-in-charge: 10 x 60 mm Providing & fixing fly proof wire gauze to windows, clerestory windows & doors with M.S. Plat 15x3 mm and nuts & bots complet c 34danised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. Fixing of old wind tie with new fittings including painting two or more coats with anticorrosive bitmastic paint of approved brand & manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer) of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 cement: 4 course sand), jointing with grey cement slurry	14	1 , 0 1	380.00	meter
if required angle threshold of mild steel angle of section 50x25 mm, or base ties of 1,60 mm, pressed mild steel welded or rigidly fixed together by mechanical means, including M.S. pressed but hinges 2.5 mm thick with mortar guards, lock strike-plate and shock absorbers as specified and applying a coat of approved steel primer after pre-treatment of the surface as directed by Engineer-in-charge: Profile IP. Fixing with adjustable lugs with split out at lio each jamb 140.00 meter Providing and fixing carbon steel galvanised (minimum coating 5 micron) dash fastener of 10 mm dia double threaded 6.8 grade (yield strength 480 N/mm2), counter sunk head, comprising of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame, concreted massonry, etc. as per direction of Engineer-in-charge: 10 x 60 mm Providing & fixing thy proof wire gauze to windows, elerestry windows & doors with M.S. Flat 15x3 mm and nuts & bolts complete: Galvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams 18 Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams 19 Taking out wind ties from roof including cutting out rasted bolts, nuts etc. and removing materials to any distance within compound and stacking. Fixing of old wind tie with new fittings including painting two or more coats with anticorrosive bitumastic paint of approved brand & manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. 105.100 meter 21 Dismantling tile work in floors and roofs laid in cennent mortar including stacking material within 50 metres lead: For thickness of files 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st qua				
pressed mild steel welded or rigidly fixed together by mechanical means, including M.S. pressed but hingss 2.5 mm thick with mortar guards, lock strike-plate and shock absorbers as specified and applying a coat of approved steel primer after pre-treatment of the surface as directed by Engineer-in-charge: Profile B: Fixing with adjustable lugs with split end tail to each jamb Providing and fixing carbon steel galvanised (minimum coating 5 micron) dash fastener of 10 mm dia obuble threaded 6.8 grade (yield strength 480 Nmm2), counter sunk head, comprising of 10 mm dia polyamide PA. 6 grade sleeve, including drilling of hole in frame, concrete/masoury, etc. as per direction of Engineer-in-charge: 10 x 60 mm Providing & fixing fly proof wire gauze to windows, clerestory windows & doors with M.S. Flat 15x3 mm and musk & bolts complete: Galvanised M.S. Wire gauze with 6.63 mm dia wire and 1.4 mm aperture on both sides Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams 19 Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. 830.29 Kg Providing of old wind tie with new fittings including painting two or more coats with anticorrosive bitumastic paint of approved brand. 10 Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of tiles 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacture), of 1st quality conforming to 15: 15622, of approved make, in colours White, lvory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 14 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminitum work for doors, windows				
but hingss 2.5 mm thick with mortar gands, lock strike-plate and shock absorbers as specified and applying a coat of approved steel primer after pre-treatment of the surface as directed by Engineer-in-charge: Profile B: Fixing with adjustable lugs with split end tail to each jamb Providing and fixing carbon steel galvanised (minimum coating 5 micron) dash fastener of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame, concrete/masorny, etc. as per direction of Engineer-in-charge: 10 x 60 mm Providing & fixing fly proof wire gauze to windows, clerestory windows & doors with M.S. Flat 15x3 mm and nuts & bolts complete: Calvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. Fixing of old wind tie with new fittings including patining two or more coats with anticorrosive bitimustic paint of approved brand. The providing and laying rectified Glazed Ceramic floor tile to size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, lover, Grey, Fune Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tite 600x600 mm Providing and laying virified floor tites in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to 1S: 15622, of approved make, including and fixing aluminium work for doors, windows, ventilators and partiti	1.5			
and applying a coat of approved steel primer after pre-treatment of the surface as directed by Engineer-in-charge: Profile B: Fixing with adjustable lugs with split end tail to each jamb Providing and fixing carbon steel galvanised (minimum coating 5 micron) dash fastener of 10 mm dia double threaded 6.8 grade (yield strength 480 N/mm2), counter sunk head, comprising of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame, concrete/masonry, etc. as per direction of Engineer-in-charge: 10 x 60 mm Providing & fixing fly proof wire gauze to windows, clerestory windows. & doors with M.S. Flat 17 Instant and 1.4 mm aperture on both sides 18 Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams 19 Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. 20 Eixing of old wind tie with new fittings including painting two or more coats with anticorrosive bitumastic paint of approved brand. 21 Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 meres lead: For thickness of these 10mm and 1.4 mm aperture. 21 Dismantling tile work in floors and roofs laid in cement mortar including grouting the yolink with exercised the manufacturer), of 1st quality conforming to 18: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1.4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. 22 Providing and laying ritrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to 18: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1.4 (1 Cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm inclu	15			
Engineer-in-charge: Profile B: Fixing with adjustable lugs with split end tail to each jamb Providing and fixing carbon steel galvanised (minimum coating 5 micron) dash fastener of 10 mm dia double threaded 6.8 grade (yield strength 480 N/mm2), counter sunk head, comprising of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame, concrete/masonry, etc. as per direction of Engineer-in-charge: 10 x 60 mm Providing & fixing fly proof wire gauze to windows, elerestory windows & doors with M.S. Flat 153 mm and unts & bolts complete: Galvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides Providing and fixing oxidised M.S. cassement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams Providing and fixing oxidised M.S. cassement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams 20 bitumastic paint of approved brand. Prixing of Idw wind te with new fittings including painting two or more coats with anticorrosive bitumastic paint of approved brand. 21 bismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 meters lead: For thickness of tiles 10 mm to 25 mm Providing and laying rectified Gilzaed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and laying virified floor tiles in different size (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 Cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm incl				
Providing and fixing carbon steel galvanised (minimum coating 5 micron) dash fastener of 10 mm dia double threaded 6.8 grade (yield strength 480 N/mm2), counter sunk head, comprising of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame, concrete/masonry, etc. as per direction of Engineer-in-charge: 10 x 60 mm Providing & fixing fly proof wire gauze to windows, etcerestory windows & doors with M.S. Flat 1533 mm and nuts & bolts complete: Galvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. Providing of old wind tie with new fittings including painting two or more coats with anticorrosive bitumastic paint of approved brand & manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. 10 Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: Fort thickness of tiles 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x,300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 33 kg/sqm including grouting the joints with white cement and matching pigments etc. complete some shades, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 coarse sand), jointing with grey cement slurry @ 3.8 kg/sqm including grouting the joints with white cement and matching pigments etc. complete as per architectural drawings and the directions of Engineerin-charge; For fixed portion: Powder coated aluminium manufacturer) with water absorption less			4.40.00	
mm dia double threaded 6.8 grade (yield strength 480 N/mm2), counter sunk head, comprising of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame, concrete/masonry, etc. as per direction of Engineer-in-charge: 10 x 60 mm Providing & fixing fly proof wire gauze to windows, clerestory windows & doors with M.S. Flat 15x3 mm and nuts & bolts complete: Galvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides 18 Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams 19 Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. 20 Fixing of old wind tie with new fittings including painting two or more coats with anticorrosive bitumastic paint of approved brand & manufacturer over and including priming coat of ready mixed zine chromate yellow primer of approved brand. 21 Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of files 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement sturry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. 23 Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Pro			140.00	meter
of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame, concrete/ masonry, etc. as per direction of Engineer-in-charge: 10 x 60 mm Providing & fixing fly proof wire gauze to windows, clerestory windows & doors with M.S. Flat 15x3 mm and nuts & bolts complete: Galvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. Fixing of old wind tie with new fittings including painting two or more coats with anticorrosive bitumastic paint of approved brand. Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of files 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Providing and laying viirified floor tiles in different mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with water absorption less than 0.08% and conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing viirified floor tiles in different mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including such				
or 10 mm dia polyamide PA o grade sleeve, including drilling of hole in trame, concrete masonry, etc. asper dricterion of Engineer-in-charge: 10 x 60 mm Providing & fixing fly proof wire gauze to windows, elerestory windows & doors with M.S. Flat 15x3 mm and nuts & bolts complete: Salvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides complete: Salvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides complete: Salvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides complete: Salvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides complete: Salvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides complete: Salvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides complete: Salvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides of the salvanised with 0.63 mm dia wire and 1.4 mm aperture on both sides of the salvanised with 0.63 mm dia wire and 1.4 mm aperture on both sides of the salvanised with 0.63 mm dia wire and 1.4 mm aperture on both sides of the salvanised with 0.63 mm dia wire and 1.4 mm aperture on both sides of the salvanised with 0.63 mm dia wire and 1.4 mm aperture on both sides of the salvanised with 0.63 mm dia wire and 1.4 mm aperture on both sides of the salvanised with anticorrosive bitumastic paint of approved brand. 1051.00 meter 120.00 meter of providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 18: 15622, of approved make, in colours White, lvory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1.4 (1 cement : 4 coarse sand), jointing with grey cement surry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with meterum and matching pigm	16			
Providing & fixing fly proof wire gauze to windows, clerestory windows & doors with M.S. Flat 15x3 mm and nuts & bolts complete: Galvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. Fixing of old wind tie with new fittings including painting two or more coats with anticorrosive bitumastic paint of approved brand & manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. 1051.00 meter 1051.00 meter of paint of approved brand and stacking. Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium works for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to 1S: 733 and 1S: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at to	10	of 10 mm dia polyamide PA 6 grade sleeve, including drilling of hole in frame, concrete/		
15x3 mm and nuts & bolts complete : Galvanised M.S. Wire gauze with 0.63 mm dia wire and 1.4 mm aperture on both sides Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete : 200 mm weighing not less than 120 grams 120.00 each Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. Fixing of old wind tie with new fittings including painting two or more coats with anticorrosive bitumastic paint of approved brand & manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of tiles 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 cement: 4 Coarse sand), jointing with grey cement surry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to 1S: 733 and 1S: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at			416.00	each
18 Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams 19 Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. 20 Fixing old wind tie with new fittings including painting two or more coats with anticorrosive bitumastic paint of approved brand & manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. 21 Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of tiles 10 mm to 25 mm 22 Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer) of 1st quality conforming to 1s: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete:				
Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc. complete: 200 mm weighing not less than 120 grams Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. 830.29 Kg Fixing of old wind tie with new fittings including painting two or more coats with anticornosive bitumastic paint of approved brand & manufacturer over and including priming coat of ready mixed zine chromate yellow primer of approved brand. Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of tiles 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.8% and conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 660x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to 1S: 733 and 1S: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straigh	17	15x3 mm and nuts & bolts complete: Galvanised M.S. Wire gauze with 0.63 mm dia wire		
complete: 200 mm weighing not less than 120 grams Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. Fixing of old wind tie with new fittings including painting two or more coats with anticorrosive bitumastic paint of approved brand & manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of tiles 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. 5.00 Sqm Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to 1S: 733 and 1S: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required the proper gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glaz		and 1.4 mm aperture on both sides	312.00	Sqm
complete: 200 mm weighing not less than 120 grams Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing materials to any distance within compound and stacking. Fixing of old wind tie with new fittings including painting two or more coats with anticorrosive bitumstic paint of approved brand & manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of tiles 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturery, of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sgm including grouting the joints with white cement and matching pigments etc., complete. Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sgm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to 1S: 133 and 1S: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazi	10	Providing and fixing oxidised M.S. casement stays (straight peg type) with necessary screws etc.		
materials to any distance within compound and stacking. Fixing of old wind tie with new fittings including painting two or more coats with anticorrosive bitumestic paint of approved brand & manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of tiles 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to 1S: 733 and 1S: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of EpDM rubber/ neoprene ga	10	complete: 200 mm weighing not less than 120 grams	120.00	each
Fixing of old wind the with new fittings including painting two or more coats with anticorrosive bitumastic paint of approved brand & manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. 10 Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of tiles 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. 23 make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the including and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate 2 sections and other sections of approved make conforming to 1S: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required 24 EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge: : For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelaminated particle board dilat pressed three layer or graded wood particle board conforming to 1S: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partitition setc.	10	Taking out wind ties from roof including cutting out rusted bolts, nuts etc. and removing		
Fixing of old wind tie with new fittings including painting two or more coats with anticorrosive bitumastic paint of approved brand & manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of tiles 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to 1S: 733 and 1S: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P. brass/stainless steel screws, all complete as per architectural drawings and the directions of fignineer-in-charge: For fixed portion: Powder coated aluminium (minimum thickness	19		830.29	Kg
bitumastic paint of approved brand & manufacturer over and including priming coat of ready mixed zinc chromate yellow primer of approved brand. Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of tiles 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, lvory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to 1S: 133 and 1S: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/ paneling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) For shutters of doors, windows & ventilators including providing				
mixed zinc chromate yellow primer of approved brand. Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of tiles 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to 1S: 733 and 1S: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/ paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) For shutters of doors, windows & wentilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required inc	20			
Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead: For thickness of tiles 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to 1S: 733 and 1S: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) 25.00 Kg Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminum doors, window			1051.00	meter
within 50 metres lead: For thickness of tiles 10 mm to 25 mm Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to 1S: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to 1S: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to 1S: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/ paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of p				
Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to IS: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P. brass/stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber/ neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelami	21		45.27	Sam
to be specified by the manufacturer), of 1st quality conforming to IS: 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P. brass/stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. : For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings wherever required including the cost of EPDM rubber / neopr			.0.2,	- q
in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P. brass/stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) 25.00 Kg For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber/ neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) 25.00 Kg Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminum doors, windows shutters	22			
Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete. Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete : Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/ paneling, C.P. brass/stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. : For fixed portion : Powder coated aluminium (minimum thickness of powder coating 50 micron) 25.00 Kg For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber/ neoprene gasket required (Fittings wherever required including the cost of EPDM rubber/ neoprene gasket required (Fittings wherever required including the cost of EPDM rubber/ neoprene gasket required (Fittings wherever required including the cost of EPDM rubber/ neoprene gasket required (Fittings shall be paid for separately) : Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelam				
pioints with white cement and matching pigments etc., complete. Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P. brass/stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) 25.00 Kg For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) 30.00 Kg Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board wood				
Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete : Size of Tile 600x600 mm 41.00 Sqm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P. brass/stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) 25.00 Kg Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides 2.00 Sqm			5.00	Sam
manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete : Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. : For fixed portion : Powder coated aluminium (minimum thickness of powder coating 50 micron) For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) : Powder coated aluminium (minimum thickness of powder coating 50 micron) 25.00 Kg Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge : Pre-laminated particle board with decorative lamination on both sides 2.00 Sqm Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.			3.00	Sqiii
make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P. brass/stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber/ neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) 25.00 Kg Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.				
sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete: Size of Tile 600x600 mm 41.00 Sqm Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to 1S: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P. brass/stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) 25.00 Kg For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber/ neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) 30.00 Kg Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides 2.00 Sqm	22	,		
24 Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) 25.00 Kg For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides 2.00 Sqm Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.	23	· · · · · · · · · · · · · · · · · · ·		
Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P. brass/stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) 25.00 Kg For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides 2.00 Sqm Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.			41.00	a
extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. : For fixed portion : Powder coated aluminium (minimum thickness of powder coating 50 micron) 25.00 Kg For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) : Powder coated aluminium (minimum thickness of powder coating 50 micron) 30.00 Kg Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge : Pre-laminated particle board with decorative lamination on both sides 2.00 Sqm Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.			41.00	Sqm
make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.				
including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade l Type ll, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.	24			
EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade l Type ll, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.				
mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. : For fixed portion : Powder coated aluminium (minimum thickness of powder coating 50 micron) For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) : Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade l Type ll, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge : Pre-laminated particle board with decorative lamination on both sides Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.				
beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade l Type ll, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.				
drawings and the directions of Engineer-in-charge.: For fixed portion: Powder coated aluminium (minimum thickness of powder coating 50 micron) 25.00 Kg For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade l Type ll, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides 2.00 Sqm Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.				
aluminium (minimum thickness of powder coating 50 micron) For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.				
For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.				
making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.			25.00	Kg
neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.				
neoprene gasket required (Fittings shall be paid for separately): Powder coated aluminium (minimum thickness of powder coating 50 micron) Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.	25			
Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides 2.00 Sqm Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.	23			
wood particle board conforming to IS: 12823 Grade l Type ll, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides 2.00 Sqm Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.			30.00	Kg
wood particle board conforming to IS: 12823 Grade l Type ll, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides 2.00 Sqm Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.				
doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer in-charge : Pre-laminated particle board with decorative lamination on both sides 2.00 Sqm Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.				
complete as per architectural drawings and directions of engineer in-charge: Pre-laminated particle board with decorative lamination on both sides 2.00 Sqm Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.	26			
particle board with decorative lamination on both sides 2.00 Sqm Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.				
Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc.			2.00	Sam
77				~ 7
Self 14000 / Respecte Subset etc. complete as per the atomicectal at awings and the	27		2 00	Sam
		with Li Divi rubber / neoptene gasket etc. complete as per the architectural drawings and the	∠.00	SqIII

	directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item):		
	With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm)		
	Providing and fixing double action hydraulic floor spring of approved brand and manufacture conforming to IS: 6315, having brand logo embossed on the body / plate with double spring		
28	mechanism and door weight upto 125 kg, for doors, including cost of cutting floors, embedding in floors as required and making good the same matching to the existing floor finishing and cover		
	plates with brass pivot and single piece M.S. sheet outer box with slide plate etc. complete as		
	per the direction of Engineer-in-charge: With stainless steel cover plate minimum 1.25 mm	• • • •	
	thickness	2.00	each
	Providing and fixing aluminium tubular handle bar 32 mm outer dia, 3.0 mm thick & 2100 mm		
29	long with SS screws etc .complete as per direction of Engineer-in-Charge : Powder coated		
	minimum thickness 50 micron aluminium tubular handle bar	2.00	each
	Providing and fixing Brass 100mm mortice latch and lock with 6 levers without pair of handles		
30	(best make of approved quality) for aluminium doors including necessary cutting and making		
	good etc. complete.	1.00	each

Note: - Lowest Contractor (L-1) will be decided on overall lowest rates basis. (All items to be used in this work should be branded and ISI certified or CPWD approved list of material may be followed. If any make is not specified, decision of Engineer-in-charge shall be final.)

Sd/-DIG (Engr), Works Dte For and on behalf of the President of India