



INVITATION TO E-TENDER
WORKS DIRECTORATE, CENTRAL RESERVE POLICE FORCE
 Level – 3, Block-7, Sec -1, East Block, R. K. Puram,
 New Delhi-110066, Tel/Fax: 011-26108447

E-Mail id – digwks@crpf.gov.in

Tele / Fax No. :011-26108447

No. B.V(GC NMH)AP/24-25-/MW/WksDte-C/Cell(NIT-47)

Dated, January, 2025

To,

.....

Dear Sir,

On behalf of the President of India, I invite you to **online bid under two bid system** for the following work at **GC CRPF NEEMUCH (M.P.)**:-

Sl. No.	Details of proposal
1.	Repair and Maintenance of Ochterlony House at GC CRPF Neemuch (M.P).

02. Details **of works** are mentioned in **Schedule- “A”** and **“B.O.Q. of Tender”**.

03. If you are in a position to quote for carrying out the proposed works in accordance with the requirements stated in the attached schedule to tender, all documents attached herewith should be properly filled in, signed and submitted through e-procurement site <http://eprocure.gov.in/eprocure/app>. You are further required to furnish along with the aforesaid tender all the information called for, attached list of questionnaire should also be answered and submitted along with documents through e-procurement site <http://eprocure.gov.in/eprocure/cpp>, failing which your tender will liable to be rejected and will not be considered.

04. This tender is not transferable.

05. **Since, work is being executed for a prestigious event of national level, there is a need by the firm to understand the importance of work to execute in given time failing which suitable punitive action shall be taken by CEA which may include penalty and/or blacklisting the firm for certain duration from bidding to CRPF projects.**

Thanking you.

Yours faithfully

DIG(Engr), Works Dte.
 For and on behalf of the President of India

SCHEDULE TO TENDER (OPEN TENDER)
CENTRAL RESERVE POLICE FORCE
(Government of India, Ministry of Home Affairs)
Works Directorate, CRPF

No. B.V(GC NMH)AP/24-25-/MW/WksDte-C/Cell(NIT-47)

Dated,

January,2025

TENDER SET IS NOT TRANSFERABLE

Tender Enquiry No.	:	As per CPP Portal
Date of Publishing of Tender	:	
Time and date of submission/receipt of tender	:	
Time and date for opening of tender	:	

01. The intending tenderers must read the terms and condition carefully and submit their tender if they consider themselves eligible and are in possession of all the required documents, through online tender (e-procurement web site in CPP Portal) before due date & time. Tenderers are also advised to go through the Earnest Money, Payment terms and other clauses, terms and conditions of this Tender Enquiry carefully before filling the Tender Application.

Tender No	Name of work with its description and location	Category of service required / Quantity / Work Timing / Periodicity / Period	Estimated cost put to tender	Earnest Money Deposit @2 %	Procedure for deposit of Earnest Money Deposit (EMD)	Critical date
B.V(GC NMH)AP/24-25-/MW/WksDt e-C/Cell(NIT-47)	REPAIR & RENOVATION OF GOS MESS ANNEXE BUILDING AT OCHTERLO NY HOUSE GOS MESS GC CRPF NEEMUCH (M.P.)	As per "Schedule tender" to	Rs. 68,53,203/-	Rs 1,37,064/- [Note: - EMD Should be valid for 90 days from the bid submission end date of tender. If there after validity of the E.M.D require extension, the firm will be responsible to extend the same suitably till the validity of the bid]	Rs 1,37,064/- Original Earnest Money Deposit (EMD) shall be deposited in office of the Works Dte, level-3, East Block-7, Sec -1, , RK Puram, New Delhi before the due date of submission of bid.	As per CPP Portal

02. Tenders will be opened online on the given date & time at CRPF Works Dte, Level-3, East Block – 07, RK Puram, Sector- 1, New Delhi.

03. Tenderers are requested to submit their bid/tender documents online through e-procurement in CPP Portal. EMD, Tender Acceptance Letter (On firms letter head), Integrity Pact (On firms letter head) documents shall be submitted in original either by hand or by registered/speed post to CRPF Works Dte, Level-3, East Block – 07, RK Puram, Sector- 1, New Delhi.

04. All Tender documents attached with this invitation to tender including the specifications are sacrosanct for considering any offer as complete offer. It is therefore important that Tender Acceptance Letter which is a written undertaking that all the terms and conditions of the tender are understood and accepted should be signed and submitted along with all documents as required through e-Procurement site <http://eprocure.gov.in/eprocure/app>.

05. All bidders required to submit earnest money as mentioned above along with their offer. EMD should be paid by the bidder mandatorily. If the bidder fails to submit EMD then his tender will be rejected summarily.

06. All bidders are required to submit their offer in **two bid system**.

07. The enlistment of the contractor should be valid on the last date of submission of the bid. In case only the last date of submission of bid is extended, the enlistment of contractor should be valid on the original date of submission of bid.

08. Details required to be furnished by all bidders in the bid (Composite i.e. Technical & Price or financial Bid together) are as under. The bid should contain the following: -

i) Documents to be submitted online in scanned copy on CPPP:-

1.	Tender acceptance letter (In firm's letter head)
2.	Earnest Money deposit (As per schedule to tender failing which offers will be summarily rejected).
3.	Copy of GST registration certificate & PAN Card.
4.	Copy of registration of the firm/contractor for Building Works with CPWD, MES, BRO, RAILWAY and MP PWD or All Documents required for Enlistment as specified in the latest CPWD Enlistment Rules.
5.	Copy of certificate of registration for EPFO and certificate of registration for ESIC (Declaration, if not applicable) failing which offers will be summarily rejected).
6.	Satisfactorily completed as a prime contractor at least one similar work of 80% value or two works of atleast 60% value or 3 works of atleast 40% value. (for non – enlisted contractors) Bidder has to submit on-line scanned copy of certificate of Work Order along with Work Completion certificate of similar nature work equal to required value during last five years issued by not below the rank of Executive Engineer.
7.	Partnership Agreement of the firm if the firm is a partnership firm. (If no papers submitted with the bid it will be assumed that the firm is a Single/Sole Proprietary and will be fully responsible if found false at later stage)
8.	Check list as per Appendix- 'B' after compliance.
9.	Information regarding any litigation or arbitration resulting from contracts executed by the bidder in the last five years or currently under execution as provided. Bidder has to submit on-line scanned copy of an information regarding litigation, arbitration, black listing, debaring etc. This document must be up loaded on line duly signed by the bidder.
10.	Bidder has to submit on-line scanned copy of an affidavit duly signed stating that the near relations defined as first blood relations, and their spouses is/are not working in CRPF. If working, give details for the same. (a relation shall mean wife, husband, parents, grandparents, children, grandchildren, brothers, sisters, uncles, aunts, cousins and their corresponding in-laws)
11.	Bidder has to submit on-line scanned copy of an affidavit duly signed stating that no retired personnel in his employment is working who retired within last two years from CRPF. If employed, give details for the same.
12.	Non-enlisted bidders are required to submit (i) Either Banker's Certificate of Rs. 41.6 Lakh (Proforma as Appendix-E) OR Net worth Certificate of Rs. 13 Lakh (proforma as Appendix-D) AND (ii) Average Annual Turnover Certificate of Rs. 41.6 Lakh (Proforma as Appendix-C) on works during the last three financial years from a Chartered Accountant.

(ii) Documents to be submitted in original manually or by registered/speed post to CRPF Works Dte, Level-3, East Block – 07, RK Puram, Sector- 1, New Delhi.

1.	Tender acceptance letter (On firms letter head)
2.	Earnest Money deposit
3.	Integrity Pact (On firms letter head)

09. Following should be noted and kept in mind while submission of rate in price bid format of C.P.P Portal-

- i) Price should only be quoted as per price bid format / B.O.Q along with tender documents at e-procurement site <http://eprocure.gov.in/eprocure/app>.
- ii) The price bid in B.O.Q format / template should not be modified and replaced by the bidder and the same should be uploaded after filling the relevant columns, else the bidder is liable to be rejected for the tender. Bidders are allowed to enter the Bidder Name and Values only.

10. Bidder should deposit earnest money with required validity along with their Tender. Earnest Money should be in form of **Account payee Demand Draft, Fixed Deposit Receipt, Banker's Cheque** from any of the commercial banks in an acceptable form in favour of **“THE DIGP GC, CRPF, NEEMUCH [Payable At-SBI, Kanawati Branch (Code-7293)]”**

11. The tender documents are consisting of specification, schedule of quantities of works to be provided and terms and conditions of this contract to be complied with other necessary documents.

SIGNATURE OF THE TENDERER

DIG (Engr), Works Dte
For and on behalf of the President of India

TENDER ACCEPTANCE LETTER
(To be given on Firm’s/Company’s Letter Head)

Date:

To,

Subject:-**Acceptance of Terms & Conditions of Tender.**

Tender Reference No:- _____

Name of Tender / Work: - _____

Dear Sir,

1. I/We have downloaded/obtained the tender document(s) for the above mentioned ‘Tender/Work’ from the web site(s) namely..... as per your advertisement, given in the above mentioned website(s).
2. I / We hereby certify that I / we have read the entire terms and conditions of the tender documents from Page No. _____ to _____ (including all documents like annexure(s), schedule(s), etc.) which form part of the contract agreement and I / we shall abide hereby by the terms / conditions / clauses contained therein.
3. The corrigendum(s) issued from time to time by your department/ organizations too have also been taken into consideration, while submitting this acceptance letter.
4. I / We hereby unconditionally accept the tender conditions of above mentioned tender document(s) / corrigendum(s) in its totality/entirety.
5. In case any provisions of this tender are found violated , then your department/ organization shall without prejudice to any other right or remedy be at liberty to reject this tender/bid including the forfeiture of the full said earnest money deposit absolutely.

Yours Faithfully,

(Signature of the Bidder, with Official Seal)
SIGNATURE OF TENDERER

Check list for tenderer**(Tenderers should check following requirements for compliance before submission of the tender documents)**

Sl. No.	Requirements to be checked by the tenderer before submission of the tender	Compliance (To be indicated With “YES” after Compliance of the requirements)
1.	Whether Tenderers has submitted required Earnest Money Deposit with their bid as specified? (As per schedule to tender failing which offers will be summarily rejected).	
2.	Whether rates have been quoted only as per price bid format / B.O.Q along with tender documents?	
3.	Whether rates have been quoted inclusive of all taxes including GST (ESI and EPF contributions on the part of employer in respect of this contract shall be paid by the contractor. The EPF & ESIC contributions on the part of the employer paid by the contractor shall be reimbursed by the department to the contractor on actual basis with site of work at GC CRPF NEEMUCH (M.P.) . only on producing original receipt of EPF & ESIC paid by the contractor to Govt. organization. (It may also be noted that the quoted rates are inclusive of all taxes.)	
4.	Whether copy of GST & PAN Card submitted?	
5.	Whether copy of registration of the firm/contractor with CPWD, MES, BRO, RAILWAY & MP PWD submitted?	
6.	Whether copy of registration of certificate registration for EPFO and certificate of registration for ESIC submitted? (Declaration, if not applicable) (Failing to submit the certificates offers will be summarily rejected).	
7.	Satisfactorily completed as a prime contractor at least one similar work of 80% value or two works of atleast 60% value or 3 works of atleast 40% value. (for non – enlisted contractors) Bidder has to submit on-line scanned copy of certificate of Work Order along with Work Completion certificate of similar nature work equal to required value during last five years issued by not below the rank of Executive Engineer.	
8.	Non-enlisted bidders are required to submit (i) Either Banker’s Certificate of Rs. 41.6 Lakh (Proforma as Appendix-E) OR Net worth Certificate of Rs. 13 Lakh (proforma as Appendix-D) AND Average Annual Turnover Certificate of Rs. 41.6 Lakh (Proforma as Appendix-C) on works during the last three financial years from a Chartered Accountant.	
9.	Tenderers should mention that Business dealing with their firms has not been banned by any Govt. / private agencies.	
10.	Tenderers should mention their address for communication with Telephone/Fax Number and e-mail address.	
11.	Whether all the Points under heading “Terms & Conditions”, “Additional Conditions” and instructions are fully abided by the contractor or not?	
12.	Whether all the requisite documents as asked in tender Schedule of inviting tender notice have been submitted by the tenderer?	
13.	Whether the firm has enclosed valid documents if the firm is a partnership proprietary in nature? (If no papers submitted with the bid it will be assumed that the firm is Single/Sole Proprietary)	
14.	Whether any other relevant documents which the firms wish to submit as a part of offer?	
15.	Tender acceptance letter (In firm’s letter head)	
16.	Integrity Pact (on firm’s letter head)	

SIGNATURE OF THE TENDERER

FORM OF CERTIFICATE OF ANNUAL TURNOVER ON WORKS FROM CHARTERED ACCOUNTANT

Certified that following is the annual turnover on works of the individual/firm/company as per returns filed with Income Tax Department for the past 3(three) financial years.

Name and registered address of individual / firm /company :.....

S. No.	Financial Year	Annual Turnover on Works in Rs. lakhs

Unique Document Identification Number (UDIN).....

(Signature of Chartered Accountant)

(Name of Chartered Accountant)

Membership No. of ICAI

Date and seal

FORM OF CERTIFICATE OF NET WORTH FROM CHARTERED ACCOUNTANT

It is to certify that as per the audited balance sheet and profit & loss account during the financial year, the networth of Shri/Smt/M/s..... (Name & Registered Address of individual/firm/company), is Rs..... after considering all liabilities. It is further certified that the networth of the individual/firm/company has not eroded by more than 50% during the last three years ending on 31st March

Unique Document Identification Number (UDIN).....

(Signature of Chartered Accountant)

(Name of Chartered Accountant)

Membership No. of ICAI

Date and seal

Appendix-“E”**FORM OF BANKER'S CERTIFICATE FROM A COMMERCIAL BANK**

This is to certify that to the best of our knowledge and information Shri/Smt/M/s..... having registered address, a customer of our bank, is/are respectable and can be treated as reliable for any engagement upto a limit of Rs..... (Rupees).

This certificate is issued without any guarantee or responsibility on the Bank or any of the officers. This certificate is issued on the request of Shri/Smt/M/S..... For obtaining Works tender in CRPF in..... (Name of Works).

(Signature)
For the Bank

Note:

- 1. Banker's certificates should be on the letter head of the bank, addressed to enlisting authority.**
- 2. In case of partnership firm, the certificate shall include names of all partners as recorded with the bank.**

NOTICE INVITING TENDER

The **DIG (Engr)**, Works Dte. invites online item rate bids for & on behalf of the President of India from approved and qualified firm/contractor with CPWD, MES, BRO, RAILWAY & MP PWD for **Repair and Maintenance of Ochterlony House at GC CRPF Neemuch (M.P)**

1. The enlistment of the contractors should be valid on the last date of submission of bids. In case the last date of submission of tender is extended, the enlistment of contractor should be valid on the original date of submission of bids.
 - 1.1 The estimated cost put to the work is **Rs. 68,53,203/- (Sixty Eight Lakh Fifty Three Thousand Two Hundred Three) only** including all taxes.
2. Agreement shall be drawn with the successful bidders on prescribed form of CPWD (or other Standard Form as mentioned) which is available as a Govt. of India Publication and also available on website www.cpwd.gov.in. Bidders shall quote his rates as per various terms and conditions of the said form which will form part of the agreement.
3. The work has to be completed by within **40 days** from the date of placing of Work Order or from the first date of handing over of the site, whichever is later, in accordance with the phasing, if any, indicated in the bid documents. Site of work is within the **RESTRICTED AREA**.
4. The site for the work is available.
5. The bid document consisting of plans, specifications, the schedule of quantities of various types of items to be executed and the set of terms and conditions of the contract to be complied with and other necessary documents except Standard General Conditions of Contract Form can be seen from CPP Portal (<http://eprocure.gov.in/eprocure/app>).
6. After submission of the bid the contractor can re-submit revised bid any number of times but before last time and date of submission of bid as notified.
7. While submitting the revised bid, contractor can revise the rate of one or more item(s) any number of times (he need not re-enter rate of all the items) but before last time and date of submission of bid as notified.
8. Bidder should deposit earnest money with required validity along with their Tender. Earnest Money should be in form of **Account payee Demand Draft, Fixed Deposit Receipt, Banker's Cheque** from any of the commercial banks in an acceptable form in favour of **THE DIGP GC, CRPF, NEEMUCH [Payable At-SBI, Kanawati Branch (Code-7293)]**

The Earnest Money shall be scanned and uploaded to the e-Tendering website within the period of bid submission. The physical EMD of the scanned copy of EMD uploaded shall be deposited in original at **Works Dte, Sec - 1, East Block, Block – 7, RK Puram, New Delhi – 110066** failing which the tender shall be rejected.

Interested contractor who wish to participate in the bid has to make following payments in the form of Demand Draft / Pay order or Banker's Cheque of any Scheduled Bank to the e-Tendering website within the period of bid submission:

- (i) Copy of Enlistment Order and other documents as specified in the press notice shall be scanned and uploaded to the e-Tendering website within the period of bid submission. Original Demand Draft of Earnest Money Deposit (EMD) shall be deposited in the office of the **Works Dte, Sec -1, East Block, Block – 7, RK Puram, New Delhi – 110066** before the due date of submission receipt of tender bids
 - (ii) **The bid/tender submitted shall be opened as per timing specified on CPP Portal.**
9. The bid/tender submitted shall become invalid and cost of bid shall not be refunded if:-
 - I. The bidders are found ineligible.
 - II. The bidders does not upload all the documents (including Labour Licence, GST registration, EPFO & ESIC registration, PAN card and copy of registration/enlistment) as stipulated in the bid document including the undertaking about deposition of physical EMD of the scanned copy of EMD uploaded.
 - III. Any discrepancy is noticed between the documents as uploaded at the time of submission of bid and hard copies as submitted physically in the office of tender opening authority.

10. The contractor whose tender is accepted will be required to deposit **PERFORMANCE SECURITY** for an amount of **Five percent (5%) of the value of the contract within a period of 07 (SEVEN) days after the Tender is accepted by the Competent Engineering Authority. Performance Security may be furnished in the form of an Fixed Deposit Receipt from a commercial bank in an acceptable form.** Performance Security should remain **valid for a period of 180 days (six months)** beyond the date of completion of all contractual obligation of the supplier including warranty obligations if any. In case the contractor fails to deposit the performance security within the stipulated period including extended period, if any, the Earnest Money deposited by the contractor shall be forfeited automatically without any notice to the contractor.
The contractor whose bid is accepted will also be required to furnish either copy of applicable licenses/registrations or Proof of applying for obtaining labour licenses and registration with EPFO & ESIC within the period specified in Schedule-“F”. Failing to submit the above certificates / documents, offers will be summarily rejected.
11. The reimbursement of EPF & ESI contributions paid by the contractor on the part of employer is to be made on submission of documentary proof of payment provided the same is in order.
12. Intending Bidders may inspect and examine the site and its surroundings and satisfy themselves before submitting their bids as to the nature of the ground and sub-soil (so far as is practicable), the form and nature of the site, the means of access to the site, the accommodation they may require and in general shall themselves obtain all necessary information as to risks, contingencies and other circumstances which may influence or affect their bid. A bidder shall be deemed to have full knowledge of the site and no extra charge consequent on any misunderstanding or otherwise shall be allowed. The bidders shall be responsible for arranging and maintaining at his own cost all materials, tools & plants, facilities for workers and all other services required for executing the work unless otherwise specifically provided for in the contract documents. Submission of a bid by a bidders implies that he has read this notice and all other contract documents and has made himself aware of the scope and specifications of the work to be done and of conditions and rates at which stores, tools and plant, etc. will be issued to him by the Government and local conditions and other factors having a bearing on the execution of the work.
13. The Competent Engineering Authority on behalf of the President of India does not bind itself to accept the lowest or any other bid and reserves to itself the authority to reject any or all the bids received without the assignment of any reason. All bids in which any of the prescribed condition is not fulfilled or any condition including that of conditional rebate is put forth by the bidders shall be summarily rejected.
14. Canvassing whether directly or indirectly, in connection with bidders is strictly prohibited and the bids submitted by the contractors who resort to canvassing will be liable for rejection.
15. The competent authority on behalf of President of India reserves to himself the right of accepting the whole or any part of the bid and the bidders shall be bound to perform the same at the rate quoted.
16. No Engineer of Gazetted Rank or other Gazetted Officer employed in Engineering or Administrative duties in an Engineering Department of the Government of India is allowed to work as a contractor for a period of one year after his retirement from Government service, without the prior permission of the Government of India in writing. This contract is liable to be cancelled if either the contractor or any of his employees is found any time to be such a person who had not obtained the permission of the Government of India as aforesaid before submission of the bid or before submission of the bid or engagement in the contractor's service.
17. The bid for the works shall remain open for acceptance for a period of Ninety (90)days from the end date of submission of bids, if any bidders withdraws his bid before the said period or issue of letter of acceptance, whichever is earlier, or makes any modifications in the terms and conditions of the bid which are not acceptable to the department, then the Government shall, without prejudice to any other right or remedy, be at liberty to forfeit 100% of the said earnest money as aforesaid. Further the bidders shall not be allowed to participate in the re-bidding process of the work.
18. This notice inviting Bid shall form a part of the contract document. The successful bidders/contractor, on acceptance of his bid by the Accepting Authority shall within 15 days from the stipulated date of start of the work, sign the contract consisting of:-
- The Notice Inviting Bid, all the documents including additional conditions, specifications and drawings, if any, forming part of the bid as uploaded at the time of invitation of bid and the rates quoted online at the time of submission of bid and acceptance thereof together with any correspondence leading thereto.
 - Standard C.P.W.D. Form 7/8 or other Standard C.P.W.D. Form as applicable.
19. The firm shall mention its authorized email address and mobile/land line number of authorized person to which any correspondence/virtual discussions can be made regarding the work. The firm shall ensure that contact details so provided are attended always & prompt action is taken on any message received.

**GOVERNMENT OF INDIA
CENTRAL RESERVE POLICE FORCE**

STATE: MADHYA PRADESH

Work Site : GC CRPF NEEMUCH (M.P.)

ITEM RATE TENDER & CONTRACT FOR WORKS

TENDER FOR THE WORK OF– Repair and Maintenance of Ochterlony House at GC CRPF Neemuch (M.P)

- (i) To be submitted online through website <http://eprocure.gov.in/eprocure/app>
- (ii) To be opened in online at **Works Dte, Sec -1, East Block, Block – 7, RK Puram, New Delhi – 110066**

T E N D E R

I/We have read and examined the Notice Inviting Tender, Schedule A, B, C, D, E & F, Specifications applicable, Drawings & Designs, General Rules and Directions, Conditions of Contract, Clauses of Contract, Special Conditions, Schedule of Rate and other documents and Rules referred to in the conditions of contract and all other contents in the tender document for the work.

I/We hereby tender for the execution of the work specified for the President of India within the time specified in Schedule-“F”, viz. Schedule of Quantities and in accordance in all respects with the Specifications, Designs, Drawings and instructions in writing referred to in Rule-1 of General Rules and Directions and in Clause-11 of the Conditions of Contract and with such materials as are provided for, by and in respects in accordance with, such conditions so far as applicable.

We agree to keep the tender open for Ninety (90) days from the date of opening of tender and not to make any modifications in its terms and conditions.

A sum of **Rs. 1,37,064/- (Rupees One Lakh Thirty Seven Thousand Sixty Four only)** is hereby forwarded in Bank Draft/ FDR of a Scheduled Bank/ Demand Draft of a scheduled bank as earnest money. If I/We, fail to furnish the prescribed performance guarantee within prescribed period, I/We agree that the said President of India or his successors, in office shall without prejudice to any other right or remedy, be at liberty to forfeit the said earnest money absolutely. Further, if I/We fail to commence work as specified, I/ We agree that President of India or the successors in office shall without prejudice to any other right or remedy available in law, be at liberty to forfeit the said performance guarantee absolutely. The said Performance Guarantee shall be a guarantee to execute all the works referred to in the tender documents upon the terms and conditions contained or referred to those in excess of that limit at the rates to be determined in accordance with the provision contained in Clause 12.2 and 12.3 of the tender form.

Further, I/We agree that in case of forfeiture of Earnest Money or Performance Guarantee as aforesaid, I/We shall be debarred for participation in the re-tendering process of the work. I/We undertake and confirm that eligible similar work(s) has/have not been got executed through another contractor on back to back basis. Further that, if such a violation comes to the notice of Department, then I/We shall be debarred for tendering in CRPF in future forever. Also, if such a violation comes to the notice of Department before date of start of work, the Engineer-in-Charge shall be free to forfeit the entire amount of Earnest Money Deposit/Performance Guarantee

I/We hereby declare that I/We shall treat the tender documents drawings and other records connected with the work as secret/confidential documents and shall not communicate information/derived there from to any person other than a person to whom I/We am/are authorized to communicate the same or use the information in any manner prejudicial to the safety & integrity of the State.

**Dated :
Witness:
Address:
Occupation:**

**Signature of Contractor
Postal Address**

ACCEPTANCE

The above tender (as modified by you as provided in the letters mentioned hereunder) is accepted by me for and on behalf of the President of India for a sum of Rs. (Rupees)

The letters referred to below shall form part of this contract agreement:-

- (a)
- (b)
- (c)

Dated: -

DIG (Engr) , Works Dte.
For and on behalf of the President of India

SCHEDULES (A TO F)**SCHEDULE - "A"**Name of work :- **Repair and Maintenance of Ochterlony House at GC CRPF Neemuch (M.P)**

Schedule of quantities:- As per BOQ :-

SCHEDULE - "B" :-

Schedule of materials to be issued to the contractor.

S.No.	Description of item.	Quantity.	Rate in figures & words at which the material will issue be charged to the contractor	Place of
(1)	(2)	(3)	(4)	(5)

----- NIL -----

SCHEDULE - "C" :-

Tools and plants to be hired to the contractor

S.NO.	DESCRIPTION.	HIRE CHARGES PER DAY	PLACE OF ISSUE
-------	--------------	----------------------	----------------

----- NIL -----

NOTE :-ALL THE TOOLS, PLANTS AND MACHINERY REQUIRED FOR CARRYING OUT THE SUBJECT WORK SHOULD BE OWNED/REGISTERED/LEASED EITHER IN THE NAME OF THE SOLE PROPRIETOR OF THE FIRM OR THE NAME OF FIRM AND THE CONTRACTOR SHALL ALSO MEET THE MINIMUM REQUIREMENT OF TOOLS, PLANTS AND MACHINERY SUCH AS VIBRATORY ROLLERS, PNEUMATIC WHEELED ROLLER, FULLY AUTOMATIC CONCRETE BATCHING PLANT, CONCRETE PAVER FINISHER ,CONTINUES TYPE HOT MIX PLANT, PAVER FINISHER (HYDRAULICALLY CONTROLLED SENSORS OPERATED ELECTRICALLY FOR THE PAVE FINISHER (HYDRAULICALLY CONTROLLED), BULL DOZERS, ROAD ROLLERS, DRILLING MACHINES, CONCRETE MOBILE WEIGH BATCHERS, TRANSIT MIXERS ONE BAG CAPACITY CONCRETE MIXER(DIESEL), VIBRATORS (NEEDLE AND PLATE TYPE), TRUCKS/ TIPPERS, TOTAL STATIONS, CONCRETE CUBE TESTING MACHINE(HYDRAULICALLY OPERATED), FULLY AUTOMATIC CONCRETE BATCHING PLANT AND ANY OTHER TOOLS, PLANTS AND MACHINERY REQUIRED FOR THE WORK AS PER GOOD ENGINEERING PRACTICE/RELEVANT IS-CODES WHICHEVER APPLICABLE.

SCHEDULE - "D" :-

Extra schedule for specific requirements/ documents for the work, if any - NIL

SCHEDULE- "E" :-

Reference to General Conditions of Contract:-

General Conditions of Contract for CPWD Works 2023 with upto-date amendments.

1.1	Name of Work:	(1) Repair and Maintenance of Ochterlony House at GC CRPF Neemuch (M.P)
1.2	Estimated Cost of work: -	Rs. 6853203/-
1.3	Earnest Money: -	Rs. 1,37,064/- (The EMD will be returned post receipt of Performance Guarantee)
1.4	Performance Guarantee	5% of tendered value(It shall be valid up to the stipulated date of completion Plus 180 days beyond that)

1.5 Security Deposit **2.5 %**

SCHEDULE- "F" :-

General Rules & Directions:-

Officer Inviting Tender: -

DIG (Engr)

Maximum percentage for quantity of items of work to be executed beyond which rates are to be determined in accordance with Clauses 12.2 & 12.3

See below

Definitions :-

2(v)	Engineer-In-Charge	AC Engr. or Designated by DC(Engr.)
2(viii)	Accepting Authority	DIG (Engr)
2(x)	Percentage on cost of Materials and labour to Cover all overheads and Profits	15%
2(xi)	Standard Schedule of Rates	DSR
2(xii)	Department	CRPF
9(ii)	Standard CPWD contract Form CPWD form 8 & General Conditions of Contract for CPWD Works-2023 with upto-date correction slips.	

Clause-1 :-

- | | | |
|------|---|-------------------------------|
| (i) | Time allowed for submission of Performance guarantee Programme Chart (Time & Progress) and from the date of issue of letter of acceptance. | 07 days |
| (ii) | Maximum allowable extension Beyond the period as provided in (i) above | 10 days by DC (Engineer) Dte. |

Clause-1A :- Recovery of Security Deposit as per GCC :- **Applicable**

Clause-2 :- Authority for fixing compensation under clause 2. **DIG (Engr)**

Clause-2A:- Whether Clause 2A shall be applicable **No**

Clause- 3 :- Applicable

Clause 3A:- Applicable

Clause 4 :- Applicable

Clause-5:- Applicable

Time allowed for execution of work **40 days**

Authority to decide

- | | | |
|------|--|---|
| i) | Extension of time | Since, it is an emergent work, time is of essence and work has to be completed within time for completion mentioned in tender/work order. No request for extension of time shall be entertained. |
| ii) | Rescheduling of mile stones | NA |
| iii) | Shifting of date of start in case of delay in handing over of site | DIG (Engr) |

Clause-6 :-	Computerized Measurement Book	No
Clause-7A :-	Whether Clause 7A shall be applicable	Applicable
Clause 8 :-	Completion Certificate and Completion Plans	Applicable
Clause-8A :-	Completion Plans to be Submitted by the Contractor	Applicable.
Clause-9 :-	Payment of Final Bill	Applicable.
Clause 9A :-	Payment of Contractor's Bills to Banks	Applicable.
Clause-10A:-	Materials to be provided by the Contractor	Applicable
Clause-10-B		
(i)	Secured Advance on Materials	No
(ii)	Whether Mobilization advance will be paid	No
Clause-10C:-		
	Payment on Account of Increase in Prices/ Wages due to Statutory Order(s)	Not applicable.
Clause-10 CA:-		
	Payment due to variation in prices of materials after receipt of tender	Not applicable.
Clause-10-CC:-		
	Payment due to Increase / Decrease in Prices/ Wages (excluding materials covered under clause 10 CA) after Receipt of Tender for Works	Not applicable
Clause 10 D :-Dismantled Material Govt. Property		
	The contractor shall treat all materials obtained during dismantling of a structure, excavation of the site for a work, etc. as Government's property and such materials shall be disposed off to the best advantage of Government according to the instructions in writing issued by the Engineer-in-Charge.	
Clause-11:-	Work to be Executed in Accordance with Specifications, Drawings, Orders etc.	
	The contractor shall execute the whole and every part of the work in the most substantial and workmanlike manner both as regards materials and otherwise in every respect in strict accordance with the specifications. The contractor shall also conform exactly, fully and faithfully to the design, drawings and instructions in writing in respect of the work signed by the Engineer-in-Charge and the contractor shall be furnished free of charge one copy of the contract documents together with specifications, designs, drawings and instructions as are not included in the standard specifications of Central Public Works Department specified in Schedule 'F' or in any Bureau of Indian Standard or any other, published standard or code or, Schedule of Rates or any other printed publication referred to elsewhere in the contract. The contractor shall comply with the provisions of the contract and with the care and diligence execute and maintain the works and provide all labour and materials, tools and plants including for measurements and supervision of all works, structural plans and other things of temporary or permanent nature required for such execution and maintenance in so far as the necessity for providing these, is specified or is reasonably inferred from the contract. The Contractor shall take full responsibility for adequacy, suitability and safety of all the works and methods of construction.	
Clause-12:-		
	Authority to decide deviation/extra items(As per CPWD norms)	DIG (Engr)
Clause -14: - Carrying out part work at risk & cost of contractor(Authority to decide)		DIG (Engr)
Clause-16:-	Competent Authority for deciding reduced rates.	DIG (Engr)
Clause17:	<u>Contractor Liable for Damages, defects during defect liability period</u>	

If the contractor or his working people or servants shall break, deface, injure or destroy any part of building in which they may be working, or any building, road, road kerb, fence, enclosure, water pipe, cables, drains, electric or telephone post or wires, trees, grass or grassland, or cultivated ground contiguous to the premises on which the work or any part is being executed, or if any damage shall happen to the work while in progress, from any cause whatever or if any defect, shrinkage or other faults appear in the work within twelve months (six months in the case of work costing Rs. Ten lacs and below except road work) after a certificate final or otherwise of its completion shall have been given by the Engineer in- Charge as aforesaid arising out of defect or improper materials or workmanship the contractor shall upon receipt of a notice in writing on that behalf make the same good at his own expense or in default the Engineer-in-Charge cause the same to be made good by other workmen and deduct the

expense from any sums that may be due or at any time thereafter may become due to the contractor, or from his security deposit or the proceeds of sale thereof or of a sufficient portion thereof. The security deposit of the contractor shall not be refunded before the expiry of twelve months after the issue of the certificate final or otherwise, of completion of work. Provided that in the case of road work, if in the opinion of the Engineer-in-Charge, half of the security deposit is sufficient, to meet all liabilities of the contractor under this contract, half of the security deposit will be refundable after six months and the remaining half after twelve months of the issue of the said certificate of completion.

In case of Maintenance and Operation works of E&M services, the security deposit deducted from contractors shall be refunded within Two months from the date of final payment or within Two months from the date of completion of the maintenance contract whichever is earlier.

Clause-18:- Tools & Plants etc.

The contractor shall provide at his own cost all materials machinery, tools & plants as specified in schedule F. In addition to this, appliances, implements, other plants, ladders, cordage, tackle, scaffolding and temporary works required for the proper execution of the work, whether original, altered or substituted and whether included in the specifications or other documents forming part of the contract or referred to in these conditions or not, or in-Charge as to any matter as to which under these conditions he is entitled to be satisfied, or which he is entitled to require together with carriage therefore to and from the work. The contractor shall also supply without charge the requisite number of persons with the means and materials, examination at any time and from time to time of the work or materials. Failing his so doing, the same may be provided by the Engineer-in-Charge at the expense of the contractor and the expenses may be deducted, from any money due to the contractor, under this contract or otherwise and/or from his security deposit or the proceeds of sale thereof, or of a sufficient portions thereof.

Clause-19 :- Labour Laws to be complied by the contractor Applicable.

Clause-19A :- No labour below the age of Eighteen years shall be employed on the work. Applicable.

Clause-19C :- Applicable.

Clause -19D :- Applicable.

Clause -19K :- Employment of skilled/semi skilled workers

The contractor shall, at all stages of work, deploy skilled/semi skilled tradesmen who are qualified and possess certificate in particular trade from CPWD Training Institute/Industrial Training Institute/ National Institute of construction Management and Research (NICMAR)/ National Academy of Construction, CIDC or any similar reputed and recognized Institute managed/ certified by State/Central Government. The number of such qualified tradesmen. The contractor shall submit number of man days required in respect of each trade, its scheduling and the list of qualified tradesmen along with requisite certificate from recognized Institute to Engineer in charge for approval. Notwithstanding such approval, if the tradesmen are found to have inadequate skill to execute the work of respective trade, the contractor shall substitute such tradesmen within two days of written notice from Engineer in- Charge. Failure on the part of contractor to obtain approval of Engineer-in-Charge or failure to deploy qualified tradesmen will attract a compensation to be paid by contractor at the rate specified in schedule 'F' per such tradesman per day. Decision of Engineer in Charge as to whether particular tradesman possesses requisite skill and amount of compensation in case of default shall be final and binding. Provided always, that the provisions of this clause, shall not be applicable for works with estimated cost put to tender being less than Rs. 5 crores. For work costing more than Rs. 10 Crores, and uptoRs. 50 Crores, the contractor shall arrange on site training as per National Skill Development Corporation (NSDC) norms for at least 20% of the unskilled workers engaged in the project in co-ordination with the CPWD Regional Training Institute& National Skill Development Corporation (NSDC) for certification at the level of skilled/semi skilled tradesmen. For works costing more than Rs. 50 Crores, the contractor shall arrange on site training as per National Skill Development Corporation (NSDC) norms for at least 30% of the unskilled worker engaged in the project in co-ordination with the CPWD Regional Training Institute & National Skill Development Corporation (NSDC) for certification at the level of skilled/semi skilled tradesmen. The cost of such training as stated above shall be born by the Government. The necessary space and workers shall be provided by the contractor and no claim what so ever shall be entertained.

Clause-19L :- Contribution of EPF & ESI Applicable.

Clause-20 :- Minimum wages act to be complied with. Applicable.

Clause 21 :- Work not to be sublet. Action in case of in solvency

The contract shall not be assigned or sublet without the written approval of the Engineer-in Charge. And if the contractor shall assign or sublet his contract, or attempt to do so, or become insolvent or commence any insolvency proceedings or make any composition with his creditors or attempt to do so, or if any bribe, gratuity, gift, loan, perquisite, reward or advantage pecuniary or otherwise, shall either directly or indirectly, be given, promised or

offered by the contractor, or any of his servants or agent to any public officer or person in the employ of Government in any way relating to his office or employment, or if any such officer or person shall become in any way directly or indirectly interested in the contract, the Engineer-in-Charge on behalf of the President of India shall have power to adopt the course specified in Clause 3 hereof in the interest of Government and in the event of such course being adopted, the consequences specified in the said Clause 3 shall ensue.

Clause 25 Settlement of Dispute by Conciliation and Arbitration

(i)	Conciliator	--	IG (Works)
(ii)	Arbitrator Appointing Authority	--	IG (Works)
(iii)	Place of Arbitration	--	New Delhi

Clause 28 Action where no Specifications are specified

In the case of any class of work for which there is no such specifications as referred to in Clause 11, such work shall be carried out in accordance with the Bureau of Indian Standards Specifications. In case there are no such specifications in Bureau of Indian Standards, the work shall be carried out as per manufacturers' specifications, if not available then as per state/ District Specifications. In case there are no such specifications as required above, the work shall be carried out in all respects in accordance with the instructions and requirements of the Engineer-in-Charge.

Clause 30 Water for Works

The contractor(s) shall make his/their own arrangements for water required for the work and nothing extra will be paid for the same. This will be subject to the following conditions.

(i) That the water used by the contractor(s) shall be fit for construction purposes to the satisfaction of the Engineer-in-Charge.

(ii) The Engineer-in-Charge shall make alternative arrangements for supply of water at the risk and cost of contractor(s) if the arrangements made by the contractor(s) for procurement of water are in the opinion of the Engineer-in-Charge, unsatisfactory.

(iii) WATER CHARGES:- The contractor has to make its own arrangement for water supply required for execution of the work, If water is used from CRPF campus then 1% amount of tendered cost shall be levied from contractor.

(iv) ELECTRICITY CHARGES:- The contractor has to make its own arrangement for power supply required for execution of the work, If electricity is provided by CPRF campus then charges shall be applied on contractor as decided by Engineer-in-charge.

Clause 31 Hire of Plant & Machinery

The contractor shall arrange at his own expense all tools, plant, machinery and equipment (hereinafter referred to as T&P) required for execution of the work.

Clause 32,33,34& 35

Applicable

Clause-32 Requirement of technical representative(s) and recovery rate

Sl. No.	Minimum qualification of technical representative	Minimum Experience	Designation of Technical Staff	Nos.	Rate at which recovery shall be made from the contractor in the event of not fulfilling provision of Clause 32	
					Figure	Words
1.	Graduate or Diploma Engineer	2 or 5 years (respectively) experience of similar nature of works	Project planning/Quality/Billing Engineer	1+1	<u>Rs. 25,000/- per month</u>	Rupees Twenty Five Thousand per month

Assistant Engineers retired from Govt. Services who are holding Diploma will be treated at par with Graduate Engineers.

Clause 37 :- No engineer of gazetted rank or other gazetted officer employed in engineering or administrative duties in an engineering department of the Government of India shall work as a contractor or employee of a contractor for a period of one year after his retirement from government service without the previous permission of Government of India in writing. This contract is liable to be cancelled if either the contractor or any of his employees is found at any time to be such a person who had not obtained the permission of Government of India as aforesaid, before submission of the tender or engagement in the contractor's service, as the case may be.

DIG (Engineer), Works Dte.
For and on behalf of the President of India

INTEGRITY PACT

To,

DIG (Engineer),
Works Branch, CRPF, Dte.
New Delhi.

Sub: Submission of Tender for the work of.....

Dear Sir, I/We acknowledge that CRPF is committed to follow the principles thereof as enumerated in the Integrity Agreement enclosed with the tender/bid document.

I/We agree that the Notice Inviting Tender (NIT) is an invitation to offer made on the condition that I/We will sign the enclosed integrity Agreement, which is an integral part of tender documents, failing which I/We will stand disqualified from the tendering process. I/We acknowledge that THE MAKING OF THE BID SHALL BE REGARDED AS AN UNCONDITIONAL AND ABSOLUTE ACCEPTANCE of this condition of the NIT.

I/We confirm acceptance and compliance with the Integrity Agreement in letter and spirit and further agree that execution of the said Integrity Agreement shall be separate and distinct from the main contract, which will come into existence when tender/bid is finally accepted by CRPF. I/We acknowledge and accept the duration of the Integrity Agreement, which shall be in the line with Article 1 of the enclosed Integrity Agreement.

I/We acknowledge that in the event of my/our failure to sign and accept the Integrity Agreement, while submitting the tender/bid, CRPF shall have unqualified, absolute and unfettered right to disqualify the tenderer/bidder and reject the tender/bid in accordance with terms and conditions of the tender/ bid.

Yours faithfully

(Duly authorized signatory of the Bidder)

To be signed by the bidder and same signatory competent / authorized to sign the relevant contract on behalf of CRPF.

INTEGRITY AGREEMENT

This Integrity Agreement is made at..... on thisday of 20.....

BETWEEN

President of India represented through DIG GC CRPF NEEMUCH (M.P.).

.....
(Name of Zone)
CRPF,, (Hereinafter referred as the
(Address of Office)

‘Principal/Owner’, which expression shall unless repugnant to the meaning or context hereof include its successors and permitted assigns)

AND
(Name and Address of the Individual/firm/Company)

through (Hereinafter referred to as the
(Details of duly authorized signatory)

“**Bidder/Contractor**” and which expression shall unless repugnant to the meaning or context hereof include its successors and permitted assigns)

Preamble

WHEREAS the Principal / Owner has floated the Tender (NIT No) (hereinafter referred to as “Tender/Bid”) and intends to award, under laid down organizational procedure, contract for
(Name of work)

hereinafter referred to as the “Contract”.

AND WHEREAS the Principal/Owner values full compliance with all relevant laws of the land, rules, regulations, economic use of resources and of fairness/transparency in its relation with its Bidder(s) and Contractor(s).

AND WHEREAS to meet the purpose aforesaid both the parties have agreed to enter into this Integrity Agreement (hereinafter referred to as “Integrity Pact” or “Pact”), the terms and conditions of which shall also be read as integral part and parcel of the Tender/Bid documents and Contract between the parties.

NOW, THEREFORE, in consideration of mutual covenants contained in this Pact, the parties hereby agree as follows and this Pact witnesses as under:

IN WITNESS WHEREOF the parties have signed and executed this Integrity Pact at the place and date first above mentioned in the presence of following witnesses:

.....
(For and on behalf of Principal/Owner)

.....
(For and on behalf of Bidder/Contractor)

WITNESSES: 1(signature, name and address)

2 (signature, name and address)

Place:

Dated :

Instructions for online Bid submission

Instructions to the Bidders to submit the bids online through the Central Public Procurement Portal for e-Procurement at <https://eprocure.gov.in/eprocure/app>

- 1) Possession of valid Digital Signature Certificate (DSC) and enrolment/ registration of the contractors/bidders on the e-procurement /e-tender portal is a prerequisite for e-tendering.
- 2) Bidder should do the enrolment in the e-Procurement site using the “Click to Enrol” option available on the home page. Portal enrolment is generally free of charge. During enrolment/registration, the bidders should provide the correct/true information including valid eMail ID. All the correspondence shall be made directly with the contractors/bidders through eMail ID provided.
- 3) Bidder need to login to the site thro“ their user ID / password chosen during enrolment / registration.
- 4) Then the Digital Signature Certificate (Class II or Class III Certificates with signing key usage) issued by SIFY/TCS/n-Code/ e-Mudra or any Certifying Authority recognized by CCA India on e-Token/Smart Card, should be registered.
- 5) The DSC that is registered only should be used by the bidder and should ensure safety of the same.
- 6) Contractor/Bidder may go through the tenders published on the site and download the required tender documents/ schedules for the tenders he/she is interested.
- 7) After downloading / getting the tender document/schedules, the Bidder should go through them carefully and then submit the documents as asked, otherwise bid will be rejected.
- 8) If there are any clarifications, this may be obtained online thro“ the tender site, or thro“ the contact details. Bidder should take into account the corrigendum published before submitting the bids online.
- 9) Bidder then logs in to the site through the secured log in by giving the user id/password chosen during enrolment/registration and then by giving the password of the e-Token/Smart Card to access DSC.
- 10) Bidder selects the tender which he/she is interested in by using the search option & then moves it to the „my tenders“ folder.
- 11) From my tender folder, he selects the tender to view all the details indicated.
- 12) It is construed that the bidder has read all the terms and conditions before submitting their offer. Bidder should go through the tender schedules carefully and upload the documents as asked; otherwise, the bid will be rejected.
- 13) Bidder, in advance, should get ready the bid documents to be submitted as indicated in the tender document/ schedule and generally, they can be in PDF/xls/rar/zip formats. If there is more than one document, they can be clubbed together and can be provided in the requested format. Each document to be uploaded through online for the tenders should be less than 2 MB. If any document is more than 2MB, it can be reduced through zip/rar and the same can be uploaded, if permitted. Bidders Bid documents may be scanned with 100 dpi with 12 black and white option. However of the file size is less than 1 MB the transaction uploading time will be very fast.
- 14) If there are any clarifications, this may be obtained through the site, or during the pre-bid meeting if any. Bidder should take into account the corrigendum published from time to time before submitting the online bids.
- 15) The Bidders can update well in advance, the documents such as certificates, annual report details etc., under My Space option and these can be selected as per tender requirements and then send along with bid documents during bid submission. This will facilitate the bid submission process faster by reducing upload time of bids.
- 16) Bidder should submit the EMD as specified in the tender. The original should be Posted / couriered/given in person to the Tender Inviting Authority, within the bid submission due date & time for the tender. Scanned copy of the instrument should be uploaded as part of the offer.
- 17) While submitting the bids online, the bidder reads the terms & conditions and accepts the same to proceed further to submit the bid packets.

- 18) The bidder has to select the payment option as offline to pay the EMD as applicable and enter details of the instruments.
- 19) The details of the DD/any other accepted instrument, physically sent, should tally with the details available in the scanned copy and the data entered during bid submission time. Otherwise submitted bid will not be acceptable.
- 20) The bidder has to digitally sign and upload the required bid documents one by one as indicated. Bidders to note that the very act of using DSC for downloading the bids and uploading their offers shall be deemed to be a confirmation that they have read all sections and pages of the bid document including General conditions of contract without any exception and have understood the entire document and are clear about the requirements of the tender requirements.
- 21) The bidder has to upload the relevant files required as indicated in the cover content. In case of any irrelevant files, the bid will be rejected.
- 22) Tenderers should submit price bid in format available Annexure in **CPP Portal <http://eprocure.gov.in/eprocure/appand>** and don't change the name of downloaded Annexure. Only fill the area which is available to fill and validate by the given button in Annexure, save the file and upload the file on portal.
- 23) The bidders are requested to submit the bids through online e-tendering system to the Tender Inviting Authority (TIA) well before the bid submission end date & time (as per Server System Clock). The TIA will not be held responsible for any sort of delay or the difficulties faced during the submission of bids online by the bidders at the eleventh hour.
- 24) After the bid submission (i.e after Clicking "Freeze Bid Submission" in the portal), the acknowledgement number, given by the system should be printed by the bidder and kept as a record of evidence for online submission of bid for the particular tender and will also act as an entry pass to participate in the bid opening date.
- 25) The time settings fixed in the server side & displayed at the top of the tender site, will be valid for all actions of requesting, bid submission, bid opening etc., in the e-tender system. The bidders should follow this time during bid submission.
- 26) All the data being entered by the bidders would be encrypted using PKI encryption techniques to ensure the secrecy of the data. The data entered will not viewable by unauthorized persons during bid submission & not be viewable by any one until the time of bid opening.
- 27) Any bid document that is uploaded to the server is subjected to symmetric encryption using a system generated symmetric key. Further this key is subjected to asymmetric encryption using buyers/bid openers' public keys. Overall, the uploaded tender documents become readable only after the tender opening by the authorized bid openers.

ADDITIONAL TERMS AND CONDITIONS

- (i) **PAYMENT:-** (a) Works are required to be executed on credit basis only and payment will be released after submission of RA bill by the contractor and scrutiny by the department.
- (b) Payment in advance or immediately cannot be made.
- (c) The Payment action will be processed on production of the following documents:
 - (i) Bill in Triplicate.
 - (ii) A Copy of award of work.
 - (iii) A copy of Certificate issued by DIG GC CRPF NEEMUCH (M.P.) in consultation with Engineer-in-charge that contracted work for the period for which payment has been claimed, has carried out by the contractor satisfactory.
- (d) GST/TDS/GST-TDS/ Labour Cess and other taxes will be deducted from the Bill of Contractor by RPAO as per norms. EPF & ESIC shall be reimbursed only on submission of proof of payment by contractor to concerned authorities.
- (e) **Since work have to be completed in a very limited time, only final bill will be done on 100% completion of work.** RA bill should be checked by Insp/SI (Civil) & Engineer-in-charge and countersigned by Estate Officer before release of payment. Security Deposit of 2.5% shall be retained from the Work Done in the RA Bill which will be paid after completion of Defect Liability Period.

(ii) **MEASUREMENT:** Entire work done at Site shall be recorded in measurement book duly signed by Contractor & Insp/SI (Civil) & AC(Engr). Measurements in measurement book shall be recorded jointly by contractor/authorized representative of contractor and Insp/SI Civil and 50% MB checked & signed by AC(Engr) before processing bill to Estate Officer for counter sign.

(iii) **COMPLETION CERTIFICATE:** Upon Completion of Work, Contractor shall intimate Estate Officer in writing of completion of work. If Estate Office is completely satisfied with the work, he shall issue Completion Certificate duly signed by Engineer-in-Charge (AC Engr) within 20 days of intimation of contractor. If Minor Defects Persists, Provisional Completion Certificate can be issued subject to rectification of defects brought out by Estate Officer. A suitable time frame for rectification of such defects shall also be intimated by Estate Officer in writing beyond which DIG Engineer Dte. Shall be empowered to rectify the defects through other agency at risk and cost of the contractor. This period shall not be less than 30 days and should not exceed 180 days in any case from the date of intimation of defects. Such defects list shall be made part of Provisional Completion certificate by Estate Officer.

(iv) **DISPUTE IN CONTRACT:-**In case of any ambiguity in the provisions of the Contract Agreement, Decision of Accepting Officer shall be Final & Binding on the Contractor. **GCC works-2023 (construction/maintenance) with upto date correction slips will prevail and applicable.**

(v) All materials required to be used on works shall be got approved from the Engineer-in-charge in advance. In case of doubt on any material, Engineer-in-charge has right to get the material tested from any Govt. approved labs/NABL and the charges for the same shall be borne by the contractor, upto the overall amount of Rs. 02 lakh in entire work. Beyond Rs. 02 lakh, the cost of such test shall be borne by the contractor if sample fails in the test & by CRPF if sample passes the test.

(vi) The quoted rate should be inclusive of all taxes, levies, works contract taxes, duties etc.

(vii) All items to be used in this work should be branded and ISI certified. In this case CPWD approved list of material for similar work may be followed. If any make is not specified, decision of Engineer-in-charge shall be final and binding.

(viii) Payment to contractor shall be released only after submission of purchase voucher of all new items.

(ix) **TERMINATION OF CONTRACT :-**

In case of violation/breach of any agreed terms and conditions of contract and persistently failure/negligence to observe and perform all or any of the acts, deeds, matters or things to be observed and performed by the Contractor. Tender Accepting Authority may cancel/Terminate this contract and the performance security deposit will be forfeited.

(x) **CONFLICT OF INTEREST**

The bids of any tenderer may be rejected if a conflict of interest between the bidder and CRPF is detected at any stage. Tender Accepting Authority reserves the right to accept or reject the tender without assigning any reason whatsoever.

(xi) Conditional tender is not acceptable and will be summarily rejected.

(xii) **DEFECT LIABILITY PERIOD:** - Defect liability period is 02 years, which will be reckoned from the date of final and complete handing/taking over of building/infrastructure. If any defects occurs/noticed during this period, then a notice in this regard will be issued to the contractor and it is the responsibility of contractor to rectify/repair the defects at his own cost. The work must be got started by the contractor within 15 days after receipt of the 1st notice. If the contractor is unable or unwilling to repair the defects, the competent authorities reserves full rights to forfeit the security deposit and may blacklisted/debarred the firm and rectify the defects at risk and cost of the contractor. Any amount on this account due to the department shall be recovered from the Contractor.

(xiii) Payment for execution of electrical works will be done only after inspection by the BOO/electrical engineer of State Electrical Department/any Govt. electrical engineer(serving) detailed by Estate Officer/Engineer-in-charge. A completion certificate is required to be submitted by the BOO/electrical engineer of State Electrical Department/any Govt. electrical engineer(serving). Any charges if occurs that will be borne by the contractor. No payment in this regard will be done by the CRPF.

(xvi) All credit obtained during dismantling shall be deposited with CRPF.

LIST OF MAKES

MATERIALS :Unless specific makes/manufacturers are specified in the tender documents all the materials to be procured by the contractor for incorporation in the work under this contract (with the exception of local materials like bricks, stone aggregate, stones, sand etc) shall be with ISI certifications mark.

SAMPLES OF MATERIALS: The contractor shall produce samples of all materials and shall obtain approval in writing from Engineer-in-charge before he places bulk order for the materials for incorporation in the work. The contractor shall not procure materials unless the samples are first got approved from the Engineer-in-charge .

TESTING : The contractor shall submit the manufacturer's test certificate in original along with the Test Sheet giving the result of each physical test as applicable and the chemical composition of the cement or authenticated copy thereof, duly signed by the manufacturer with each consignment clearly bringing out lot No. The Engineer-in-Charge shall record these details in the Cement Supply & Acceptance register

Following mandatory tests shall be carried out for cement procured by the Contractor:

- (i) Initial and final setting time
- (ii) Soundness test
- (iii) Compressive strength test at 3, 7 & 28 days as specified in relevant IS code.

CONCRETE

MATERIALS FOR CONCRETE:-

- I. **LIME**: Lime shall be eminently hydraulic lime (Class 'A') and shall conform to IS:712.
- II. **CEMENT**: Cement shall be stored in dry a place covered all round and no stacks shall be more than 15 bags high.
- III. **COARSE AGGREGATE**: Coarse aggregate shall be crushed stone aggregate and shall conform to standard specifications followed in the industry.

LIST OF APPROVED MANUFACTURERS AND MAKES

S/NO.	NAME OF PRODUCT	MAKES/BRANDS/MANUFACTURERS
1	ORDINARY PORTLAND CEMENT	J.K., ACC, AMBUJA, BIRLA
2	REINFORCEMENT BARS	TATA STEEL (TISCON), SAIL (EQR/ SEQR), RINL, JINDAL (JSW NEOSTEEL/PANTHER)
3	EXPANSION JOINTS	J.SONGS, METCO, SANFIELD (INDIA) P LTD. Z-TECH (INDIA) PVT. LTD.
4	ADMIXTURES FOR CONCRETE	FOSROC, SIKA, MBT, ASIAN LABORATORIES DURA BUILD CARE, BASF, FEVICOL, CICO TECHNOLOGIES LTD
5	STRUCTURAL STEEL	TATA, SAIL, RINL. ISCO, SRMB
6	WELDING ELECTRODES	ESAB, ADVANI-ORLIKON, WELD ALLOY
7	WATER PROOFING	SIKA, PIDILITE, ASIAN PAINTS, FOSROC
8	SYNTHETIC ENAMEL PAINT	ICI (SUPER GLOCE), NEROLAC, BERGER (LUXOL), JENSONS AND NICHOLSON, ASIAN PAINTS (APCOLITE). CICO, MBT, FOSROC
9	ANTI CARBONATION PAINTS	CICO, MBT, FOSRO
10	THERMOPLASTIC PAINTS	CBM, CMS, RELIANCE THERMOPLAST
11	RMC	RMC, ACC, BIRLA, L&T AND OTHER REPUTED

		MANUFACTURE OF RMC SUBJECTED TO APPROVAL OF ENGINEER-IN-CHARGE
12	TMT FE 415/500	TISCON, ISCON, RINL, SAIL, JINDAL
13	WHITE CEMENT	BIRLA WHITE, J.K. WHITE
14	PUTTY	BIRLA, J.K. PUTTY OR EQUIVALENT.
15	WASH BASIN	PARRYWARE, CER, JAQUAR.
16	CLEAR GLASS	MODI GUARD, SAINT GOBAIN, AIS
17	G.I. PIPES	TATA STEEL TUBES, JINDAL, PRAKASH, SURYA
18	G.I. FITTINGS	UNIK, KS, AMCO, AVR, NVR, RR
19	HUBLESS CENTRIFUGALLY CAST IRON SPUN PIPES & FITTINGS IS:151205	NECO, HEPCO OR EQUIVALENT.
20	DI PIPES & FITTINGS	KESORAM, ELECTROSTEEL OR EQUIVALENT
21	CP BRASS FITTINGS	PARRYWARE, JAQUAR, CERA
22	BRASS STOP & BIB COCK	ZOLOTO, SANT, L&T, LEADER, CERA
23	ALUMINIUM SECTIONS (ANODISING BY APPROVED ANODIZING FIRM)	HINDALCO, JINDAL, INDIAN ALUMINIUM CO. OR AS APPROVED BY ENGINEER-IN-CHARGE
24	STAINLESS STEEL KITCHEN SINK	NIRALI, JAYNA, PRAYAG, JINDAL
25	PLASTIC W.C. SEAT COVER	PARRYWARE, HINDWARE, CERA
26	UPVC WINDOW	FENESTA, EWIN, REHAU
27	PVC TANKS	SINTEX, SUPREME, ASTREL-3 OR LAYERED MORE ISI MARKED
28	MIRROR GLASS	ATUL, SAINT GOBAIN, MODI GUARD, HNG, CERA
29	CP WASTE & FLUSH PIPES	AS APPROVED BY ENGINEER-IN-CHARGE.
30	PVC FLUSHING CISTERN.	PARRYWARE, HINDWARE, JOHNSON, CERA
31	TILE FIXER / ADHESIVE	AS APPROVED BY ENGINEER-IN-CHARGE.
32	VENEERED PARTICLE BOARD	NOVAPAN, KITPLY, ANCHOR, NATIONAL, ARCHIDPLY, CENTURY PLY
33	LAMINATED PARTICLE BOARD / LAMINTAES	NOVAPAN, KITPLY, NATIONAL, ARCHIDPLY, CENTURY PLY, ECOBOARD.
34	FLUSH DOOR SHUTTERS	DURO, ARCHIDPLY, KUTTY FLUSH DOOR, KITPLY INDUSTRIES (SWASTIK), CENTURY PLY. OR AS APPROVED BY ENGINEER-IN- CHARGE
35	FACTORY MADE PANELLED & WIRE GAUGE WOODEN DOOR/ WINDOW SHUTTERS	AS APPROVED BY ENGINEER-IN-CHARGE
36	STEEL WINDOWS / PRESSED STEEL FRAMES	AS APPROVED BY ENGINEER-IN-CHARGE.
37	M.S PIPE	TATA, JINDAL, BHUSHAN INDUSTRIES, PRAKASH STEEL TUBES, OR AS APPROVED BY ENGINEER-IN-CHARGE
38	PVC PIPE & FITTINGS	SUPREME, AKG, FINOLEX, PRINCE, SFMC
39	ACRYLIC DISTEMPER	NEROLAC, BERGER (BISION ACRYLIC) ASIAN PAINTS (TRACTOR ACRYLIC) IST QUALITY, DULUX WEATHER SHIELD, ICI
40	DRY DISTEMPER	BERGER (CASTLE), JENSON & NICHOLSEN (J&N)
41	STEEL PRIMER	ICI, NEROLAC, BERGER, ASIAN PAINTS. IST QUALITY
42	WOOD PRIMER	ICI, NEROLAC, BERGER, ASIAN PAINTS. IST QUALITY
43	MOSAIC TITLES / CHEQUERED TILES	HINDUSTAN, JONSON, NITCO, MODERN, NTC, A-1
44	CERAMIC WALL TILES	KAJARIA, SOMANY, JOHNSON, AGL, VERMORA

45	DASH / ANCHORING FASTENERS	HILTI / FISCHER OR EQUIVALENT
46	NUTS / BOLTS & SCREWS	GKW, ATUL OR EQUIVALENT
47	FLOAT VALVE	LEADER, PRAYAG, ZOLOTO, L&T
48	CP FITTINGS/MIXER PILLAR TAP WASHERS	JAQUAR, HINDWARE, PARRYWARE, CERA
49	CP ACCESSORIES	JAQUAR, HINDWARE, PARRYWARE, CERA
50	C.I SLUICE VALVES & REFLEX VALVES GUN METAL GATE VALVES, GLOBES	LEADER, ZOLOTO, SANT, KIRLOSKER, L&T
51	STONE WARE PIPES & GULLY TRAPES	PERFECT, HIND OR ISI MARKED S.W PIPES OR AS APPROVED BY ENGINEER-IN-CHARGE
52	GLAZED FIRE CLAY KITCHEN SINK	PAMINI, SANFIRE, RKCP OR AS APPROVED BY ENGINEER-IN-CHARGE
53	VITRIFIED TILES	JOHNSON, AGL, VARMORA, KAJARIA, SOMANY
54	WATER METER	PRIMA (ISI), KRANTI, DASHMESH OR BIS MARKED PRODUCT
55	GROUTING COMPOUND	ENDURA, PIDILITE OR AS APPROVED BY ENGINEER-IN-CHARGE
56	GLASS MOSAIC TILES	ITALIA, OPIO OR AS APPROVED BY ENGINEER-IN-CHARGE
57	PAVER BLOCKS & CURVE STONES	NITCO PREFEB, ULTRA KK, TERRAFIRMA, UNISTONE, UNITILE, NTC, ISI MARKED
58	GLASS MOSAIC TILES	ITALIA, OPIO OR AS APPROVED BY ENGINEER-IN-CHARGE
59	NON RETURN VALVE (CHECK VALVE)1/2" TO 1/4"	KALSI PUMP PVT. LTD, ZOLOTO, SAKARAL, UNIK OR BIS APPROVED PRODUCTS.
60	LINE FILTER VALVE 1/2" TO 2"	KALSI PUMP PVT. LTD OR BIS APPROVED PRODUCTS.
61	FERRULES 15 MM, 20MM & 25 MM	DHAWAN SANITARY UDYOG (PRIMA) OR BIS APPROVED PRODUCTS
62	STAINLESS STEEL STAIRCASE RAILING	JINDAL S S LTD, ICICH INDUS, ESSAL, DORMA OR AS APPROVED BY ENGINEER-IN-CHARGE
63	LOCKS/LATCH/FITTINGS	GODREJ, HARRISON, YALE, DORMA
64	HYDRAULIC DOOR CLOSER / FLOOR SPRING	HARDWYN, GODREJ, GRACE, EVEREST, DORMA
65	FIRE CHECK DOOR	NAVAIR, ROMAT, KUTTY DOOR
66	ANODISED ALUMINUM HARDWARE (HEAVY DUTY)	HARDIMA, EVERITE, SIGMA (ISI MARKED), DORMA
67	TEMPERED GLASS	MODI FLAT & SAINT GOBAIN, ASHAHI
68	POLYESTER POWDER COATING SHADES	NEROLAC, BERGER, J&N
69	FRICTION STAY HINGES	EARL-BIHARI OR AS APPROVED BY ENGINEER-IN-CHARGE
70	NUTS, BOLTS AND SCREWS, STEEL	KUNDAN PRIYA ATUL OR AS APPROVED BY ENGINEER-IN-CHARGE
71	EPDM GASKET	HANU / ANAND OR AS APPROVED BY ENGINEER-IN-CHARGE
72	STRUCTURAL SILICON	DOW CORNING / WACKER OR EQUIVALENT
73	WEATHER SILICON	DOW CORNING / WACKER OR EQUIVALENT
74	COPPER TUBES / PIPES	RAJCO, MAX FLOW ABC OR EQUIVALENT
75	COPPER FITTINGS	YORKSHINE, IBP, BCONEX
76	U-PVC PIPE	FLOW GUARD, FINOLEX, ASTRAL
77	C-PVC PIPE AND FITTINGS	ASTRAL, ASHIRVAD, PRINCE HEAVY DUTY, FINOLEX
78	CEMENT BASED PAINT	M/S SNOWCEM INDIA LTD, ASIAN, BURGER, DELUXE
79	ALUMINUM SLIDING DOOR BOLT, TOWER BOLT HANDLE.	PILOT AND AODI. OR AS APPROVED BY ENGINEER-IN-CHARGE
80	VITREOUS CHINA SANITARY	PARRYWARE, NEYCER, CERA, HINDWARE

	WARE	
81	CENTRIFUGALLY SAND CAST (SPUN) IRON PIPES	NECO OR ANY OTHER AND FITTINGS B.I.S MARKED PRODUCT, BABULAL BAJAJ IRON FOUNDRY MATHURA (HIF) OR BIS APPROVED PRODUCTS
82	CENTRIFUGALLY CAST (SPUN) PIPE	ELECTRO STEEL, KESORAM (CLASS LA) OR EQUIVALENT
83	APP SHEET	SALIMAR, DR FIXIT, SIKKA OR AS APPROVED BY ENGINEER-IN-CHARGE
84	PVC DOOR SHUTTER & FRAME	SINTEX, RAJSHRI OR EQUIVALENT AS APPROVED BY ENGINEER-IN-CHARGE
85	PRE-COATED PROFILE SHEET	TATA, JSW OR EQUIVALENT
86	HDF LAMINATED BOARD	ACTION TESA, CENTURY OR AS APPROVED BY ENGINEER-IN-CHARGE
87	BITUMEN	HPL, COAL INDIA, IOCL OR AS APPROVED BY ENGINEER-IN-CHARGE
88	ACP SHEET	REYNOBOND, VIRGO ACP, ALEX PANELS, ALUDECOR OR AS APPROVED BY ENGINEER-IN-CHARGE
89	LED LIGHT FITTING & LUMINARIES FOR ROAD AND STREET LIGHTING (OUT DOOR)	WIPRO, C&S ELECTRIC, PHILIPS, CROMPTON, BAJAJ, OSRAM
90	LED LAMPS	WIPRO, PHILIPS, CROMPTON, BAJAJ, OSRAM
91	SMART STREET LIGHTS AND CONTROL SYSTEM	ORIENT ELECTRIC LTD, OPULUS
92	STREET LIGHT FITTING & ACCESSORIES -HPSC (70/ 150/ 250/ 400) HPMV (80/ 125/ 250/ 400)	POLYCAB, PHILIPS, C&S ELECTRIC, SURYA, WIPRO
93	SOLAR STREET LIGHT FITTINGS	JILCO, PHILLIPS, OSRAM
94	STREET LIGHT TIMERS	SINETRAC, INDO ASIAN, HAVELLS
95	CI PIPES & FITTINGS	JINDAL, TATA METALIKS, TATA KUBOTA
96	INTERLOCKING TILES/ PAVER BLOCKS	ISI MARKED GLOSSY FINISH
97	DECORATIVE PAINT (EXT & INT)	SNOWCEM, ASIAN, BERGER, DULUX
98	CHAIN LINK FENCING / BARBED WIRE / PUNCHED TAPE CONCERTINA COIL / RAZOR BLADE TAPE FENCING	A-1 FENCE, ARMOSTRONG WIRES, MAIMOM ROGER
99	GALVALUME SHEET	TATA BLUE SCOPE, JSW, BHUSHAN, VARDHMAN
100	CHROMIUM PLATED BATHROOM FITTINGS OF CP, CAST COPPER ALLOY FANCY TYPE BIB TAP, STOP VALVES AND PILLAR TAP, SANITARY FITTINGS, SHOWER PNAEL	JAQUAR /KOHLER/ROCA/GROHE
101	VITREOUS CHINA WC / WHB / URINAL / SOAP DISH / URINAL PARTITION WALL / LABORATORY SINK	PARRYWARE /CERA/ JAQUAR
102	NON ASBESTOSFIBRE CEMENT BOARDAS PER IS 14862	ARMSTRONG / SAINT GOBAIN (GYPROC) / EVEREST /INDIA GYPSUM/
103	ACRYLIC EMULSION / WEATHER PROOF PAINT	ASIAN PAINTS (ROYAL) / BERGER (LUXOL SILK SPLENDER)/ ICI (DULUX VELVET TOUCH)
104	PLASTIC EMULSION PAINT	ACROCEM / DUROCEM / SUPER SNOWCEM / BERGER / ASIAN PAINT (GUTUCAM)
105	HOUSE WIRING CABLE (1100 VOLTS)/CABLE FOR SERVICE	POLYCAB, RR KABEL, FINOLEX, RPG

	CONNECTION/CABLE FOR PANEL BARD WIRING	
106	PIANO SWITCHES/SOCKETS ETC.	ISI MARKED PRODUCTS OF LEGRAND/ CRABTREE/ JAQUAR/SCHNEIDER/PHILLIPS (MODULAR TYPE)
107	PVC CASING CAPPING / CONDUIT	FINOLEX / MODI / PRESTO PLAST / PLAZA / KALINGA/ RICHA
108	WIRING ACCESSORIES AND FITTINGS	ANCHOR / LEGRAND/ KINJAL (ISI MARKED)/ RICHA
109	MCBS, DBS, ISOLATOR	LEGRAND /SIEMENS/ SCHNIEDER/ ABB.
110	MCCB	ABB/ LEGRAND/ SCHNEIDER/ SIEMENS
111	LT UG /SERVICE CABLE	POLYCAB/FINOLEX/KEC
112	EXHAUST FAN/CEILING FAN	CROMPTON GREAVES/KHAITAN/BAJAJ/HAVELLS/ORIENT
113	HEATER WATER STORAGE TYPE ELECTRIC GEYSER	CROMPTON GREAVES /BAJAJ/HAVELLS
114	FALSE CEILING	ARMSTRONG/ EVEREST/GYPROC
115	EPOXY PAINT	NEROLAC OR EQUIVALENT
116	CC KERB STONE	NITCO PREFAB, K.K. MANHOLE, TERRAFIRMA, UNISTONE.
117	MILD STEEL TUBES	TATA, SAIL, ISCO, SRMB
118	APP MEMBRANE	ASIAN PAINTS/FOSROC/SIKA/STP
119	GLOW STUD	TATA BP/3M India or Equivalent

➤ Raw material source to be approved by the Engineer-in-Charge.

Remarks:- Any change in the brands mentioned above and elsewhere shall be allowed only after approval of the Engineer-in-charge.

PARTICULAR SPECIFICATIONS

GENERAL

Work under this contract shall be carried out in accordance with Specifications, drawings, General Specifications and other provisions contained in CPWD Manuals and Specifications General Rules, specifications, special conditions and all preambles in the CPWD Schedule shall be deemed to be applicable to the work under this contract, unless specifically stated otherwise in these documents and in case of any conflicting provisions in CPWD schedule and in these tender documents, the provisions in these documents shall take precedence over the aforesaid provisions in the CPWD Schedule. The term "as specified" wherever appears in the tender documents and drawings, relates to relevant particular specifications and in its absence, general specifications. Where specifications for any item of work are not given in CPWD Schedule or in these particular specifications, specifications as given in relevant Indian Standard Code of Practice shall be followed. Unit rate quoted by the tenderer shall be deemed to include for any minor details/items of work and/or constructions which are obviously and fairly intended and which may not have been included in these documents but which are essential for the execution and entire completion of work. Decision of the Accepting Officer as to whether any minor detail of work and/or construction is obviously and fairly intended to be included in the contract or not, shall be final, conclusive and binding.

LOCAL MATERIALS:

Irrespective of actual distance involved, local materials such as stones, aggregates, sand, road metals etc shall conform to or superior to the specifications given here in after and to the samples kept in the office of Executing Officer. The tenderers are advised to inspect these samples. The tenderers shall be deemed to have inspected the samples and have full knowledge thereof whether they inspect them or not before quoting their tender.

SAMPLES OF MATERIALS: -

(a) Specific requirements regarding dimensions, strength, weight and finishes, as per IS, CPWD Specification and the particular specifications given hereinafter vis-à-vis actual properties check, tests carried out, reference to test certificates and markings, etc based on which samples of each materials are approved as Conforming to relevant specification shall be recorded in the sample approval register.

(b) The contractor shall produce samples of all materials and shall obtain approval in writing from Engineer-in-charge before he places bulk order for the materials for incorporation in the work. The contractor shall not procure materials unless the samples are first got approved from the Engineer-in-charge.

- (c) Samples of approved materials shall be kept in custody of Engineer-in-Charge till completion of work.

RECORD OF MATERIALS

- (a) The quantity of all the proprietary materials (including materials and quantity of which cannot be checked after incorporation in the works) shall be recorded in measurement books and signed by the Contractor, the Engineer-in-Charge and Insp/SI (Civil) as a check to ensure that the required quantity has been brought at site for incorporation in the work.
- (b) Materials brought to site shall be stored as directed by the Engineer-in-Charge and shall be suitably marked for identification.
- (c) The contractor shall procure all the materials (where specific makes/manufacturer's specified) directly from their manufacturers or from their authorised dealers only. The contractor shall ensure that the materials are brought to site in original sealed containers/packing bearing manufacturers marking except in the case of the requirement of material(s) being less than smallest packing.
- (d) The contractor shall produce to Engr-in-charge original printed and machine numbered purchase vouchers/invoices including manufacturer's test certificate (where applicable) for all the materials mentioned. Copies of orders placed on the manufacturer/authorised dealers shall also be provided by the contractor to Engr-in-Charge along with above documents. Whenever procured and brought to site of work for incorporation in the work, a Xerox copy of such vouchers/invoices shall be stamped (office stamp) and defaced in ink by the Engineer-in-Charge & Insp/SI (Civil) stating verified for materials purchased and brought to the site of work for incorporation in the subject work and signed with date before allowing payment for these materials through RA Bills.

STANDARD OF WORKMANSHIP

To determine the acceptable standard of workmanship and fittings, wiring etc, the Engr-in-charge shall order the contractor to execute certain typical portion of work (different trades) and services sufficiently in advance of other work. These shall be executed and completed under the close supervision of the Engineer-in-charge and Insp/SI(Civil).

On approval by the Engineer-in-charge of such items, these items shall signed and/or suitably identified by the Engineer-in-charge and labeled as guiding samples. The record of such inspection and passing of each stage of these samples shall be recorded by Engineer-in-charge under his dated signatures. Work on such sample shall be progressed well ahead (minimum two stages ahead). Approved finishes/workmanship shall be followed in the work as a whole.

TESTING OF CEMENT

The Engr-in-charge shall also organize independent testing of random samples of cement (both physical and chemical properties) drawn from various lots for each consignment to cement brought out by the contractor before incorporation in the work from the National Test House, SEMT, Regional Research Laboratories, Government approved laboratories, as per IS: 3535 (Method of sampling Hydraulic cement), IS: 4031 (Method of physical test for Hydraulic Cement) and IS: 4032 (Method of chemical analysis of Hydraulic cement.)The cement shall conform to chemical requirements and physical requirements as specified in respective IS. The tests carried out as per provisions of IS codes specified herein before shall be the criteria for acceptance of cement by Engr-in-Charge & Insp/SI(Civil). If samples from a lot/lots are not within the acceptance limits of Indian standard the lot/lots shall be rejected without any claims or compensation to the contractor for the lot/lots purchased. The contractor shall replace the lot/lots with the fresh one, which shall be tested again for acceptance. The cost of all tests carried out on cement before acceptance for incorporation in the work shall be borne by the contractor whether the results are acceptable or not.

STORAGE

Cement shall be stored over dry platform at least 20cm high in such a manner as to prevent deterioration due to moisture or intrusion of foreign matter. In case of store rooms, the stock should be at least 20cm above from floors and 60 cm away from walls in addition to precautions specified in Works Manuals. Inspections shall be carried out once a day by the Engineer-in-Charge & Insp/SI(Civil). It shall be ensured by the Engineer-in-Charge that tested and untested cement are segregated and stored separately with distinct identification. The cement godown shall be provided with two locks on each door. The key of one lock at each door shall remain with the Engineer-in-Charge or his representative and that of the other lock with the contractor's authorized representative at site of works so that cement is removed from the godown only according to daily requirement with the knowledge of both the parties.

DOCUMENTATION

The contractor shall submit original vouchers from the supplier for the total quantity of cement supplied under each consignment to be incorporated in the work. All consignments received at the work site shall be inspected by Engr-in-charge & Insp/SI(Civil) along with the relevant documents before acceptance. The original vouchers and the Test Certificates shall be defaced by the Engineer-in Charge & Insp/SI(Civil) and kept on record duly authenticated and with cross-reference to the control number in the cement Supply & Acceptance Register. The cement supply & Acceptance Register will be signed by Insp/SI(Civil), Engineer-in-Charge and the Contractor. The Accepting Officer may order a Board of Officers for random check of cement and verification of connected documents. The entire quantity of all types cement shall also be suitably recorded in the Measurement Book for record purpose not to be abstracted before incorporation in the work and shall be signed by the Engineer-in-Charge, Insp/SI(Civil) and the contractor.

SCHEDULING OF SUPPLY

Schedule of procurement of cement shall be finalized by the contractor with Engr-in-charge and shall be incorporated in the CPM chart so that procurement is in accordance with the progress contemplated in the CPM prepared. The complete requirement of cement shall be worked out before making any RA Bill payment and procurement of cement by the contractor shall be completed sufficiently in advance of the execution of work.

SAND(Coarse & Fine)

Sand for all concrete work shall be M-sand and /or Badarpur river sand (from near area or any other Sand) conforming to samples, complying with the requirement as specified in CPWD. Sand in the zone II grading may also be permitted provided mix design is done and the requisite strength of the concrete is achieved.

Note: Wherever M-sand has been specified in the tender documents, the Contractor shall be permitted to use Badarpur sand (from near area) at his own cost, if he so desire due to inadequate supply/non availability of M-Sand. No price adjustment shall be made on this account. Sample of sand shall however, be got approved from the Engr-in-charge & Insp/SI(Civil) before incorporation in the work. Other provisions in the respective clauses shall remain unchanged.

CONCRETE MIX

All mixes of concrete and mortar mentioned in this tender document shall be by volume except design mix concrete conforming to IS-456 for which all the ingredients are proportioned and mixed by weight.

WATER BOUND MACADAM (WBM)

WBM shall consist of consolidated thickness as per schedule of broken/crushed stone (granite, trap or basalt stone aggregate). Stone shall be hard and durable and shall be free from excess of flat and elongated, soft and disintegrated particles, dirt and other objectionable matter. Stone aggregate shall be grading 2 (63 to 45 mm size) as given under CPWD Specifications & Manuals. Screening shall be of red Bajri/Mooram. Unless otherwise specified, the laying, compacting and rolling etc shall be as specified in CPWD Works Manual & Specifications. Stone for WBM shall be laid out as specified in CPWD.

STEEL AND IRON WORK

General:- All items of steel which are required for the work under this contract shall be procured supplied and incorporated in the work by the contractor under his own arrangement.

Grades and Quality

Steel supplied by the contractor shall conform to the following grades and quality.
Structural steel

- (i) Structural steel wherever mentioned shall be conforming to Fe 550 Gde conforming to IS-2062.
- (ii) General purpose steel wherever mentioned shall be conforming E-165(Fe-290) conforming to IS-2062.

Source of Procurement

- (a) Structural Steel : The Contractor shall procure all the structural steel from the main manufacturers.
- (b) The contractor shall within 15 days of placing of work order indicate the source for procurement of steel to Engineer-in-charge in writing.

(c) However, steel sections for railing, gates, fencing, guard bars, grills steel chowkats, hold fast etc, which do not constitute structural members, can be procured from main producers/secondary producer/BIS marked manufacturers or their authorized dealers at the option of contractor

(d) The contractor shall produce original vouchers from suppliers for the total quantity of steel purchased, under each consignment and be kept on record by Engineer-in-Charge and authenticated.

Testing and Test Certificate

(a) The contractor shall produce manufacturers test certificate in original along with the test sheet giving the result of each mechanical test as applicable and the chemical composition of the steel supplied as specified in relevant IS Codes, duly signed by the manufacturer of their authorized dealers with each consignment.

(b) The original test certificate shall be kept on record in the office of Engineer-in-Charge (AC Engr).

(c) Independent testing of structural steel by the Engineer-in-Charge shall be mandatory in case of procurement from secondary producers and testing charges shall be borne by the Contractor irrespective of the outcome of test results.

(d) In both the cases at sub para (c) and (d) above, the contractor at his cost shall provide all facilities required for the testing and cost consumed in tests shall be borne by the contractor.

Minimum frequency of testing for each source and each consignment

(a) Structural Steel: -

(i) Tensile test : One sample (3 specimen) for each test for every 25 tonnes or part thereof.

(ii) Bend test : One sample (3 specimen) for each test for every 10 tonnes or part thereof.

(b) Steel for concrete reinforcement: -

(i) Bar size less than 10mm : One sample (3 specimen) for each test for every 25 tonnes or part thereof.

(ii) Bar size 10mm to 16mm (inclusive): One sample (3 specimen) for each test for every 35 tonnes or part thereof

(iii) Bar size over 16mm: One sample (3 specimen) for each test for every 45 tonnes or part thereof.

(c) Bend test and tensile test for structural steel shall be carried as per IS-226 of 1975. For high strength deformed bar tensile, bend test and rebend test shall be done as per IS-1786 of 1985. For MS bars tensile and bend test shall be carried out as per IS 432 of 1982.

(d) Engineer-in-Charge has the right to get one more sample (3 specimen) tested if he is not satisfied with test result of the consignment.

(e) If the test results as per manufacturer's test certificate or of independent testing of random samples are not as per criteria laid down in the relevant BIS provisions, the entire consignment which is represented by the samples shall be rejected. Such rejected materials shall be removed and replaced by the contractor at his own cost forthwith.

(f) Cost of transportation of samples to the approved laboratory/test house and all testing charges shall be borne by the contractor.

Storage: - Steel supplied by the contractor shall be stored in accordance with the requirement of IS. Each grade and quality of steel shall be stored separately and have identification tags indicating the source, quality and grade.

Preservation and maintenance of steel :- The steel brought by the contractor shall be preserved to ensure that no rusting takes place till it is incorporated in the works.

Schedule of Supply :- The contractor shall procure the steel sections, timely as required in accordance with CPM Chart, agreed between Engr-in-charge and contractor. The contractor will forego his right to demand extension of time if the supply of steel got delayed due to his failure in placing order in time to the manufacturer/supplier.

Payment :- Payment shall allowed after production of test certificate and original paid/purchase vouchers by the contractor.

Measurement

(a) The entire quantity of steel brought to site shall be recorded in measurement book as “NOT TO BE ABSTRACTED” indicating the reference to manufacturers, source of supply voucher number and test certificate before incorporation in the work and shall be signed both by the Engineer-in-Charge and the contractor. Proper documentation/record shall be maintained as per the instructions on the subject.

Normal waste and off cuts shall be stacked neatly which shall be the property of the Contractor. Contractor shall be allowed to remove such cut pieces after inspection and certifications by the Engineer-in-Charge.

Advance on account of payment made towards these cut pieces shall be recovered from advance on account of payment immediately falling due and before removal of such cut pieces from site.

Bending and fixing of bars for concrete reinforcement including mild steel wire for binding shall be carried out all as specified in CPWD. Binding wire for reinforcement shall be mild steel wire(annealed) of size not less than 0.9mm.

Steel supply/Acceptance form :- For each consignment of steel supply/acceptance form will be filled in and jointly signed by the department Rep.(Engineer-in-Charge/SI civil/Insp Civil) and contractor and accepted/rejected by Engineer-in-Charge before incorporation in the works.

Steel Reinforcement :- Reinforcement shall be fabricated, placed in position all as specified in CPWD specifications.

Guard Bars/Grills:

MS Guard bars/grills wherever applicable and as indicated shall be provided to wooden/steel windows/ventilators as per details shown on drawings/schedule. Steel Guard bars/ steel grills shall be painted with 2 coats of synthetic enamel paint over a coat of primer as specified here-in-after.

Hold Fast/Lugs: Flat iron hold fast/lugs shall be provided by welding as and where shown on drawings except those, to be provided to wooden chowkats, which shall be fixed with screws as per details shown on drawings. Hold fasts/lugs shall be embedded in PCC(1:3:6) bed blocks of size 220mmx220mmx75mm in one brick thick walls and 100mmx220mmx75mm in half brick thick walls..

FLOORING

General adopted for laying floors and pavements.

Floors shall be laid to levels and as directed by the Engineer-in-Charge.

Floor topping of cast-in-situ cement concrete shall be finished even and smooth using extra cement as specified in CPWD specifications.

Pozzolana or pozzolana slag cement shall not be used for floor topping.

Floor finish over RCC slabs shall be laid all as specified.

Sub floor may not be laid in panels. The thickness of sub base concrete shall be as indicated in schedule.

CEMENT CONCRETE FLOORS :- PCC floors shall be provided as indicated in Schedule.

All tiling works in floors, proper slope shall be ensured to avoid accumulation of water/liquids or formation of puddle. Slope shall be checked by spirit level/pouring water on the floor & then only the work shall be passed. In case work fails in the slope test, firm shall re-do the tiling work at that particular location as its own cost.

VITRIFIED TILES FLOORING

Where vitrified tiles specified on Schedules provide coloured vitrified tiles of size as specified in the schedule and shall be laid and jointed pointed with white cement paste & pigment. Tiles shall confirm to IS – 15622-2006.

The tiles shall be first quality product procured from any of the manufacturers as listed in list of manufacturers

Laying jointing and finishing shall be all as per manufactures guidance/ instructions.

The colour of tiles shall be as decided by Estate Officer and Engineer-in-Charge.

KOTA STONE SLAB FLOORING

Kota stone shall be hard, durable, regular in shape, of uniform colour and free from cracks, decay and weathering. It shall be set, jointed and pointed in neat cement slurry mixed with pigment to match with the colour of stone. The slabs used in one location shall be of uniform size and shall be laid over cement screed as indicated. Kota stone slabs shall be machine cut and true fine cut dressing on all sides up to full depth . All angles and edges shall be true, square, free from chipping and surface shall be true and plain. The joints of the tiles shall not be more than 1mm.Laying, polishing and finishing of kota stone shall be all as specified.

GLAZED CERAMIC TILE DADO

The ceramic dado shall be provided with ceramic tiles of size as specified in BOQ and shall be glazed quality colour and/or white as indicated in BOQ and conforming to relevant IS specifications.

The tiles shall be jointed and pointed with white or coloured cement to match with the colour of tiles. The tiles shall be laid over cement mortar screed as specified in BOQ.

GRANITE FLOORING /CILL

It shall be all as described on Schedule. Granite slab shall be machine cut, pre-polished, over cement screed 15mm thick in CM 1:6 over 25mm thick PCC 1:2:4 using 12.5mm aggregate over RCC slab or as per BOQ.

WHITE MARBLE TILE: 20mm thick makrana white marble tile shall be laid over cement screed CM 1:4,15mm thick jointed with grey cement slurry mixed with pigment to match the shades of slab used as the boarder to kota slab flooring.

CERAMIC FLOOR/WALL TILES

Where Non-skid ceramic tiles specified on Schedules provide coloured non-skid ceramic tiles of size as specified in the schedule, as per Gde B II (a) shall be laid and jointed pointed with white cement paste & pigment. Tiles shall confirm to IS – 15622-2006.

The tiles shall be first quality product procured from any of the manufacturers as listed in list of manufacturers here-in-below.

Laying jointing and finishing shall be all as per manufactures guidance/ instructions.

The colour of ceramic tiles shall be as decided by Estate Officer and Engineer-in-Charge.

PLASTERING AND POINTING

GENERAL

Cement: Refer to specifications and list as mentioned above.

Fine aggregate for plastering and pointing work shall be river sand conform to IS 1542-1992 and as specified in Clause 14.5 to 14.5.2 of SSR Part I. Sand shall be obtained from sources as approved by Engineer-in-Charge.

Particular attention of the contractor is invited to take note of local practices and the local availability of materials like bricks form work etc and cater for any extra quantities of mortar required for rendering smooth for extra dubbing required for touching up properly and for smooth and even surfaces.

This shall be deemed to have been included in the lump sum.

Plaster and skirting/dado shall be returned in jambs, soffits of lintels and windows sills etc.

All plastered surface shall be trowel led to a smooth and even surfaces, without using extra cement.

Thickness of cement plaster mentioned hereinafter shall be finished thickness exclusive of dubbing. Dubbing may however be done in one operation with plaster.

Plaster on external surface shall be carried out upto 15cm below ground level or as per BOQ except where plinth protection/ramp etc are provided.

All corners, angles, junctions and riser shall be truly vertical or horizontal as the case may be and shall be carefully finished. Corners around jabs of openings and junction of walls shall be finished straight and square. 12mm wide groove at the junction of wall and RCC slabs to the entire thickness of wall plaster shall be provided. Also trowel groove shall be provided at junction of walls and RCC columns or any other dissimilar material e.g. wooden chowkhats etc.

Any spalling of concrete/plaster on the surface to be painted/distempered shall be repaired first as per instructions of Engineer-in-Charge followed by premier cost of patch work and then only paint/distemper shall be applied.

Plastering shall be carried out all as specified in Schedule 'A' .

OIL EMULSION DISTEMPER

Distemper shall be applied as specified in BoQ. Preparation of surfaces and applications of distempering shall be all as per BOQ/CPWD specifications.

Preparation of surfaces and application of interior emulsion shall be done all as per manufacturer's instructions/ as specified in BOQ. The contractor shall give 05 years Guarantee for interior emulsion on stamp paper of value for Rs.100/-

CEMENT BASED PAINT

Cement based paint shall comply with IS 5410-1992, specification for cement paint colour as required. The material shall be in powder form, free from lumps that are not friable and when mixed with required volume of water shall be suitable for use on porous surfaces of masonry, concrete, bricks and rough plaster work. Cement base painting shall be provided where indicated in BOQ and all as specified.

WHITE/COLOUR WASHING

Lime shall be fresh burnt lime (Class 'C'), white in colour conforming to IS-712, 1984. The samples of lime, blue, sodium chloride and gum shall be approved the Engineer-in-Charge before incorporation in work.

Workmanship shall be generally conforming to specification as described in Schedule.

SYNTHETIC ENAMEL PAINTING

The synthetic enamel paint shall be from any of the make/ brand listed in list of manufacturers.

Preparation of surfaces and application of synthetic enamel paint shall be done through the authorized applicator of approved manufacturer all as per manufacturer's instructions/ as specified in BOQ.

The colour scheme for building shall be got approved from Estate officer in consultation of Engineer-in-Charge and the contractor shall progress the application of paint only on receipt of approval from Engineer-in-Charge.

GENERAL NOTES FOR APPLYING PUTTY, DISTEMPER, ANTIFUNGAL AND ENAMEL PAINTING

These works shall be executed using modern technics and tools to maintain the required quality work. Following smart painting tools shall be used in site.

- (a) Hand held sander / long handle sander shall be used for plaster / putty work.
- (b) Multipurpose mixer shall be used for mixing putty to get a uniform mix.
- (c) Auto roller and Airless spray shall be used for painting.
- (d) Jet washer to be used for cleaning dirt and fungus etc from external walls.

WORKMANSHIP

All wood work required to be painted shall be smoothened sized and knotted and then applied with priming coat. Stopping and filling (filler coat) shall be done after priming coat and surface rubbed down to a level and smooth surface and thereafter under coat and finishing coat applied. Where painting to wood work is specified prepare surface and apply one priming coat of pink primer, one under coat and one finishing coat of synthetic enamel paint all as specified in Schedule/BOQ.

GALVANIZED SHEET

Galvanized steel sheet, plain or corrugated shall comply with the requirement of IS 277- 2003, Specification for galvanized steel sheets, plain or corrugated. The thickness sheet shall be 0.63mm and Grade of coating shall be 275 or as per BOQ

Plain sheets shall be reasonably flat and free from twist. Corrugated sheet shall be free from twist or buckle and shall have uniform corrugation, true in depth and pitch, and parallel to the sides of the sheets. The tolerance on weight of an individual sheet shall be $\pm 10\%$ and tolerance on bundle of sheets shall be $\pm 5\%$.

GALVALUME SHEETING:-

Galvalume sheet shall be colour coated corrugated / plain sheeting as per requirement and as directed. The feed material is manufactured out of steel with minimum 550 MPa yield strength coated with hot-dip metallic zinc aluminum alloy coating zinc alume AZ-150 or equivalent (as per AS 1397). AS150 Gms/sqm total on both sides of Zn (43.5%), Al (55%) & Si (1.5%) with Regular silicon modified(SMP) polyester paint or equivalent as per AS/NZS-2728-(category 3-4) of approved colour. The colour shall have a total coating thickness of 35 microns of approved paint system or equivalent comprising of 20 microns (nom) exterior coat on top surface and 5 microns(nom) reverse coat of back surface over 5micron (nom) primer coat on both surfaces of approved colour shade.

The sheet shall have brand marking of the manufacturer on the back of the sheet at spacing not exc 1.5 m c/c confirming to genuinity of the material. The sheet shall be fastened with good quality fastener of suitable size as directed by Engineer –in-Charge/SI/Insp/Civil, galvanized water head, self-drilling, tapping screw as per AS 3566 class 4 (min) of approved make (Buildex, Corroshield or equivalent) and quality including EPDM/neoprene washer on each crest of sheets for connecting with purloins or as per design. All accessories shall be made from the same material which is used for main roofing/ wall cladding application .

INTERLOCKING PAVER BLOCK

Precast interlocking paver blocks shall be M 40/M-35 grade for 60/80mm thick and shall be laid over 30mm thick cushioning using 6mm and below aggregate or as per BOQ. The paver blocks shall be ISI marked

having Glossy Finish. Paver blocks shall be sound and free from cracks or other defects. The tolerance in thickness shall be +3mm. Water absorption shall not be more than 6% by mass. Size, shape, pattern and colour shall be as approved Estate Officer in consultation with Engineer-in-Charge.

PRECAST PCC SOLID BLOCKS FOR MASONRY

SOLID PCC BLOCKS : PCC solid block masonry shall conform to the specifications as per IS2185 -2005.

The blocks shall have a minimum average Compressive strength of 5 N/ Sq mm (Minimum strength of individual unit 4 N/ Sq mm) conforming to C-5 grade IS 2185 -2005 when tested for 28 days cube test. The manufacture of Block, surface texture and finish, physical requirements of blocks, testing of PCC blocks, sampling etc shall be all as per IS 2185-2005 and proper record shall be maintained. The cost of blocks including transportation of block from work site to an approved laboratory for testing and cost of testing shall be borne by the contractor.

Notes:-

(i) Trial mix shall be carried out before casting the blocks to ensure that the required strength and block density is obtained as per IS.

(ii) Proper care shall be taken to protect the corners of PCC blocks. To achieve better consistency, contractor may use suitable plasticizers as approved by the Engineer-in-Charge without any price adjustment.

Masonry work shall be kept constantly moist for a minimum of 7 days. All concrete shall be mixed in mechanical mixer. The blocks shall be manufactured with vibratory moulding machines.. However, contractor may use machine moulds of other standard manufacturers if approved by Engineer-in-Charge. Appropriate consistency of concrete shall be used to enable de-moulding of the blocks immediately after casting. The blocks shall have sufficiently rough surface to afford a good key to the plaster and joints. The hardened blocks shall be cured in a water tank in curing yard and shall be kept continuously moist for 14 days. The curing water tank/yard must therefore be of adequate capacity/size. Curing shall be done as per IS -2185.

After curing, the blocks shall be dried for a period of 4 weeks before being used in the work. The blocks shall be allowed to complete their initial shrinkage before they are laid in wall.

Chain Link Fencing:-Mild steel galvanized chain link fencing with mesh of size 50mm x50mm nominal dia of wire 3.10mm fixed to fencing posts sing suitable bolts and nuts.

HARD CORE

The materials for hard core shall be of broken granite stone to a gauge not exceeding 63mm and shall be free from dust and impurities.

Hard core shall be of stones/ boulders (Broken to gauge) not exceeding 63mm. Hard core shall be deposited spread and leveled in layers not exceeding 15cm thick and well watered, rammed to a true surface and compacted. The thickness of the hard core specified or as indicated in the drawings is the thickness after consolidation, where thickness had not indicated, it shall be 100 mm (consolidated thickness).

FORM WORK- As per CPWD Specifications.

GENERAL

(a) The work under these specifications consists of furnishing all labour , equipments and materials required for form work including all supporting structure for all works of cast in situ concrete as required by drawing and specification of contract.

(b) The contractor shall submit Form and Centering layout to SI/Insp Civil for checking and final approval by Engineer-in-charge and Estate officer. The complete final approval of the plan will be obtained by the contractor before such work is started on ground. The procedure of erection and removal of forms will be decided at this stage itself. These approvals shall not relive the contractor of any responsibility for correct and complete performance of all works included in the contract. The design and engineering of the formwork as well as its construction shall be the responsibility of the contractor.

ELECTRIFICATION

General-The scope of work consists of providing internal electric wiring to the buildings and connected other works as described in BOQ and as specified/Shown on drawings.

The general layout of wiring points and fittings are as directed by the Engineer in charge.

All electrical fittings and wiring must run clear of door, windows and openings No diagonal run shall be allowed. These must always be parallel or perpendicular to the ground.

The specification and general rules/conditions laid down in the CPWD Schedule(E&M) and CPWD Specifications will be generally applicable to the whole work unless otherwise specified hereinafter.

The work shall be carried out in strict compliance with the latest edition of Indian Electricity Act the Indian Electricity Rules and IEE Regulations and the latest edition of IS732. It shall be of high standard and approved construction used in a modern electrical work both as regards design and workmanship. Complete work shall be suitable in every respect of type of voltage specified and shall be to the satisfaction of Engineer-in-Charge.

WORKMANSHIP

The execution of electrical & mechanical works shall be mandatorily carried out only by licensed person under the supervision of contractor or representative of contractor. License of concerned person shall be produced for inspection, if asked by the Engineer-in-Charge.

Passing of cables through walls floors etc shall be protected.

SAMPLES

Before starting the work, the contractor shall produce samples of all materials including accessories and got approved by the Engineer-in-Charge. Samples that are approved will be retained by Engineer-in-Charge until the work is completed and accepted. The contractor will not be allowed to commence the work before the samples are produced and approved. The contractor shall ensure that the materials used in the work are identical with approved samples and are uniform through out. All materials shall be accordance with latest edition of the IS/BS specification and shall be of the best indigenous make approved by the Engineer-in-charge.

MATERIALS : All materials shall be accordance with latest edition of the relevant IS/BS specification and shall be of indigenous make approved by Engineer-in-Charge.

CABLES: Cables shall be single core PVC insulated and PVC sheathed/unsheathed (all as described in BOQ). All cables shall be 1100 volts grade for point wiring and shall be of such size as to be capable to carrying the maximum current which will normally flow through them without the respective rating being exceeded as laid down in IEE Regulations.

Cables shall be delivered a site in makers wrappers etc, with the seal intact and shall not be installed unless approved by Engineer-in-charge. If cables of size as specified in BOQ as per relevant IS are not available, cables of equivalent size with identical current carrying capacity and with multi-stands shall be got approved from accepting office before incorporation works without extra cost to Govt.

MS PRESSED STEEL TERMINAL BOXES

Mild steel pressed terminal boxes shall be made out of 2 thick MS sheet of suitable size. The boxes shall be embedded in the walls with cement mortar (1:2) clear depth of the box shall be not less than 60mm and this shall be increased suitability to accommodate mounting of fan regulators. The box shall be painted with one coat of red oxide primer.

LAMINATED SHEET

Laminated sheet shall be 3mm thick fixed in MS pressed steel terminal boxes by cadmium plated iron screws

CIRCUITS

Separate circuits shall be provided for lighting and power wiring.
Lighting sub circuits shall not be loaded with more than 8 light points.

CONDUIT AND CONDUIT ACCESSORIES: All conduits, conduit fittings and accessories shall be rigid PVC conduit and fittings conforming to IS-9537 Part III of 1983 of (Medium grade).

CEILING ROSES: Ceiling roses shall be ISI marked.

SOCKET OUTLETS: These shall be ISI marked.

MINIATURE CIRCUIT BREAKERS AND DISTRIBUTION BOARDS

MCB shall be of approved make and shall be obtained from any one of the manufacturers listed above.

The unused portion of DBs are to be blocked by the blank piece.

FAN REGULATOR: Fixing of fan regulator and hanging ceiling. All ceiling fans and regulators shall be earthed effectively by means of 2mm bare GI iron conductors. Cost of this earthing to fans and regulators shall be deemed to be included in the rate for point wiring for fans.

EARTHING : Earthing shall be carried out as specified in BOQ. Earthing shall be with earth plate electrode as mentioned in BOQ buried directly in ground (earth pit) not less than 2.25m deep below ground level connected to galvanized earth top edge of the plate not less than 1.5m below ground level connected to earth strip as mentioned in BOQ by means of bolt nut and washers of galvanized iron or steel, and protected by GI pipe light grade of suitable size. Excavation and earth work shall be in soft/loose soil. All surplus soil to be removed to a distance not exceeding 50m. Cement concrete for PCC chamber , cover slab, reinforcement etc shall be as per BOQ. The unit rate of relevant item of BOQ including the cost of earth work, PCC Chamber, RCC cover, testing etc complete.

LED LIGHT FITTING: These shall be all as specified in BOQ and shall be obtained from any of the manufacturer listed here in after and shall be fixed to walls/roofs etc with proper size of clamps/screws and connecting cables etc complete.

PAINTING: Unless otherwise specified all exposed surface of steel works like terminal boxes LT panel board MS clamps etc shall be painted with 2 coats of synthetic enamel paint over a coat of red-oxide primer. Metallic suspenders of tube light fittings shall be black painted.

SYSTEM OF WIRING: Wiring shall be carried out with PVC insulated cable and shall run as far as possible on walls, ceilings so as to be easily accessible and capable of being inspected. Power wiring shall be kept apart at minimum distance of 2 run unless they are enclosed in earthed metal conduit suitably marked to indicate the risk of dangerous shock due to voltage in the conductor.

CONCEALED WIRING: Provide concealed wiring all as described in BOQ. PVC conduit shall be rigid PVC conforming to relevant IS. The make of PVC conduit as mentioned above. PVC conduit shall be adequate size to draw required for cables.

TESTING

On completion of the work, the entire electrical installation including energy meter shall be tested by the contractor for the necessary following tests in the presence of and to the satisfaction of Engineer-in-Charge :-

- (a) Continuity
- (b) Insulation resistance

(c) Any other test prescribed by the Engineer-in-Charge

All testing equipment/apparatus, material, labour etc required for above tests shall be provided by the contractor at his own expenses through his sources, works for which test results do not conform to standard will be redone by the contractor at his own expenses.

RECORD DRAWINGS: On completion of work, wiring diagram showing the internal electrification (including high frequency supply) and layout of the buildings shall be prepared by the contractor at his own expenses through his sources and submitted to Engineer-in-Charge in triplicate.

SUB MAIN WIRING

CABLES:- Cables shall be single core PVC insulated and PVC sheathed/unsheathed(all as described in BOQ' with multistranded copper conductor conforming to specifications. All cables shall be 1100 volts grade for point wiring and shall be of such size as to be capable to carrying the maximum current which will normally flow through them without the respective rating being exceeded as laid down in IEE Regulations. Cables shall be delivered at site in makers wrappers etc, with the seal intact and shall not be installed unless approved by the Engineer-in-charge.

CONDUIT WIRING: Provide PVC conduit wiring all as described in BOQ. PVC conduit shall be rigid medium grade PVC conforming to relevant IS. The make of PVC conduit shall be as specified in here-in-after . PVC conduit shall be of adequate size to draw required No of cables.

System of wiring: Wiring shall be carried out with PVC insulated cable and shall run as far as possible on walls, ceiling so as to be easily accessible and capable of being inspected. Power wiring shall be kept apart at minimum distance of 2mm unless they are enclosed in earthed metal conduit suitably marked to indicate the risk of dangerous shock due to voltage in conductor.

DISMANTLING/ DEMOLITION/ TAKING DOWN: The work of dismantling/ demolition/ taking down shall be done carefully and in a workman like manner. Any damage done by contractor or his workmen to existing sanitary fittings/ water supply fittings/ electrical fittings etc in the building while working shall be made good by him at his own expense. All the materials retrieved from demolition/ dismantling/ taking down shall become the Government property except those listed in Credit Schedule. The rates inserted by the CPWD or quoted by the contractor (whichever is more) shall be deemed to include removal or disposal of all waste materials from site of work and site shall be left clean and tidy to the entire satisfaction of Engineer-in-Charge.

SITE CLEARANCE

The contractor shall from time to time, clear away all debris and excess materials accumulated at the site. After the fixtures, etc have been fixed, contractor shall clean-up the same and remove all paints, stains and other foreign matter or discoloration leaving the same in a ready to use condition. On completion of all works, contractor shall demolish all stores, remove all surplus materials and leave the site in a broom clean condition.

SETUP OF FIELD SAMPLE TEST LABORATORY:- Contractor will setup a laboratory at site for testing of sample i.e. cube testing, Sand test, gravel testing, cement testing, sieve analysis, CBR test, Compressive strength machine, Los angles abrasion, Slump test, Silt test of sand etc.

ACCEPTABLE MAKES OF VARIOUS EQUIPMENTS/MATERIALS:-

The acceptable makes of various equipment/components/accessories/materials have been indicated in "Acceptable Makes" appended with the tender documents. The tenderer shall work out the cost of the offer on this basis. Alternate makes are not acceptable.

DIG (Engr) , Works Dte
For and on behalf of the President of India

APPENDIX-A

SL.NO	DESCRIPTION	QTY	UNIT
1	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.	2257.11	SqM
2	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.:		
	With cement mortar 1:4 (1cement: 4 coarse sand)	631.99	SqM
3	Providing and applying white cement based putty of average thickness 1mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	3611.37	SqM
4	Finishing with Deluxe Multi surface paint system for interiors and exteriors using Primer as per manufacturers specifications :		
	Two or more coats applied on walls @ 1.25 ltr/10 sqm over and including one coat of Special primer applied @ 0.75 ltr /10 sqm	5291.40	SqM
5	Finishing walls with Acrylic Smooth exterior paint of required shade :		
	Old work (Two or more coat applied @ 1.67 ltr/ 10 sqm) on existing cement paint surface	3737.02	SqM
6	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade :		
	One or more coats on old work.	1633.68	SqM
7	Renewing glass panes, with putty and nails wherever necessary including racking out the old putty:		
	Float glass panes of nominal thickness 5 mm (weight not less than 12.5kg/sqm)	94.20	SqM
8	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.		
	For thickness of tiles above 25 mm and up to 40 mm	28.00	SqM
9	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	66.00	SqM
10	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20 mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete.		
	Size of Tile 600x600 mm	72.80	SqM
11	Providing and laying gang saw cut 30 mm thick, mirror polished pre moulded and pre polished machine cut granite stone of required size and shape of approved shade, colour and texture in footpath, flooring in road side plazas and similar locations, laid over 20mm thick base of cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement mixed with matching pigment, epoxy touch ups etc. complete as per direction of Engineer-in-Charge.		

	With granite stone of all colour except black, cherry/ruby red of area less than 0.50 sqm.	9.00	SqM
12	Providing & fixing false ceiling at all heights with GRG (Glass Fibre Reinforced Gypsum-12 mm thick) false ceiling of approved texture, design and patterns to be laid in true horizontal level suspended or in design/shape as desired including all materials required for fittings. The work shall be carried out as per specifications, drawing including putty & primer making the surface even and making the space for fixation of light and wiring all complete as per directions of the Engineer-in-Charge.	297.56	SQM
13	Providing and fixing in position WPC wall panelling/louvers(25-30mm thick) at all heights of approved design as per direction of Engineerin- Charge all complete.	377.92	SqM
14	Providing and fixing floor mounted-European type, white vitreous china single piece,double traps syphonic water closet of approved brand/make, shape,size and pattern including integrated white vitreous china cistern ofcapacity 10 litres with dual flushing system, including all fittings and fixtures with seat cover, cistern fittings, nuts, bolts and gasket etc including making connection with the existing P/S trap, complete in all respect as per directions of Engineer-in-Charge.	3.00	Each
15	Providing and fixing wodden table cabinet(size-1.5m x .6m x .75m) having italian glossy finished granite (colour as desired by engineer-in-charge) top with White Vitreous Wash basin size 550x400 mm with CP brass basin mixer of premium quality having weight not less than 700gm of approved make, including all plumbing fittings , cutting and making good the walls wherever required complete in all respect as per directions of Engineer-in-Charge.	3.00	Each
16	Providing and fixing SS liquid soap container 109 mm wide, 125 mm high and 112 mm distance from wall of standard shape with bracket of the same materials with snap fittings of approved quality and colour, weighing not less than 105 gms.	10.00	Each
17	Providing and fixing 600 mm long towel rail-SS with total length of 645 mm, width 78 mm and effective height of 88 mm, weighing not less than 190 gms.	10.00	Each
18	Providing and fixing 900x750 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass screws and washers complete.	5.00	Each
19	Providing and fixing ss curtain rods of wall thickness 1.25 mm with two ss brackets fixed with ss screws and wooden plugs etc. wherever necessary complete. 25 mm diameter.	50.00	Meter
20	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings and fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc.		
	20 mm nominal dia Pipes	50.00	Meter
	32 mm nominal dia Pipes	75.00	Meter
21	Providing and fixing C.P. brass stop cock (having weight not less than 650gms) (concealed) of standard design and of approved make conforming to IS:8931.		
	15 mm nominal bore each	10.00	Each
22	Providing and fixing C.P. Brass extension nipple (size 15 mm x 50 mm) of approved make and quality as per direction of Engineer-in-charge.	6.00	Each
23	Providing and fixing CP brass stop cock of approved quality : 20 mm nominal bore weight should not less than 600gm	5.00	Each
24	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end) :weight should not less than 800gm 32 mm nominal bore.	3.00	Each
25	Providing and fixing 12 mm thick frameless toughened glass door shutter of approved brand and manufacture, including providing and fixing top & bottom pivot & double acting hydraulic floor spring type fixing arrangement and making necessary holes etc. for fixing required door fittings, all complete as per direction of Engineer-in-charge	30.00	SqM
26	Providing and fixing toilet paper holder :C.P. brass	5.00	Each

27	Providing and fixing 600x120x5 mm glass shelf with edges round off, supported on anodised aluminium angle frame with C.P. brass brackets and guard rail complete fixed with 40 mm long screws, rawl plugs etc., complete.	12.00	Each
28	Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete.Semi rigid pipe 40 mm dia	5.00	Each
29	Providing and fixing premium quality health faucet of approved make as approved by Engineer - in - charge.	5.00	Each
30	Providing and fixing unplasticised PVC connection pipe with brass unions : 45 cm length, 15 mm nominal bore	20.00	Each
31	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes.		
	75 mm diameter metre	50	Meter
	110 mm diameter metre	40	Meter
32	Providing and fixing CP brass basin mixer of premium quality of approved make having weight not less than 800 gm as approved by Engineer - in - charge.	5	Each
33	Providing and fixing CP brass wall mixer of premium quality of approved make having weight not less than 1200 gmas approved by Engineer - in - charge.	5	Each
34	Providing and fixing electric geyser-25 litre capacity 5star energy efficient including all plumbing and electrical fixtures and fitting etc. Complete as approved and directed by Engineer - in - charge.	5	Each
35	Providing and fixing on wall face unplasticised - PVC moulded fittings/accessories for unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS : 5382,leaving 10 mm gap for thermal expansion.		
	Coupler		
	75 mm	5	Each
	110 mm	5	Each
35.1	Single tee with door		
	75x75x75 mm	5	Each
	110x110x110 mm	5	Each
35.2	Single tee without door		
	75x75x75 mm	5	Each
	110x110x110 mm	5	Each
35.3	Bend 87.5°		
	75 mm bend	5	Each
	110 mm bend	5	Each
35.4	Shoe (Plain)		
	75 mm Shoe	5	Each
	110 mm Shoe	5	Each
36	Providing and fixing flase celing down light(18W) including wiring, modular switches and modular box & plate etc. all complete as per direction of Engineer-in-charge	30	Each
37	Providing and fixing flase celing down light 600x600mm (36 W) including wiring, modular switches and modular box & plate etc. all complete as per direction of Engineer-in-charge	20	Each
38	Providing and fixing casing & capping in position including removal of old casing at all height etc. complete as per direction of Engineer-in-charge	200	Metre
39	Providing & fixing modular switches-5/6A etc complete as per direction of Engineer-in-charge	100	Each
40	Providing & fixing modular switches-16/20A etc complete as per direction of Engineer-in-charge	40	Each
41	Providing & fixing modular socket-5/6A etc complete as per direction of Engineer-in-charge	20	Each
42	Providing & fixing modular socket-16/20A etc complete as per direction of Engineer-in-charge	40	Each

43	Providing & fixing modular box with plate etc complete-size as per direction of Engineer-in-charge	20	Each
44	Providing & fixing 1.5 sqmm copper wire for various connections etc complete as per direction of Engineer-in-charge	600	Metre
45	Providing & fixing 4 sqmm copper wire for various connections etc complete as per direction of Engineer-in-charge	300	Metre
46	Providing & fixing decorative wall mounted night lamp including wiring switches etc. all complete at all height as per direction of Engineer-in-charge	12	Each
47	Providing and fixing exhaust fan 450mm including electrical connection and fitting and making the wall as same as good or as per direction of Engineer-in-charge	3	Each
48	Providing and fixing CP brass two way bib cock including all fixtures and fittings having weight not less than 700gm of approved brand as per direction of Engineer-in-charge	3	Each
49	Providing and fixing of shower 300x300mm with 600mm ram as design approved by Er.-in-charge	5	Each
50	providing and fixing of 1.5 ton 5 star branded air-conditioning (AC) with wiring, switches, Iron box, Modular plates, including surface conducting, etc as per requirement design as approved by Er.-in-charge	10	Each
51	Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge.		
	In cement mortar	9.6	Cum
52	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in:		
	Cement mortar 1:6 (1 cement : 6 coarse sand)	7.2	Cum
	Brick work with common burnt clay machine moulded perforated bricks of class designation 12.5 conforming to IS: 2222 in superstructure above plinth level up to floor five level in cement mortar 1:6 (1 cement : 6 coarse sand) :		
53	With F.P.S.(non modular) bricks	27.6	Cum
54	Providing and fixing of modular wooden TV cabinet for 65/55 Inch LED TV with drawers and accessories of approved brand/design as per direction of Engineer-in-charge.	9	Each
55	Providing and fixing of wooden cupboard of size 2.1x1.2x0.45M with accessories of approved brand/design as per direction of Engineer-in-charge	9	Each
56	Mirror polishing on marble work/Granite work/stone work where ever required to give high gloss finish complete.	30	SqM
57	Taking out existing wooden door shutter, repair by cutting, painting etc. and refixing of repaired door shutters to existing door frames, including replacement of hinges with screws, etc. as required, all complete as per the direction of the Engineer-in-charge.	50	Each
58	Tiles Cleaning and epoxy filling in tiles joints complete work as per direction of Engineer-in-Charge.	100	SqM
59	Providing and fixing of SS Wire mesh of 0.5mm thickness with complete fitting including dismantling of old wire mesh and other necessary screws and wooden beading complete work as per direction of Engineer-in-Charge.	150	SqM
60	Providing and fixing double scaffolding system (cup lock type) on the exterior side of building/structure, upto 25 metre height, above ground level, including additional rows of scaffolding in stepped manner as per requirement of site, made with 40 mm dia M.S. tube, placed 1.5 metre centre to centre, horizontal & vertical tubes joint with cup & lock system with M.S. Tubes, M.S. tube challis, M.S. clamps and staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for execution of work of cleaning and/ or pointing and/ or applying chemical and removing it thereafter. The scaffolding system shall be stiffened with bracings, runners, connecting with the building etc, wherever required, if feasible, for inspection of work at required locations with essential safety features for the workmen etc., complete as per directions and approval of Engineer-in-charge. Note:- (1) The elevational area of the scaffolding shall be measured for payment purpose. (2) The payment will be made once only for execution of all items for such works.	371.20	SqM

61	Providing and fixing of powder coated auto/digital electric distribution panel (4 in 1) 20 Kwatt including necessary nuts and bolts, lugs, cable for connection, and all fixtures as per requirement of approved brand and design as per direction of Engineer-in-charge.	3	Nos
62	Providing corrugated G.S. sheet roofing including vertical / curved surface fixed with polymer coated J or L hooks, bolts and nuts 8 mm diameter with bitumen and G.I. limpet washers or with G.I. limpet washers filled with white lead, including a coat of approved steel primer and two coats of approved paint on overlapping of sheets complete (up to any pitch in horizontal/ vertical or curved surfaces), excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.		
	0.63 mm thick with zinc coating not less than 275 gm/ m ²	20	SqM
63	Steel work in built up tubular (round, square or rectangular hollow tubes etc.) trusses etc., including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete.		
	Hot finished welded type tubes	170	Kg
64	Providing and laying gang saw cut 18 mm thick, mirror polished pre moulded and pre polished machine cut granite stone of required size and shape of approved shade, colour and texture in footpath, flooring cut granite stone of required size and shape of approved shade, colour and texture in footpath, flooring in road side plazas and similar locations, laid over 20mm thick base of cement mortar 1:4 (1cement : 4 coarse sand) including grouting the joints with white cement mixed with matching pigment, epoxy touch ups etc. complete as per direction of Engineer-in-Charge.		
	With granite stone of area less than 0.50 sqm.	10.125	sqm

Note: - Lowest Contractor (L-1) will be decided on overall lowest rates basis. (All items to be used in this work should be branded and ISI certified or as per approved list of material may be followed. If any make is not specified, decision of Engineer-in-charge shall be final.)

DIG (Engr) , Works Dte
For and on behalf of the President of India