

OFFICE OF THE Dy. INSPECTOR GENERAL OF POLICE, CRPF GREATER NOIDA, G.B. NAGAR (U.P)

NOTICE INVITATING TENDER

N.I.T. No.: L-VII-1/2021-22-GCNDA (BLDG) SAP

NAME OF WORK: "Construction of 01 No. toilet (western style with wash

basin) for ladies at 100 mtr baffle firing range in GC,

CRPF Greater Noida".

ESTIMATED COST: Rs.1,59,553/-

EARNEST MONEY: NIL

COMPLITION PERIOD: 30 Days.

Sd/-13-01-2022 (Ras Bihari Singh) DIG, GC, CRPF G/NOIDA For and on behalf of the President of India

SCHEDULE TO TENDER

(Open Tender)

GROUP CENTRE, CENTRAL RESERVE POLICE FORCE

Village-Suthiyana, Post-Kuleshara, Opp.-Dewoo Motors, Greater Noida, Distt- G.B.Nagar (U.P.) – 201306, Tel/Fax: 0120-2352900

No. L.VII-1/21-22-GC G/NDA-BLDG (SAP)

Dated, the

13 January'2022

//E-TENDER //

Sealed tenders are invited from registered firms/contractors for work "Construction of 01 No. toilet (western style with wash basin) for ladies at 100 mtr baffle firing range in GC, CRPF Greater Noida". The works will be executed departmentally through contract basis in accordance with the PE of CRPF.

As per details given below.

Sl.No.	Description of Item's	Unit	QTY
1	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m.		
1.1	All kinds of soil.	cum	2.27
2	Brick work with common burnt clay F.P.S. (non-modular) bricks of class designation 7.5 in foundation and plinth in:		
2.1	Cement mortar 1:6 (1 cement : 6 coarse sand)	cum	1.13
3	Brick work with common burnt clay F.P.S. (non-modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in :		
3.1	Cement mortar 1:6 (1 cement : 6 coarse sand)	cum	2.69
5	12 mm cement plaster of mix :		
5.1	1:4 (1 cement: 4 fine sand)	sqm	23.52
6	Supplying and filling in plinth with sand under floors, including watering, ramming, consolidating and dressing complete.	cum	0.43
7	Providing and laying in position cement concrete of specified grade excluding the cost of cantering and shuttering - All work up to plinth level:		
7.1	1:5:10 (1 cement : 5 coarse sand (zone-III): 10 graded stone aggregate 40 mm nominal size)	cum	0.43
8	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete.		
8.1	Size of Tile 500x500 mm	sqm	1.80
9	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	sqm	6.48

10	Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in		
	240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should		
	besupplied in single length upto 12 metre or as desired by Engineerin- charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or		
	curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	sqm	3.24
11	Providing and fixing false ceiling at all height including providing andfixing of frame work	~ 1	
	made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS: 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate		
	channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mmthick 27 mm high having flanges of 20 mm and 30 mm long, theperimeter of ceiling fixed to wall/partition with the help of rawl plugsat 450 mm centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum board to ceiling section andperimeter channel with the help of dry wall screws of size 3.5 x 25mm at 230 mm c/c, including jointing and finishing to a flush finishof tapered and		
	square edges of the board with recommended jointingcompound, jointing tapes, finishing with jointing compound in 3layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitablyfixed, all complete as per drawings, specification and direction of the Engineer in Charge but excluding the cost of painting with		
11.1	12.5 mm thick tapered edge gypsum moisture resistant board	sqm	3.24
12	Providing and fixing white vitreous china pedestal type water closet(European type) with seat and lid, 10 litre low level white vitreous china flushing cistern & C.P. flush bend with fittings & C.I. brackets,40 mm flush bend, overflow arrangement with specials of standard make and mosquito proof coupling of approved municipal design complete, including painting of fittings and brackets, cutting and making good the walls and floors wherever required:		
12.1	W.C. pan with ISI marked white solid plastic seat and lid	Each	1.00
13	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require:		
13.1	White Vitreous China Wash basin size 630x450 mm with a pair of 15 mm C.P. brass pillar taps.	Each	1.00
14	Providing and fixing CP Brass 32mm size Bottle Trap of approved quality & make and as per the direction of Engineer-in-charge.	Each	1.00
15	Providing and fixing mirror of superior glass (of approved quality) and of required shape and size with plastic moulded frame of approved make and shade with 6 mm thick hard board backing:		
15.1	Rectangular shape 1500x450 mm	Each	1.00
16	Providing and fixing 600x120x5 mm glass shelf with edges round off,		
15	supported on anodised aluminium angle frame with C.P. brass brackets and guard rail complete fixed with 40 mm long screws, rawl plugs etc., complete.	Each	1.00
17	Providing and fixing toilet paper holder:	Г 1	1.00
18 19	C.P. brass Providing and fixing soil, waste and vent pipes:	Each	1.00
19.1	100 mm dia		
19.1.1	Sand cast iron S&S pipe as per IS: 1729	metre	10.00
17.1.1	Sand cast non sees pipe as per is. 1/27	mene	10.00

• •		1	
20	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and		
	the cost of cutting chases and making good the same including testing of joints		
	complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc.		
20.1	15 mm nominal outer dia Pipes	Metre	10.00
20.1.1	20 mm nominal outer dia Pipes	Metre	14.00
21	Providing and fixing C.P. brass angle valve for basin mixer and geyser points	Wietre	11.00
	of approved quality conforming to IS:8931		
21.1	15mm nominal bore	Each	2.00
22	Providing and fixing unplasticised P.V.C. connection pipe with PTMT Nuts, collar and bush of approved quality and colour.		
22.1	15 mm nominal bore with 45 cm length	Each	2.00
23	Constructing brick masonry circular manhole 1.22 m internal dia at bottom		
	and 0.56 m dia at top in cement mortar 1:4 (1 cement :4 coarse sand) inside		
	cement plaster 12 mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished with a floating coat of neat cement foundation concrete 1:3:6		
	(1 cement : 3 coarse sand : 6 graded stone aggregate 40 mm nominal size)		
	and making necessary channel in cement concrete 1:2:4 (1 cement : 2 coarse		
	sand: 4 graded stone aggregate 20 mm nominal size) finished with a		
	floating coat of neat cement, all complete as per standard design:		
23.1	1.68 m deep with SFRC Cover and frame (heavy duty HD- 20 grade		
	designation) 560 mm internal diameter conforming to I.S. 12592, total weight of cover and frame to be not less than 182 kg. fixed in cement concrete 1:2:4		
	(1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)		
	including centering, shuttering all complete. (Excavation, foot rests and 12		
222.1.1	mm thick cement plaster at the external surface shall be paid for separately):		
233.1.1	With common burnt clay F.P.S. (non modular) bricks of class designation 7.5	Each	1.0
24	Providing and fixing Fiber Glass Reinforced plastic (FRP) Door Frames of		
	cross-section 90 mm x 45 mm having single rebate of 32 mm x 15 mm to receive shutter of 30 mm thickness. The laminate shall be moulded with fire		
	resistant grade unsaturated polyester resin and chopped mat. Door frame		
	laminate shall be 2mm thick and shall be filled with suitable wooden block in		
	all the three legs. The frame shall be covered with fiber glass from all sides.		
	M.S. stay shall be provided at the bottom to steady the frame.	Metre	15.00
24.1	30 mm thick Glass Fibre Reinforced Plastic (FRP) panelled door shutter of		
	required colour and approved brand andmanufacture, made with fire - retardant grade unsaturated polyester resin, moulded to 3 mm thick FRP		
	laminate for forming hollow rails and styles, with wooden frame and suitable		
	blocks of seasoned wood inside at required places for fixing of fittings, cast		
	monolithically with 5 mm thick FRP laminate for panels conforming to IS:		
25	14856, including fixing to frames.	Sqm	1.58
25	Providing and applying plaster of paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete.	cam	22 52
26	Distempering with oil bound washable distemper of approved brand and	sqm	23.52
	manufacture to give an even shade :		
26.1	New work (two or more coats) over and including water thinnable priming		10.50
27	coat with cement primer Finishing walls with Acrylic Smooth exterior paint of required shade:	sqm	12.50
27.1	New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including		
2,1	priming coat of exterior primer applied @ 2.20 kg/10 sqm)	sqm	15.57
28	Providing and fixing PTMT grating of approved quality and colour.		
28.1	Circular type		
28.2	100 mm nominal dia	Each	1.00
	Providing and fixing of two way bib cock.	Each	1.00

30	Providing and fixing of Exhaust fan 9" with 1.5 sq mm copper wire and all		
	required fittings.	Each	1.00
31	Providing and fixing of LED ceiling Light 1' x 1' with all fittings (Wiring and		
	Switch etc.)	Each	2.00
32	Providing and fixing of LED T5 Tube light with all fittings.	Each	1.00

A) SCHEDULE TO TENDER:

Schedule to Tender No.			No. L.VII-1/2	21-22-GC	G/NDA-B	LDG (SAP)	
	date and time	of receipt of on-line & s of tender	line & 21/01/22 at 1600 Hrs,				
Time and date of on-line opening e-tender 22/01/22 at 1600 Hrs							
Valid	dity of offer			The tender shall remain open for acceptance till 180 days from the date of opening of Tender.			
Sl. No.	Ref. No.	Name of work & Location		Estimated	Period of Completion	Last date & time of Submission of tender	Time & date of opening of tender
01.	No. L.VII- 1/21-22- GC /NDA- BLDG (SAP)	"Construction of 01 No. with wash basin) for ladie firing range in GC, CRPF (es at 100 mtr baffle	Rs. 1,59,553/-	30 days after award of work	21/01/22 at 1600 Hrs,	22/01/22 at 1600 Hrs

B. Terms and conditions are as under:

1.Terms of	1.1 Rates quoted by the Contractor should be in Indian Rupees both in figures as well as in words
Price	for complete units as per specifications any and every alteration in the rates should be signed in
	ink otherwise the offers will not be considered.
	1.2 Contractor should clearly indicate different taxes and duties, which they propose to charge as extra along with the present rates thereof. Offers with such stipulations like 'as applicable' will be treated as vague and are liable to be ignored.

2. Payment terms

- **2.1** Works are required to be executed on **credit basis only** and payment will be made after drawl of amount from RPAO. CRPF Delhi.
- **2.2** Payment in advance or immediately on delivery of material cannot be considered and tender with such condition will be rejected.
- **2.3** The Payment action will be processed on production of the following documents:-
- a) Bill in Triplicate.
- b) A Copy of award of work.
- c) A copy of Certificate issued by the DIG-cum-Estate Officer GC, CRPF, G/Noida /Work Committee of GC, CRPF, G/Noida that contracted work for the period for which payment has been claimed, has carried out by the contractor satisfactory.
- **2.4** TDS, Labour Cess and other taxes will be deducted from the Bill of contractor by RPAO as per norms.
- **2.5** Tenderer are requested to check physically the location where the work "Construction of 01 No. toilet (western style with wash basin) for ladies at 100 mtr baffle firing range in GC, CRPF Greater Noida".is to be carried out and other technical details before submitting the tender. TEC detailed by the DIG GC, G/Noida will check technical bid of work "Construction of 01 No. toilet (western style with wash basin) for ladies at 100 mtr baffle firing range in GC, CRPF Greater Noida".) and price bid will be opened of only those firms which qualify in technical bid.

Tender Fee

Not Required

Performance Security Deposit

- 3.1. The successful contractor shall have to deposit a Performance Security deposit **equivalent** to 3 % of the contract value of the work to be executed within 08 days from the date of award of contract for due performance. Failure on the part of the firm to Deposit the Performance Security Deposit within the stipulated time empowers the competent authority to cancel the contract.
- 3.2. The Performance Security Deposit submitted by the contractor will remain valid at least for 180 days beyond the date of completion of work as well as all contractual obligations of the supplier including guarantee/warrantee obligations.
- 3.3. The performance security deposit can be deposited in any of the following alternative forms (a) A **FDR/DD**/drawn in favour of DIGP, GC, CRPF, Greater Noida, Payable at SBI COLLECTORATE COPMOUND G/NOIDA (Branch code-05106).
- (b) An **irrevocable Bank Guarantee** of any nationalized/Scheduled Bank or reputed commercial bank in **any other form prescribed.**
- 3.4. If the contractor fails to start the work within the stipulated period and places and requests for extension of time, he shall submit an undertaking on Non Judicial stamp paper of Rs.10/- duly attested by the Notary public stating that the performance security deposit has already been extended for sixty days beyond the guarantee/warrantee period.
- 3.5. The Performance Security Deposit shall be withheld or forfeited in full or part in case the work order is not executed satisfactorily within the stipulated period or requisite standard within the guarantee period is not undertaken to the best satisfaction of the user.

4. Eligibility of Contractor

The Tenderer should be a Govt. registered like CPWD, MES, BRO, NBCC, State PWD participating.

- 1. The enlistment of the contractor should be valid on the last date of submission of Bids.
- 2. In case the last date of submission of Bid is extended, the enlistment of the contactor should be valid on the original date of submission of Bids.
- 3. Supply order as a experience certificate will not be considered, In case of execution of work/repair and renovation work.
- 4. Attested copy of registration in any Govt. deptt. as approved contractor (Registration details showing appropriate class and category).
- 5. Enlisted CPWD contractors above Class I Composite category are allowed to participate up to their tendering limits without submitting Eligibility documents. Firms and Contractors, not registered with CPWD are required to submit Eligibility documents of executing similar works.
- (i) Experience of having successfully completed works during the last 7 years ending previous day of last date of submission of tenders Three similar completed works, each costing not less than the amount equal to 40% of estimated cost put to tender.

oı

		ilar completed works, each costing not less than the cost put to tender. or	e amount equal to 60% of the
	One simi	lar completed work of aggregate cost not less than t	he amount equal to 80% of the
5. TWO BID	5.1. Since	e the work to be undertaken is of a complex and technic	cal nature, bids are required to be
SYSTEM :-		l in two parts as under :-	•
	https://ep details of	Bids will be accepted ONLINE at rocure.gov.in/eprocure/cppp and all documents also re online documents should be clearly visible otherwise nical bid: Relevant documents and information to be	the bid will be rejected.
	technical		Turning and succession as part of
	5.4 Sca http://epr	anned copy of Documents to be submicocure.gov.in/eprocure/cpppand all documents OFFLIN d envelope placed at Adm Block of GC CRPF, Greate	E to be dropped in the tender box
	SL No.	Name of documents	Description of documents
		Tender Notice All pages of tender notice duly	Tender Notice All pages of tender notice duly
	01	CPWD,MES,BRO,NBCC,PWD Reg. Certificate	
	02	PAN /TAN card details	
	03	GSTIN/ Firm registration certificate	
	04	Bank guarantee for furnishing performance security deposit	APPENDIX-A
	05	Performance statement of last three years including last three year work completion certificate	APPENDIX-B
	06	List No. 01	APPENDIX-C
	07	Questionnaires/ Check list (Must be filled in all respect)	APPENDIX-D
	08	Tender acceptance Letter(duly signed by bidder and witness)	APPENDIX-E
	09	Form 68-A	APPENDIX- F
	10	Index of Documents (Indicate page number of tender documents required).	APPENDIX-G
	11	Proforma for Earnest Money Deposit Declaration.	APPENDIX-H
	12	Any other document	
	provided	ncial / price bid :- The composite bid shall be quote along with tender document at ocure.gov.in/eprocure/cppp.	ed as per enclosed BOQ format E —Procurement site
6. EVALUATION	authority opened for 6.2 The tenvelopes	technical bids are to be opened at the first instance at In the second stage, financial bids of only the technical bid and financial bid submitted by the Tenes placed in one big envelope while submission of offliraping of tender.	nically acceptable offers will be contract. derer should be in two separate

7. WORK SPECIFICATION

The work shall be carried out according to C.P.W.D. Specifications 2018 Volume-I & II including up to date correction slips and as per additional conditions.

6.3 The tender enquiries duly filled in all respects and having completed in all applicable formalities may be sent to DIG-cum-Estate Officer GC, CRPF Greater Noida, Campus so as to reach on or before to the tender enquiry. Department is not responsible for any postal delay as

8. SITE VISIT AND COLLECTING LOCAL INFORMATION

well as technical problem at portal/site.

Before tendering, the Tenderer is advised to visit the site, its surroundings to assess and satisfy themselves about the local conditions such as the working and other constraints at site, approach roads to the site, availability of water & power supply, application of taxes, duties and levies as applicable, accommodations they may require etc& any

other relevant information required by them to execute complete scope of work. The Tenderer may obtain all necessary information as to risks, weather conditions, contingencies & other circumstances (insurgencies etc.) which may influence or affect their tender prices. Tenderer shall be deemed to have considered site conditions whether he has inspected it or not and to have satisfied himself in all respect before quoting his rates and no claim or extra charges whatsoever in this regard shall be entertained / payable by the **GC CRPF**, **Greater Noida** at a later date.

9. VALIDITY OF TENDER

The tender for the works shall remain open for acceptance for a period **180** days from the date of opening of Price Bid of tenders.

10. REJECT/CANCEL/SCRAP

The Competent Authority has got the right to accept or reject/cancel/scrap the tender as whole or part of it and no claims what so ever will be entertained on this account. The competent authority also reserves the right to increase/decrease/alter the scope of work/ quantity of work etc. and no claims what so ever will be entertained

11. TERMINATION OF CONTRACT ON DEATH OF CONTRACTOR

Without prejudice to any of the right or remedies under this contract if the contractor dies, the DIG-cum-Estate Officer GC, CRPF, Greater Noida shall have the option of terminating the contract without compensation to the contractor. If the contractor is an individual or proprietary concern and individual or the proprietor dies or if the contractor is a partnership concern and one of the partner dies then unless, the DIG-cum-Estate Officer GC, CRPF, Greater Noida is satisfied that the legal representative of the individual for the proprietary concern or the surviving partners are capable of carrying out and completing contract, the (DIG-cum-Estate Officer GC, CRPF, Greater Noida) is entitled to cancel the contract for the uncompleted part without being in any way liable for any compensation payment to the estate of deceased contractor or to the surviving partners of the contractor's firm on account of the cancellation of contract. The decision of the DIG-cum-Estate Officer GC, CRPF, Greater Noida in such assessment shall be final and binding on the parties. In the event of such cancellation the DIG-cum-Estate Officer GC, CRPF, Greater Noida shall not hold the state of deceased contractor and/or the surviving partners of the contractor's firm liable for any damages for non-completion of contract.

12. DIRECTION FOR WORKS

All works to be executed under the contract shall be executed Under the direction and subject to approval in all respect of the DIG-cum-Estate Officer GC, CRPF Greater Noida/Work Committee /Officer commanding of Building /Engineer-in-Charge of DIG-cum-Estate Officer GC, CRPF, Greater Noida who shall be entitled to direct at what point or points and in what manner works are to be commenced and executed.

13. DEFECT LIABILITY PERIOD

- i) 12 Months from the date of Completion as certified by the DIG-cum-Estate Officer GC, CRPF, Greater Noida/Officer commanding of Building Branch / Work Committee.
- ii) The contractor shall stand guarantee for materials and workmanship. During the defect liability period, if any defect is observed due to workmanship or from any act or omission of the contractor, the contractor shall execute all such work of rectification and making good of defects, as may be required of him by competent authority at his own cost and within the time stipulated by competent authority. If the contractor shall fail to do any such work as required by the competent authority, Security/Retention money shall be liable to be forfeited and the contractor shall make himself liable to be blacklisted.

14. SECURITY DEPOSIT/ RETENTION MONEY

The security deposit @ 2.5% of the gross amount of the bill shall be deducted from final bill of the contractor. The contractor can also deposit the security deposit through FDR @ 2.5% of the tendered amount in favor of DIG, GC, CRPF, Greater Noida payable at SBI COLLECTORATE COPMOUND G/NOIDA (Branch code-05106) before submitting the final bill for payment action. The security deposit or retention money shall be refunded to the contractor after expiry of defects liability period (referred to Clause No.13) or on payment of the amount of the final bill whichever is later. This is in addition to Performance Guarantee that the contractor is required to deposit.

- **15.** Before starting the work the contractor shall chalk out a programme, in consultation with the DIG-cum-Estate Officer GC, CRPF, Greater Noida or his authorized representative at least one week in advance. The contractor shall have to adhere to this programme failing which he shall be held responsible for any inconvenience caused to the occupants. In order to ensure that the work is carried out according to the programme drawn, the contractor shall ensure adequate supply of the material and employ required labour strength for execution of work. The contractor shall put his authorized representatives daily at the site of work /Enquiry Office for receiving instructions from DIG cum- Estate Officer GC, CRPF, **Greater Noida** and other inspecting officials from the department. His name and signature shall be attested by the contractor and kept on the record with the department.
- **16**. Payment shall be made to contractor only after giving certificate about satisfactory completion of work. All measurement shall be recorded on standard measurement sheets which will be submitted to the DIG-cum-Estate Officer GC, Greater Noida for scrutiny and passing.
- **17.** DIG-cum-Estate Officer GC, CRPF, Greater Noida/ Works committee/ Officer commanding of Building/ Engineer-in-charge shall scrutinize and check the measurement records practically/on ground based on the measurement sheet provided by contractor and final measurement sheet will be prepared by Engineer-in-charge of this office.
- 18 while the Tenderer and the purchaser shall make every effort to resolve any issue amicably through direct informal negotiation, in the event of any disagreement or dispute arising between them under or in connection with the contract shall be settled under court of law within its jurisdiction at state under. The resultant contract will be interpreted as per the prevailing Indian laws and various directions of the Govt. of India. Dispute in mode of measurement: In case of dispute as to the mode of measurement not covered by the contract to be adopted for any item of work, mode of measurement as per latest Indian specification shall be followed.
- 19. Intending Tenderer is eligible to submit the bid provided he has definite proof from the appropriate authority, which shall be to the satisfaction of the competent authority, of having satisfactorily completed similar works of magnitude specified.
- 20. The time allowed for carrying out the work will be within 30 days from the date of work order.
- 21. The site for the work is available or the site for the work shall be made available in parts as specified above.
- **22.** The contractor shall not be permitted to tender for works in the CRPF in which his near relative of CRPF is involved. If so, he shall also intimate the names of persons who are working with him in any capacity or are subsequently employed by him and who are near relatives to any CRPF officer/personnel.
- **23.** Department will not be responsible for any kind of incident involving the labour during or after the work. The contractor must insure the workers against all contingencies and be responsible for their safety.
- **24.** GST No. / Service Tax No. and Contractor's Regn. No. must be printed on the bill which is submitted for recoupment/payment action.
- 25. The tender for the works shall remain open for acceptance for a period of 180 Days from the date of opening of tenders. If any Tenderer withdraws his tender before the said period or issue of letter of acceptance, whichever is earlier, or makes any modifications in the terms and conditions of the tender which are not acceptable to the department, then the Government shall, without prejudice to any other right or remedy, be at liberty to not be allowed to participate in the retendering process of the work.
- **26**. The contractor shall bear cost **of Liquidated Damage** for Delay in completion of work within the stipulated time @ of **2%** of contracted value not exceeding the 10% of contracted value in whole.
- 27. This Notice Inviting Tender shall form a part of the contract document.
- **28**. Hard copies as submitted physically in the office of DIG-cum-Estate Officer GC, CRPF, Greater Noida, shall be only valid document for evaluation of technical specification. The DIG-cum-Estate Officer GC, CRPF, Greater Noida, has all rights to break contract at any time without assigning any reason.
- 29. The Tenderer are requested to return a copy of this Tender duly signed on each page along with other relevant documents as required with the tender for evaluation purpose. If Tenderer fails to return a copy of this Tender duly signed, his offer will not be considered and it will be rejected.

- **30**. The Tenderer shall be responsible for arranging and maintaining at his own cost all materials, tools & plants, water, electricity access, facilities for executing work and all other services required for executing the work.
- **31.** The successful Tenderer shall make his own arrangement for storage and watch and ward of material whether the same brought by him or supplied by the department. He shall remain responsible for watch and ward of installation and other fittings till these are commissioned and handed over to the department.
- **32.** Successful Tenderer should be in a position to produce, after opening of the price bids, the Original Certificates in support of the self-attested copies of relevant documents submitted along with tender document. Failure to produce the original certificates at this stage in support of the attested copies of firm registration /Electrical License/any other documents etc. submitted earlier would result in disqualification and also liable for debarring from participation in DIG-cum-Estate Officer GC, CRPF Greater Noida, tenders.
- **33. FINAL INSPECTION: -** After completion of work as per specification the whole work will be subject to a final inspection to ensure that job has been completed as per requirement. If any defects noticed in the work are attributable to Contractor, these shall be attended by the Contractor at his own cost, as and when they are brought to his notice by the DIG-cum-Estate Officer GC, CRPF, Greater Noida, /Work committee/ Officer Commanding of Building/Engineer in charge. The DIG cum-Estate Officer GC, CRPF, Greater Noida, and its representative shall have the right to have these defects rectified at the risk and cost of the contractor if he fails to attend to these defects immediately.
- **34. MEASUREMENTS OF WORK DONE:** Engineer-in-charge shall, except as otherwise provided, ascertain and determine by measurement, the value in accordance with the contractor of work done.

All measurement of all items having financial value shall be entered in Measurement Book/level field book so that a complete record is obtained of all works performed under the contract. All measurement and levels shall be taken jointly by the Insp/SI/civil or his authorized representative and by the contractor or his authorized from time to time during the progress of the work and such measurement shall be signed and dated by the Engineer –in-charge and the contractor or their representatives in token of their acceptance. If the contractor objects to any of the measurement recorded, a note shall be made to that effect with reason and signed by both the parties. If for any reason the contractor or his authorized representative is not available and the work of recording measurement is suspended by the Insp/SI/civil or his representative, the Engineer –in-charge and the Department shall not claim from contractor for any loss or damages on his account. If the contractor or his authorized representative does not remain present at the time of such measurements after the contactor or his authorized representative has been given a notice in writing three (3) days in advance or fails to countersign or to record objection within a week from the date of the measurement, then such measurement recorded in his absence by the Engineer –in-charge or his representative Shall be deemed to be accepted by the contractor.

It is also a term of this contract that recording of measurements of any items of work in the measurement book and /or its payment in the interim, on account of final bill shall not be considered as conclusive evidence as to the sufficiency of any work or material to which it relates nor shall it relieve the contractor from liabilities from any over measurement or defects noticed till completion of the liability period.

- **35.** Work scope may be changed depending upon the priority of the work.
- **36.** No part of the CONTRACT nor any share or interest therein shall in any manner or degree be transferred, assigned or sublet by the CONTRACTOR directly or indirectly to any person, firm or corporation whatsoever without the consent in writing of the DIG-cum-Estate Officer GC, CRPF, Greater Noida.

Sd/-13-01-2022 (Ras Bihari Singh) DIG, GC, CRPF G/NOIDA For and on behalf of the President of India

A. ADDITIONAL SPECIFICATIONS FOR CIVIL WORKS:

- 1. All materials required to be used on works shall be got approved from the DIG-cum-Estate Officer GC, CRPF Greater Noida,/ Officer Commanding of Building in advance. In case of doubt on any material, DIG, GC CRPF Greater Noida, wears the right to get the material test from Govt. approved labs/NABL.
- 2. The quoted rate should be inclusive of all taxes, levies, works contract taxes, duties etc.
- 3. All items to be used in this work should be branded and ISI. In this case CPWD approved list of material for similar work may be followed.

Sd/-13-01-2022
(Ras Bihari Singh)
DIG, GC, CRPF G/NOIDA
For and on behalf of the President of India

The Performance Security Deposit submitted by the contractor will remain valid at least for 180

B. Details of work: -

	days beyond the date of completion of work as well as all contractual obligations of the supplier				
	including guarantee/warrantee obligations.				
Scope of	1. Earth work in excavation for foundation of Toilet.				
Work	2. 230 mm and 115 mm thick Brick work in foundation and super structure		cement: sand).		
	3. Plastering with 12 mm thick cement sand ration 1:4 both side outer and in	nner side.			
	4. Providing and laying of ceramic wall tile & floor tile.				
	5. Providing and fixing sanitary and plumbing work.				
	6. Providing and fixing PVC tank with MS structure. 7. Providing and fixing profile about reafing % false Cailing.				
	7. Providing and fixing profile sheet roofing & false Ceiling.8. Providing and fixing an electrical work i.e. wiring and light fittings etc.				
	9. Connection with sewer line.				
S.NO.	Description of Item's	Unit	QTY		
1	Earth work in excavation by mechanical means (Hydraulic excavator) / manual				
	means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm				
	on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m,				
	including getting out the excavated soil and disposal of surplus excavated soil as				
	directed, within a lead of 50 m.				
1.1	All kinds of soil.	cum	2.27		
2	Brick work with common burnt clay F.P.S. (non-modular) bricks of class				
	designation 7.5 in foundation and plinth in:				
2.1	Cement mortar 1:6 (1 cement : 6 coarse sand)	cum	1.13		
3	Brick work with common burnt clay F.P.S. (non-modular) bricks of class				
	designation 7.5 in superstructure above plinth level up to floor V level in all				
	shapes and sizes in:				
3.1	Cement mortar 1:6 (1 cement : 6 coarse sand)	cum	2.69		
5	12 mm cement plaster of mix :				
5.1	1:4 (1 cement: 4 fine sand)	sqm	23.52		
6	Supplying and filling in plinth with sand under floors, including watering,				
	ramming, consolidating and dressing complete.	cum	0.43		
7					
	Providing and laying in position cement concrete of specified grade excluding				
	the cost of centering and shuttering - All work up to plinth level:				

7.1	1510/1 . 5 1/ 10 11	1	
7.1	1:5:10 (1 cement : 5 coarse sand (zone-III): 10 graded stone aggregate 40 mm nominal size)	cum	0.43
8			
	Providing and laying vitrified floor tiles in different sizes (thickness to be		
	specified by the manufacturer) with water absorption less than 0.08% and		
	conforming to IS: 15622, of approved make, in all colours and shades, laid on		
	20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey		
	cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and		
	matching pigments etc., complete.		
8.1	Size of Tile 500x500 mm	sqm	1.80
9			
	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS:		
	15622 (thickness to be specified by the manufacturer), of approved make, in all		
	colours, shades except burgundy, bottle green, black of any size as approved by		
	Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed		
	of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement		
	slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment		C 10
10	of matching shade complete.	sqm	6.48
10	Providing and fixing precoated galvanised iron profile sheets (size, shape and		
	pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240		
	mpa steel grade, 5-7 microns' epoxy primer on both side of the sheet and		
	polyester top coat 15-18 microns. Sheet should have protective guard film of 25		
	microns minimum to avoid scratches during transportation and should		
	besupplied in single length upto 12 metre or as desired by Engineer in- charge.		
	The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55)		
	mm) with EPDM seal, complete upto any pitch in horizontal/vertical or curved		
	surfaces, excluding the cost of purlins, rafters and trusses and including cutting		
	to size and shape wherever required.	sqm	3.24
11	Providing and fixing false ceiling at all height including providing and fixing of frame	Sqiii	3.21
	work made of special sections, power pressed from M.S. sheets and galvanized with zinc		
	coating of 120 gms/sqm (both side inclusive) as per IS: 277 and consisting of angle		
	cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm		
	centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50		
	mm of required length with nuts & bolts of required size and other end of angle hanger		
	fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm		
	centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with		
	tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall		
	be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips		
	made out of 2.64 mm dia x 230 mm long G.I.wire at every junction, including fixing		
	perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugsat 450 mm		
	centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum		
	board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5		
	x 25mm at 230 mm c/c, including jointing and finishing to a flush finishof tapered and		
	square edges of the board with recommended jointing compound, jointing tapes,		
	finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint		
	and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made		
	with frame of perimeter channels suitablyfixed, all complete as per drawings,		
	specification and direction of the Engineer in Charge but excluding the cost of painting		
	with		
11.1	12.5 mm thick tapered edge gypsum moisture resistant board		2.24
12	Providing and fixing white vitreous china pedestal type water closet(European	sqm	3.24
	type) with seat and lid, 10 litre low level white vitreous china flushing cistern &		
	C.P. flush bend with fittings & C.I. brackets,40 mm flush bend, overflow		
	arrangement with specials of standard make and mosquito proof coupling of		
	approved municipal design complete, including painting of fittings and brackets,		
	cutting and making good the walls and floors wherever required:		
i			
12.1	W.C. pan with ISI marked white solid plastic seat and lid	Each	1.00

13			
	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps,		
	32 mm C.P. brass waste of standard pattern, including painting of fittings and		
	brackets, cutting and making good the walls wherever require:		
13.1			
	White Vitreous China Wash basin size 630x450 mm with a pair of 15 mm C.P.	Each	1.00
14	brass pillar taps. Providing and fixing CP Brass 32mm size Bottle Trap of approved quality &	Each	1.00
1.	make and as per the direction of Engineer-in-charge.	Each	1.00
15	Providing and fixing mirror of superior glass (of approved quality) and of	Lacii	1.00
	required shape and size with plastic moulded frame of approved make and shade		
	with 6 mm thick hard board backing:		
15.1	Rectangular shape 1500x450 mm	Each	1.00
16	Providing and fixing 600x120x5 mm glass shelf with edges round off, supported		
	on anodised aluminium angle frame with C.P. brass brackets and guard rail		
	complete fixed with 40 mm long screws, rawl plugs etc., complete.	Each	1.00
17	Providing and fixing toilet paper holder:		
18	C.P. brass	Each	1.00
19	Providing and fixing soil, waste and vent pipes:		
19.1	100 mm dia		
19.1.1	Sand cast iron S&S pipe as per IS: 1729	metre	10.00
20	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having		
	thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes		
	jointing of pipes & fittings with one step CPVC solvent cement and the cost of		
	cutting chases and making good the same including testing of joints complete as		
	per direction of Engineer in Charge. Concealed work, including cutting chases		
20.1	and making good the walls etc.		
20.1	15 mm nominal outer dia Pipes	Metre	10.00
20.1.1	20 mm nominal outer dia Pipes	Metre	14.00
21	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931		
21.1	15mm nominal bore	Each	2.00
22		Eacii	2.00
22	Providing and fixing un-plasticised P.V.C. connection pipe with PTMT Nuts, collar and bush of approved quality and colour.		
22.1	15 mm nominal bore with 45 cm length	Each	2.00
23	Constructing brick masonry circular manhole 1.22 m internal dia at bottom and	Lacii	2.00
	0.56 m dia at top in cement mortar 1:4 (1 cement :4 coarse sand) inside cement		
	plaster 12 mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished		
	with a floating coat of neat cement foundation concrete 1:3:6 (1 cement : 3		
	coarse sand: 6 graded stone aggregate 40 mm nominal size) and making		
	necessary channel in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) finished with a floating coat of neat		
	cement, all complete as per standard design:		
23.1	1.68 m deep with SFRC Cover and frame (heavy duty HD- 20 grade designation)		
	560 mm internal diameter conforming to I.S. 12592, total weight of cover and		
	frame to be not less than 182 kg. fixed in cement concrete 1:2:4 (1 cement: 2		
	coarse sand: 4 graded stone aggregate 20 mm nominal size) including centering,		
	shuttering all complete. (Excavation, foot rests and 12 mm thick cement plaster		
233.1.1	at the external surface shall be paid for separately):		
	With common burnt clay F.P.S. (non-modular) bricks of class designation 7.5	Each	1.0
24	Providing and fixing Fiber Glass Reinforced plastic (FRP) Door Frames of		
	cross-section 90 mm x 45 mm having single rebate of 32 mm x 15 mm to receive shutter of 30 mm thickness. The laminate shall be moulded with fire resistant		
	grade unsaturated polyester resin and chopped mat. Door frame laminate shall		
	be 2mm thick and shall be filled with suitable wooden block in all the three legs.		
	The frame shall be covered with fiber glass from all sides. M.S. stay shall be		
	provided at the bottom to steady the frame.	Metre	15.00

24.1	30 mm thick Glass Fibre Reinforced Plastic (FRP) panelled door shutter of required colour and approved brand and manufacture, made with fire - retardant grade unsaturated polyester resin, moulded to 3 mm thick FRP laminate for forming hollow rails and styles, with wooden frame and suitable blocks of seasoned wood inside at required places for fixing of fittings, cast monolithically with 5 mm thick FRP laminate for panels conforming to IS: 14856, including fixing to frames.		
	fixing to frames.	Sqm	1.58
25	Providing and applying plaster of paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete.	sqm	23.52
26	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade :		
26.1	New work (two or more coats) over and including water thinnable priming coat with cement primer	sqm	12.50
27	Finishing walls with Acrylic Smooth exterior paint of required shade:		
27.1	New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/10 sqm)	sqm	15.57
28	Providing and fixing PTMT grating of approved quality and colour.		
28.1	Circular type		
28.2	100 mm nominal dia	Each	1.00
29	Providing and fixing of two way bib cock.	Each	1.00
30	Providing and fixing of Exhaust fan 9" with 1.5 sq mm copper wire and all required fittings.	Each	1.00
31	Providing and fixing of LED ceiling Light 1' x 1' with all fittings (Wiring and		
	Switch etc.)	Each	2.00
32	Providing and fixing of LED T5 Tube light with all fittings.	Each	1.00

Note: - Lowest Contractor (L-1) will be decided on overall lowest rates basis

Sd/-13-01-2022 (Ras Bihari Singh) DIG, GC, CRPF G/NOIDA For and on behalf of the President of India

PROFORMA OF BANK GUARANTEE FOR FURNISHING PERFORMANCE SECURITY DEPOSIT

Banker's common seal

PERFORMANCE STATEMENT

1	Name & location of work		
2	Cost of work		
3	Name of Client		
4	Full address of the firm		
5	Contact no. of the contact person of the		
	Client for whom works was executed		
6	E-mail id of the contact person (Mandatory)		
7	Completion period	Stipulated	
		Actual	
8	Whether the work was left incomplete (reason if any for delay in completion of work) or contract was terminated from either side (give full details)		
9	Any other relevant information		
10	Works completion certificate for last three years		
	be attached		

LIST NO-1

TENDERERS SHOULD FURNISH SPECIFIC ANSWERS TO ALL THE QUESTIONS GIVEN BELOW. TENDERERS MAY PLEASE NOTE THAT IF THE ANSWER SO FURNISHED ARE NOT CLEAR AND / OR ARE EVASIVE, THE TENDER WILL BE LIABLE TO BE IGNORED.

1. Tender No	
2. Name and address of firm/contractor:	
3. What is your permanent Income Tax A/C No.:	
4. Status.	
a) Indicate whether you are Govt. registered or not:	
b) TIN/GST No.:	
5. Please indicate name & full address of your banker in the follow	ving format-
a) Bank Name, Branch and Bank Account No. (Core bank account	t)
b) IFSC Code:	
c) Whether bank branch is NEFT/RTGS enables or not:	
6. State whether your firm with you have been banned by any Govt. /CPWD authority?	
7. Please confirm that you have read all the instructions carefully a complied with accordingly.	and have
Signature of Witness	Signature of Tenderer
(Full Name and address of witness in Block letters)	(Full Name and address of the persons signing in Block letters)
	Whether signing as Proprietor /Partner/ Constituted Attorney/duly authorized by the Company

Questionnaire/Check List (Please fill the answer correctly. Tenders leaving the column and Questionnaire un-answered shall be rejected)

	Whether firm/Contractor is registered for the tendered	
01	work or not	
02	Registration No. and Date	
03	Registration issued by	
04	Registration valid up to	
05	Copy of Registration submitted or not	
06	GST registration No	
	Whether Copy of GST registration certificate submitted	
07	or not with tender	
08	PAN No.	
09	Whether Copy of PAN No submitted or not with tender	
	Whether Copy of replacement Warranty period of new	
10	fittings enclosed or not	
11	Whether EMD enclosed, if yes details of EMD	
12	Whether offer is valid up to 180 days or otherwise.	
	Complete details of Banker with IFSC code, Account	
13	No. Name of Bank, Name of Branch, Bank Code, Swift	
	code etc.	
	Whether past performance Performa submitted Along	
14	with copies of award of contracts or not	
	Whether tender specification / work scope accepted by	
15	the firm/contractor or not	
	Whether all pages of tender have been signed by the	
16	authorized signatory or not and returned with offer of	
	not.	
	Whether all the terms and condition of the Tender	
17	Enquiry including payment terms are acceptable or not	
18	Any other specific condition of the firm/contractor	
	·	•

Signature	
(Name of the firm/Contractor)	
With seal/stamp	

TENDER ACCEPTANCE LETTER (To be given on Company Letter Head)

Date:
To,
Sub: Acceptance of Terms & Conditions of Tender.
Tender Reference No:
Name of Tender / Work: -
Dear Sir, 1. I/ We have downloaded / obtained the tender document(s) for the above mentioned 'Tender/Work' from the web site(s) namely:
as per your advertisement, given in the above mentioned website(s).
2. I / We hereby certify that I / we have read the entire terms and conditions of the tender documents from
Page No to (including all documents like annexure(s), schedule(s), etc .,), which form
part of the contract agreement and I / we shall abide hereby by the terms / conditions / clauses contained
therein.
3. The corrigendum(s) issued from time to time by your department/ organization too have also been taken
into consideration, while submitting this acceptance letter.
4. I / We hereby unconditionally accept the tender conditions of above mentioned tender document(s) /
corrigendum(s) in its totality / entirety.
5. In case any provisions of this tender are found violated, then your department/ organization shall withou
prejudice to any other right or remedy be at liberty to reject this tender/bid including the forfeiture of the
full said earnest money deposit absolutely.

Yours Faithfully,

(Signature of the Bidder, with Official Seal)

Form 68-A

Tender No	
	ress of the Tenderer in addition Contractor's telegraphic Address To post box No. if ed in all
Communication to	this Office
	Telephone No
	Fax No
Dear Sir,	
may specify in the	er to supply the stores detailed in the schedule here to or such portion thereof as you acceptance of tender at the price given in the said schedule and agree to hold this offer be bound by a communication of acceptance within the prescribed time.
contract in the Forr contracts placed be amendments annex quoted in the sched	erstood the instructions to Tenderers in the booklet DGS&D-229 and conditions of m No-68 (Revised) including in the pamphlet entitling conditions of contract governing by the Central Purchases Organization of the Government of India read with the ked herewith and have thoroughly examined the specification drawing and/or pattern lule here to and am/are fully aware of the nature of the stores required and my/our offer strictly in accordance with the requirements.
	Signature of the Tenderer
The following page	es have been added to and form part of this tender
Here paste couponin case where coupons are supplied to contractors on payment	Yours faithfully, (Signature of the Tenderer) Address
(Signature of the W	
Address Dated	
Daleu	

"Appendix-G"

Sl.	Requirement	(Firm should correctly fill	(Indicate page number of tender documents where related information is shown/available, it can be verified
No.		following column.)	columns should be highlighted.
01.	Whether Regd with PWD/PWD		
	Validity of registration		
02	Whether EMD enclosed (Reqd Rs/- should be valid upto 180 Days from the date of opening of tender) Whether Specification. Of work		
	Confirmed or Not		
03	Terms of Work Start and Finish (Our requirement is start within 08 days and finished within 60 days)		
04	Validity of offer (Our requirement is 180 days from the date of opening)		
05	Past performance (attached or not)		
06	Arbitration Clause (agreed or not)		
07	Warranty Clause (agreed or not)		
08	GSTIN NO. (attached or not)		
09	Liquidated damage clause (agreed or not)		
10	Partnership agreement (attached or not)		
11	Name & Add of Bankers.		
12	Whether business dealing banned or not		
13	Whether tender signed properly		
14	Pan Card Details		
15	Tin No. (if available)		

Signature of Tenderer
Date
Name of Tenderer.

PROFORMA FOR EARNEST MONEY DEPOSIT DECLARATION

	/We name of firm have submitted bids forork		
	by submit following declaration in lieu of submitting Earnest Money Deposit.		
(i)	If after the opening of tender, I/We withdraw or modify My/Our bid during the period of validity of tender (including extended validity of tender) specified in the tender documents,		
	Or		
(ii)	If, after the award of work, I/We fail to sign the contract, or to submit total security depos before the dead line defined in the tender documents,		
	I/We shall be suspended/banned for one year and shall not be eligible to bid for CRPF tenders from date if issue of suspension order.		
	Signature of the contractor(s)		

<u>Instructions for Online Bid Submission</u> Instructions to the Bidders to submit the bids online through the Central Public Procurement

Portal for e Procurement at http://eprocure.gov.in/eprocure/app

- 1) Possession of valid Digital Signature Certificate (DSC) and enrolment/registration of the contractors/bidders on the e-procurement/e-tender portal is a prerequisite for e-tendering.
- 2) Bidder should do the enrolment in the e-Procurement site using the "Click here to Enroll" option available on the home page. Portal enrolment is generally free of charge. During enrolment/registration, the bidders should provide the correct/true information including valid email-id. All the correspondence shall be made directly with the contractors/bidders through email-id provided.
- 3) Bidder need to login to the site through their user ID/ password chosen during enrolment/registration.
- 4) Then the Digital Signature Certificate (Class II or Class III Certificates with signing key usage) issued by SIFY/TCS/n-Code/e-Mudra or any Certifying Authority recognized by CCA India on e-Token/Smart Card, should be registered.
- 5) The DSC that is registered only should be used by the bidder and should ensure safety of the same.
- 6) Contractor/Bidder may go through the tenders published on the site and download the required tender documents/schedules for the tenders he/she is interested.
- 7) After downloading / getting the tender document/schedules, the Bidder should go through them carefully and then submit the documents as asked, otherwise bid will be rejected.
- 8) If there are any clarifications, this may be obtained online through the tender site, or through the contact details. Bidder should take into account the corrigendum published before submitting the bids online.
- 9) Bidder then logs in to the site through the secured log in by giving the user id/ password chosen during enrolment/registration and then by giving the password of the e-Token/Smart Card to access DSC.
- 10) Bidder selects the tender which he/she is interested in by using the search option & then moves it to the 'my tenders' folder.
- 11) From my tender folder, he selects the tender to view all the details indicated.
- 12) It is construed that the bidder has read all the terms and conditions before submitting their offer. Bidder should go through the tender schedules carefully and upload the documents as asked; otherwise, their bid will be rejected.
- 13) Bidder, in advance, should get ready the bid documents to be submitted as indicated in the tender document/schedule and generally, they can be in PDF/xls/rar/zip/dwf formats. If there is more than one document, they can be clubbed together and can be provided in the requested format. Each document to be uploaded through online for the tenders should be less than 2 MB. If any document is more than 2MB, it can be reduced through zip/rar and the same can be uploaded, if permitted. Bidders Bid documents may be scanned with 100 dpi with black and white option. However, if the file size is less than 1 MB the transaction uploading time will be very fast.
- 14) If there are any clarifications, this may be obtained through the site, or during the pre-bid meeting if any. Bidder should take into account the corrigendum published from time to time before submitting the online bids.
- 15) The Bidders can update well in advance, the documents such as certificates, annual report details etc., under My Space option and these can be selected as per tender requirements and then send along with bid documents during bid submission. This will facilitate the bid submission process faster by reducing upload time of bids.
- 16) Bidder should submit the Tender Fee/ EMD as specified in the tender. The original should be posted/couriered/given in person to the Tender Inviting Authority, within the bid submission due date & time for the tender. Scanned copy of the instrument should be uploaded as part of the offer.
- 17) While submitting the bids online, the bidder reads the terms & conditions and accepts the same to proceed further to submit the bid packets.

- 18) The bidder has to select the payment option as offline to pay the Tender Fee/ EMD as applicable and enter details of the instruments.
- 19) The details of the DD/any other accepted instrument, physically sent, should tally with the details available in the scanned copy and the data entered during bid submission time. Otherwise submitted bid will not be acceptable.
- 20) The bidder has to digitally sign and upload the required bid documents one by one as indicated. Bidders to note that the very act of using DSC for downloading the bids and uploading their offers shall be deemed to be a confirmation that they have read all sections and pages of the bid document including General conditions of contract without any exception and have understood the entire document and are clear about the requirements of the tender requirements.
- 21) The bidder has to upload the relevant files required as indicated in the cover content. In case of any irrelevant files, the bid will be rejected.
- 22) If the price bid format is provided in a spread sheet file like BoQ_xxxx.xls, the rates offered should be entered in the allotted space only and uploaded after filling the relevant columns. The Price Bid/BOQ template must not be modified/replaced by the bidder, else the bid submitted is liable to be rejected for this tender.
- 23) he bidders are requested to submit the bids through online e-tendering system to the Tender Inviting Authority(TIA) well before the bid submission end date & time (as per Server System Clock). The TIA will not be held responsible for any sort of delay or the difficulties faced during the submission of bids online by the bidders at the eleventh hour.
- 24) After the bid submission (ie after Clicking "Freeze Bid Submission" in the portal), the acknowledgement number, given by the system should be printed by the bidder and kept as a record of evidence for online submission of bid for the particular tender and will also act as an entry pass to participate in the bid opening date.
- 25) The time settings fixed in the server side & displayed at the top of the tender site, will be valid for all actions of requesting, bid submission, bid opening etc., in the e-tender system. The bidders should follow this time during bid submission.
- 26) All the data being entered by the bidders would be encrypted using PKI encryption techniques to ensure the secrecy of the data. The data entered will not viewable by unauthorized persons during bid submission & not be viewable by any one until the time of bid opening.
- 27) Any bid document that is uploaded to the server is subjected to symmetric encryption using a system generated symmetric key. Further this key is subjected to asymmetric encryption using buyers/bid openers public keys. Overall, the uploaded tender documents become readable only after the tender opening by the authorized bid openers.
- 28) The confidentiality of the bids is maintained since the secured Socket Layer 128-bit encryption technology is used. Data storage encryption of sensitive fields is done.
- 29) The bidder should logout of the tendering system using the normal logout option available at the top right-hand corner and not by selecting the (X) exit option in the browser.
- 30) For any queries regarding e-tendering process, the bidders are requested to contact as provided in the tender document. For any further queries, the bidders are asked to contact over phone: **0120-2352900** or send a mail over to gcnda@crpf.gov.in.

Signature of the tenderer