

OFFICE OF THE DEPUTY INSPECTOR GENERAL OF POLICE, GROUP CENTRE, CRPF, JAMMU (J&K)- PIN- 181123. Contact No. of the tender inviting authority :- 0191-2592071

Tender Notice No. **B.V-04/2022-23-GC-BLDG**

Dated The

14 May' 2022

E-TENDER NOTICE

Deputy Inspector General of Police, GC, CRPF, Jammu J&K for and on behalf of the President of India invites online tenders **under two bid system (Technical and Commercial bid)** from registered firms/contractors **for Repair and Renovation of 03 Nos VVIP Security post size-6'x6'x9' at GC CRPF Jammu.**

2. Bids will be accepted online at e-Procurement website <http://eprocure.gov.in/eprocure/app> (CPPP).

3. All relevant details, including specification, terms & conditions etc., are available on CRPF website (<http://crpf.nic.in/tender-notice.htm>) and at e-Procurement website <http://eprocure.gov.in/eprocure/app> (CPPP) and same may be downloaded by the bidders.

4. For any changes/amendment in Tender Enquiry/Specifications etc., tenderers are requested to visit the CRPF /CPPP web sites regularly.

5. The EMD is: Rs. **20,000/-**

6. Date of availability of tender on CRPF website: 18/08/2022

7. In case of any problem please contact on telephone numbers 0191-2592071

Sd-14/05/2022

(Bhanu Pratap Singh)

DIGP, GC, CRPF, Jammu

For and on behalf of President of India

OFFICE OF THE DEPUTY INSPECTOR GENERAL OF POLICE, GROUP CENTRE, CRPF, JAMMU (J&K)- PIN- 181123.

Tender Notice No. B.V-04/2022-23-GC-BLDG

Dated the 14 May'2022

//TENDER //

Sealed tenders are invited from registered firms/contractors for Estimate for Repair and Renovation of 03 Nos VVIP Security post size-6'x6'x9' at GC CRPF Jammu as per details given below.

SCOPE OF WORK				
S.N	Details of Work	A/U	Qty.	Earnest Money
1	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m.			Rs. 20,000/- (Twenty Thousand) Only
1.1	All kinds of soil.	CUM	5.62	
2	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level :			
2.1	1:4:8 (1 Cement : 4 coarse sand (zone-III) : 8 graded stone aggregate 40 mm nominal size)	CUM	0.62	
3	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in:			
3.1	Cement mortar 1:6 (1 cement : 6 coarse sand)	CUM	10.10	
4	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in :			
4.1	Cement mortar 1:6 (1 cement : 6 coarse sand)	CUM	2.89	
5	Providing and laying damp-proof course 50mm thick with cement concrete 1:2:4 (1 cement : 2 coarse sand(zone-III) : 4 graded stone aggregate 20mm nominal size).	Sqm	2.08	
6	12 mm cement plaster of mix :			
6.1	1:6 (1 cement: 6 coarse sand)	Sqm	11.88	
7	15 mm cement plaster on rough side of single or half brick wall of mix:			
7.1	1:4 (1 cement: 4 coarse sand)	Sqm	24.00	
8	Supplying and filling in plinth with sand under floors, including watering, ramming, consolidating and dressing complete.	CUM	0.97	
9	62 mm thick cement concrete flooring with concrete hardener topping, under layer 50 mm thick cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size) and top layer 12mm thick cement hardener consisting of mix 1:2 (1 cement hardener mix : 2 graded stone aggregate, 6mm nominal size) by volume, hardening compound mixed @ 2 litre per 50 kg of cement or as per manufacture's specifications. This includes cost of cement slurry, but excluding the cost of nosing of steps etc. complete.	Sqm	0.19	
10	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete.			
10.1	Size of Tile 600x600 mm	Sqm	1.93	
11	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by	Sqm	6.67	

	Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.			
12	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	Kg	120	
13	Providing and fixing pre-coated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	Sqm	4.84	
14	Providing and fixing pre-coated galvanised steel sheet roofing accessories 0.50 mm (+0.05 %) total coated thickness, Zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws complete			
14.1	Ridges plain (500 - 600mm)	Metre	4.8	
15	Providing and fixing false ceiling at all height including providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25 mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound , jointing tapes , finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of the Engineer in Charge but excluding the cost of painting with :			
15.1	Fully Perforated Gypsum Plaster Board of size 1200 x 2400x12.5 mm having approx. 15 % perforated area with perforation size and pattern as approved by the Engineer-in-charge and as per manufacturer's specification, with all 4 side tapered and backed	Sqm	1.93	

	by acoustical tissue with NRC value not less than 0.60 sqm			
16	Designing, fabricating, testing, installing and fixing in position Curtain Wall with Aluminium Composite Panel Cladding, with open grooves for linear as well as curvilinear portions of the building , for all heights and all levels etc. including:			
16.1	(a) Structural analysis & design and preparation of shop drawings for pressure equalization or rain screen principle as required, proper drainage of water to make it watertight including checking of all the structural and functional design			
16.2	(b) Providing, fabricating and supplying and fixing panels of aluminum composite panel cladding in pan shape in metallic colour of approved shades made out of 4mm thick aluminum composite panel material consisting of 3mm thick FR grade mineral core sandwiched between two Aluminium sheets (each 0.5mm thick). The aluminum composite panel cladding sheet shall be coil coated, with Kynar 500 based PVDF / Lumiflon based fluoropolymer resin coating of approved colour and shade on face # 1 and polymer (Service) coating on face # 2 as specified using stainless steel screws, nuts, bolts, washers, cleats, weather silicone sealant, backer rods etc.			
16.3	(c) The fastening brackets of Aluminium alloy 6005 T5 / MS with Hot Dip Galvanized with serrations and serrated washers to arrest the wind load movement, fasteners, SS 316 Pins and anchor bolts of approved make in SS 316, Nylon separators to prevent bi-metallic contacts all complete required to perform as per specification and drawing The item includes cost of all material & labour component, the cost of all mock ups at site, cost of all samples of the individual components for testing in an approved laboratory, field tests on the assembled working curtain wall with aluminum composite panel cladding, cleaning and protection of the curtain wall with aluminum composite panel cladding till the handing over of the building for occupation. Base frame work for ACP cladding is payable under the relevant aluminum items The Contractor shall provide curtain wall with aluminum composite panel cladding, having all the performance characteristics all complete , as per the Architectural drawings, as per item description, as specified, as per the approved shop drawings and as directed by the Engineer-in-Charge. However, for the purpose of payment, only the actual area on the external face of the curtain wall with Aluminum Composite Panel Cladding (including width of groove) shall be measured in sqm. up to two decimal places. sqm 4309.80	Sqm	24.48	
17	Renewing glass panes and refixing existing wooden fillets.			
17.1	Float glass panes of nominal thickness 5 mm (Weight not less than 12.5 kg/sqm)	Sqm	4.8	
18	Providing and fixing factory made uPVC door frame made of uPVC extruded sections having an overall dimension as below (tolerance ± 1 mm), with wall thickness 2.0 mm (± 0.2 mm), corners of the door frame to be Jointed with galvanized brackets and stainless steel screws, joints mitred and Plastic welded. The hinge side vertical of the frames reinforced by galvanized M.S. tube of size 19 X 19 mm and 1mm (± 0.1 mm) wall thickness and 3 nos. stainless steel hinges fixed to the frame complete as per manufacturer's specification and direction of Engineer in- charge			
18.1	Extruded section profile size 42x50 mm metre 267.45	Metre	12.60	
19	Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface :			
19.1	Water thinnable cement primer.	Sqm	11.2	
20	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	Sqm	11.2	
21	Distempering with 1st quality acrylic distemper (ready mixed) having VOC content less than 50 gms/litre, of approved manufacturer, of required shade and colour complete, as per			

	manufacturer's specification.			
21.1	Two or more coats on new work	Sqm	11.2	
23	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with piano type switch, phenolic laminated sheet, suitable size MS box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required			
23.1	Group C	Points	3.00	
24	Wiring for light/ power plug with 2X4 sq. mm FRLS PVC insulated copper conductor single core cable in surface/ recessed medium class PVC conduit alongwith 1 No. 4 sq. mm FRLS PVC insulated copper conductor single core cable for loop earthing as required	Mtrs	20.00	
25	Supplying and fixing DP sheet steel enclosure on surface/ recess along with 25/32 A 240 V "C" curve DP MCB complete with connections, testing and commissioning etc. as required.	each	1.00	
26	Supplying and fixing following way, horizontal type three pole and neutral, sheet steel, MCB distribution board, 415 V, on surface/ recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator)			
26.1	8 way (4 + 24), Double door	each	1.00	

(A) SCHEDULE TO TENDER

Schedule to Tender No.	:	B.V-04/2022-23-GC-BLDG.
Last date and time of receipt of on-line & Manual documents of tender	:	07/09/2022 at 1600 hrs
Time and date of on-line opening e-tender	:	08/09/2022 at 1600 hrs
Validity of offer	:	The tender shall remain open for acceptance till 180 days from the date of opening of Tender.

Sl. No.	Ref. No.	Name of work & Location	Earnest Money	Estimated cost	Period of Completion	Last date & time of Submission of tender	Time & date of opening of tender
01	B.V-04/2022-23-GC-BLDG	Repair and Renovation of 03 Nos VVIP Security post size-6'x6'x9' at GC CRPF Jammu	3Rs. 20,000/-	Rs. 9,40,674/-	Within 30 days from the date of award of contract	07/09/2022 at 1600 hrs	08/09/2022 at 1600 hrs

B. Terms and conditions are as under:

1. Terms of Price	<p>1.1 Rates quoted by the Contractor should be in Indian Rupees both in figures as well as in words for complete units as per specifications any and every alteration in the rates should be signed in ink otherwise the offers will not be considered.</p> <p>1.2 Contractor should clearly indicate different taxes and duties, which they propose to charge as extra along with the present rates thereof. Offers with such stipulations like 'as applicable' will be treated as vague and are liable to be ignored.</p>
2. Payment terms	<p>2.1 Works are required to be executed on credit basis only and payment will be made after drawl of amount from RPAO, CRPF, Jammu</p> <p>2.2 Payment in advance or immediately cannot be made.</p> <p>2.3 The Payment action will be processed on production of the following documents :-</p> <p>a) Bill in Triplicate.</p> <p>b) A Copy of award of work.</p> <p>c) A copy of Certificate issued by the DIG-cum-Estate Officer GC, CRPF, Jammu (J&K)/Work Committee of GC, CRPF, Jammu that contracted work for the period for which payment has been claimed, has carried out by the contractor satisfactory.</p> <p>2.4 TDS , Labour Cess and other taxes will be deducted from the Bill of Contractor by RPAO as per norms.</p> <p>2.5 Tenderers are requested to check physically the location where the work for repair of wall in GO'S Mess at GC Jammu is to be carried out and other technical details before submitting the tender. TEC detailed by the DIGP will check technical bid of work for repair of wall in GO'S Mess at GC Jammu and price bid will opened of only those firms which qualify in technical bid.</p>
Tender Fee	If required.

3. Earnest Money Deposit	<p>3.1 All the contractors are required to deposit required earnest money 2% along with the quotation, failing which their offers will be summarily rejected.</p> <p>3.2 The earnest money can be deposited through any of the following alternative forms: (a) A TDR/FDR drawn in favour of DIGP, GC, CRPF, Jammu,(J&K) payable at SBI Bank code 10347, SBI Bantalab, Jammu (J&K) (b) An irrevocable Bank Guarantee of any nationalized, scheduled bank or reputed commercial bank in the attached format as at Appendix-A.</p> <p>3.3 The earnest money shall remain valid and to be deposited with the purchaser for a period of 180 days from the date of tender opening. If the validity of the tender is extended, the validity of the Bank Guarantee/or any other alternate document submitted in lieu of earnest money will also be suitably extended by the tenderer, failing which their tender after the expiry of the aforesaid period shall not be considered by the purchaser.</p> <p>3.4 No interest shall be payable on the earnest money deposited by the tenderer.</p> <p>3.5 The earnest money deposited is liable to be forfeited if the tenderer withdrawn or amends impairs or derogates from the tender in any respect within the period of validity of his tender.</p> <p>3.6 The earnest money of the successful tenderer shall be returned after the security deposit as required in terms of the contract is furnished by the tenderer.</p> <p>3.7 If the successful tenderer fails to furnish the security deposit as required in the contract within the stipulated period, the earnest money shall be treated as performance security deposit for all practical purposes.</p> <p>3.8. Earnest money deposits of all the unsuccessful tenderers will be returned as early as possible after the expiry of bid's validity, but not later than 30 days after placement of contract. Tenderers are advised to send a pre receipt challan affix with revenue stamp and cross signature of the firm along with their bids so that refund of earnest money can be made in time.</p> <p>3.9. Any tender, where the tenderer is required to deposit earnest money in terms of conditions mentioned in preceding paras, not accompanied with earnest money in any one of the approved forms acceptable to the competent authority, shall be summarily rejected.</p>
4. Performance Security Deposit	<p>4.1. The successful contractor shall have to deposit a Performance Security equivalent to 5 % of the contract value of the work to be executed within 07 days from the date of award of contract for due performance. Failure on the part of the firm to Deposit the Performance Security Deposit within the stipulated time empowers the competent authority to cancel the contract.</p> <p>4.2. The Performance Security Deposit submitted by the bidder will remain valid at least for 180 days beyond the date of completion of work as well as all contractual obligations of the supplier including guarantee/warranty obligations.</p> <p>4.3. The performance security deposit can be deposited in any of the following alternative forms :</p> <p>(a) A TDR/FDR drawn in favour of DIGP, GC, CRPF, Jammu,(J&K) payable at SBI Bank code 10347, SBI Bantalab, Jammu (J&K) (b) An irrevocable Bank Guarantee of any nationalized/Scheduled Bank or reputed commercial bank in any other form prescribed.</p> <p>4.4. If the contractor fails to start the work within the stipulated period and places and</p>

	<p>requests for extension of time, he shall submit an undertaking on Non Judicial stamp paper of Rs.10/- duly attested by the Notary public stating that the performance security deposit has already been extended for sixty days beyond the guarantee/warranty period.</p> <p>4.5 The Performance Security Deposit shall be withheld or forfeited in full or part in case the work order is not executed satisfactorily within the stipulated period or requisite standard within the guarantee period is not undertaken to the best satisfaction of the user.</p>																											
<p>5. Eligibility of Contractor</p>	<p>The Tenderer should be a Govt. registered like CPWD, MES, BRO, NBCC, State PWD participating</p> <ol style="list-style-type: none"> 1. The enlistment of the contractor should be valid on the last date of submission of Bids. 2. In case the last date of submission of Bid is extended, the enlistment of the contractor should be valid on the original date of submission of Bids. 3. Supply order as a experience certificate will not be considered, in the case of execution of work/repair and renovation work. 4. Attested copy of registration in any Govt. depts. As approved contractor (Registration details showing appropriate class and category) 5. Enlisted CPWD contractors above Class I composite category are allowed to participate up to their tendering limits without submitting eligibility documents. Firms and contractor, not registered with CPWD are required to submit eligibility documents of executing similar works. <ol style="list-style-type: none"> (i) Experience of having successfully completed works during the last 7 years ending previous day of last date of submission of tenders Three similar completed works, each costing not less than the amount equal to 40% of estimated cost put to tender. <p style="text-align: center;">OR</p> Two similar completed works, each costing not less than the amount equal to 60% of the estimated cost put to tender. <p style="text-align: center;">OR</p> One similar completed work of aggregate cost not less than the amount equal to 80% of the estimated cost. 																											
<p>6. Two Bid System</p>	<p>6.1 Since the work to be undertaken is of a complex and technical nature, bids are required to be submitted in two parts as under :-</p> <p>6.2 Bids will be accepted only online at e-procurement web site http://eprocure.gov.in/eprocure/app (CPPP).</p> <p>6.3 Technical bid :- Following documents and information to be fulfilled and submitted as part of technical bid :-Original offline to be dropped in the tender box in a sealed envelope :-</p> <p>Note :- Tenders are requested to submit all the tender documents offline and Online.</p> <table border="1" data-bbox="350 1444 1468 2007"> <thead> <tr> <th>S.No.</th> <th>Name of documents</th> <th>Description of documents</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Tender Acceptance Letter (To be given on company Letter Head)</td> <td>APPENDIX-"F" duly signed by bidder & witness.</td> </tr> <tr> <td>2</td> <td>EMD document to be deposited in original</td> <td>APPENDIX-"A"</td> </tr> <tr> <td>3</td> <td>Tender Notice</td> <td>All pages of tender notice and documents duly signed by authorized person and seal of the firm marked.</td> </tr> <tr> <td>4</td> <td>CPWD, MES, BRO, NBCC, PWD Registration Certificate.</td> <td></td> </tr> <tr> <td>5</td> <td>PAN/TAN Card details</td> <td></td> </tr> <tr> <td>6</td> <td>Bank guarantee for furnishing performance security deposit</td> <td>APPENDIX-"B"</td> </tr> <tr> <td>7</td> <td>Performance statement of works with completion certificate last three years is also enclosed.</td> <td>APPENDIX-"C"</td> </tr> <tr> <td>8</td> <td>List No.1</td> <td>APPENDIX-"D"</td> </tr> </tbody> </table>	S.No.	Name of documents	Description of documents	1	Tender Acceptance Letter (To be given on company Letter Head)	APPENDIX-"F" duly signed by bidder & witness.	2	EMD document to be deposited in original	APPENDIX-"A"	3	Tender Notice	All pages of tender notice and documents duly signed by authorized person and seal of the firm marked.	4	CPWD, MES, BRO, NBCC, PWD Registration Certificate.		5	PAN/TAN Card details		6	Bank guarantee for furnishing performance security deposit	APPENDIX-"B"	7	Performance statement of works with completion certificate last three years is also enclosed.	APPENDIX-"C"	8	List No.1	APPENDIX-"D"
S.No.	Name of documents	Description of documents																										
1	Tender Acceptance Letter (To be given on company Letter Head)	APPENDIX-"F" duly signed by bidder & witness.																										
2	EMD document to be deposited in original	APPENDIX-"A"																										
3	Tender Notice	All pages of tender notice and documents duly signed by authorized person and seal of the firm marked.																										
4	CPWD, MES, BRO, NBCC, PWD Registration Certificate.																											
5	PAN/TAN Card details																											
6	Bank guarantee for furnishing performance security deposit	APPENDIX-"B"																										
7	Performance statement of works with completion certificate last three years is also enclosed.	APPENDIX-"C"																										
8	List No.1	APPENDIX-"D"																										

9	Questionnaires/Check list (Must be filled in all respect)	APPENDIX-“E”
10	Form 68-A	APPENDIX-“G”
11	Index of Documents (Indicate page number of tender documents required)	APPENDIX-“H”
12	Copy of Income Tax Return of last three years	Attached with tender enquiry
13	Any other documents	Attached with tender enquiry
<p>6.4 Financial/Price Bid :- The composite bid shall be quoted as per enclosed BOQ format Provide along with tender document at E-Procurement site http://eprocure.gov.in/eprocure/app (CPPP).</p> <p>6.5 The technical bids are to be opened at the first instance and evaluated by the competent authority. In the second stage, financial bids of only the technically acceptable offers will be opened for further evaluation and ranking before awarding the contract.</p> <p>6.6 The participated firms should not submit financial bid with technical bids while submission of offline tender.</p> <p>6.7 The estimated cost of the work should be mentioned in the tender excluding ESI&EPF and contingency charges.</p> <p>6.8 The tender enquires duly filled in all respect and having completed in all applicable formalities may be sent to DIG-cum-Estate Officer GC, CRPF Bantalab Jammu, Campus so as to reach on or before 07/09/2022 at 1600 Hrs to the tender enquiry. Department is not responsible for any postal delay as well as technical problem at portal/site.</p>		

7. WORK SPECIFICATION

The work shall be carried out according to C.P.W.D. Specifications 2016 Vol-I & II including up to date correction slips and as per additional conditions.

8. SITE VISIT AND COLLECTING LOCAL INFORMATION

Before tendering, the tenderer is advised to visit the site, its surroundings to assess and satisfy themselves about the local conditions such as the working and other constraints at site, approach roads to the site, availability of water & power supply, application of taxes, duties and levies as applicable, accommodations they may require etc & any other relevant information required by them to execute complete scope of work. The tenderer may obtain all necessary information as to risks, weather conditions, contingencies & other circumstances (insurgencies etc.) which may influence or affect their tender prices. Tenderer shall be deemed to have considered site conditions whether he has inspected it or not and to have satisfied himself in all respect before quoting his rates and no claim or extra charges whatsoever in this regard shall be entertained / payable by the **GC CRPF, Bantalab, Jammu Campus- (J&K)** at a later date.

9. VALIDITY OF TENDER

The tender for the works shall remain open for acceptance for a period of **180** days from the date of opening of Price Bid of tenders. The earnest money will be forfeited without any prejudice to any right or remedy, in case the contractor withdraws his tender during the validity period or in case he changes his offer to his benefits which are not acceptable to **GC CRPF, Jammu**. The validity period may be extended on mutual consent.

10. REJECT/CANCEL/SCRAP

The Competent Authority has got the right to accept or reject/cancel/scrap the tender as whole or part of it and no claims what so ever will be entertained on this account. The competent authority also reserves the right to increase/decrease/alter the scope of work/ quantity of work etc., and no claims what so ever will be entertained.

11. TERMINATION OF CONTRACT ON DEATH OF CONTRACTOR

Without prejudice to any of the right or remedies under this contract if the contractor dies, the DIG-cum-Estate Officer GC, CRPF, Jammu (J&K) shall have the option of terminating the contract without compensation to the contractor. If the contractor is an individual or proprietary concern and individual or the proprietor dies or if the contractor is a partnership concern and one of the partner dies then unless, the DIG-cum-Estate Officer GC, CRPF, Jammu (J&K) is satisfied that the legal representative of the individual for the proprietary concern or the surviving partners are capable of carrying out and completing contract, he (DIG-cum-Estate Officer GC, CRPF, Jammu) is entitled to cancel the contract for the uncompleted part without being in any way liable for any compensation payment to the estate of deceased contractor or to the surviving partners of the contractor's firm on account of the cancellation of contract. The decision of the DIG-cum-Estate Officer GC, CRPF, Jammu (J&K) in such assessment shall be final and binding on the parties. In the event of such cancellation the DIG-cum-Estate Officer GC, CRPF, Jammu (J&K) shall not hold the state of deceased contractor and/or the surviving partners of the contractor's firm liable for any damages for non-completion of contract.

12. DIRECTION FOR WORKS

All works to be executed under the contract shall be executed Under the direction and subject to approval in all respect of the DIG-cum-Estate Officer GC, CRPF, Jammu/Work Committee /Officer commanding of Building /Engineer-in-Charge of DIG-cum-Estate Officer GC, CRPF, Jammu (J&K) who shall be entitled to direct at what point or points and in what manner works are to be commenced and executed.

13. DEFECT LIABILITY PERIOD

i) **12 Months** from the date of Completion as certified by the DIG-cum-Estate Officer GC, CRPF, Jammu (J&K) /Officer commanding of Building Branch / Work Committee.

ii) The contractor shall stand guarantee for materials and workmanship. During the defect liability period, if any defect is observed due to workmanship or from any act or omission of the contractor, the contractor shall execute all such work of rectification and making good of defects, as may be required of him by competent authority at his own cost and within the time stipulated by competent authority. If the contractor shall fail to do any such work as required by the competent authority, Security/Retention money shall be liable to be forfeited and the contractor shall make him liable to be blacklisted.

14. SECURITY DEPOSIT/ RETENTION MONEY

The security deposit @ 2% of the gross amount of the bill shall be deducted from final bill of the contractor. The contractor can also deposit the security deposit through **FDR @ 2%** of the tendered amount in favour of DIGP, GC, CRPF, Jammu,(J&K) payable at SBI Bank code 10347, SBI Jammu (J&K) before submitting the final bill for payment action . The security deposit or retention money shall be refunded to the contractor after **expiry of defects liability period** (referred to Clause **No.13**) or on payment of the amount of the final bill whichever is later. This is in addition to Performance Guarantee that the contractor is required to deposit.

15. Before starting the work the contractor shall chalk out a programme, in consultation with the DIG-cum-Estate Officer GC, CRPF, Jammu (J&K) or his authorized representative at least one week in advance. The contractor shall have to adhere to this programme failing which he shall be held responsible for any inconvenience caused to the occupants. In order to ensure

that the work is carried out according to the program me drawn, the contractor shall ensure adequate supply of the material and employ required labour strength for execution of work. The contractor shall put his authorized representatives daily at the site of work /Enquiry Office for receiving instructions from DIG-cum-Estate Officer GC, CRPF, Jammu (J&K) and other inspecting officials from the department. His name and signature shall be attested by the contractor and kept on the record with the department.

16. Payment shall be made to contractor only after giving certificate about satisfactory completion of work. All measurement shall be recorded on standard measurement sheets which will be submitted to the DIG-cum-Estate Officer GC, CRPF, Jammu (J&K) for scrutiny and passing.

17 DIG-cum-Estate Officer GC, CRPF, Jammu / Works committee/ Officer commanding of Building/ Engineer-in-charge shall scrutinize and check the measurement records practically/on ground based on the measurement sheet provided by contractor and final measurement sheet will be prepared by Engineer-in-charge of this office.

18 While the tenderer and the purchaser shall make ever effort to resolve any issue amicably through direct informal negotiation, in the event of any disagreement or dispute arising between them under or in connection with the contract shall be settled under court of law within its jurisdiction at state under. The resultant contract will be interpreted as per the prevailing Indian laws and various directions of the Govt. of India.

Dispute in mode of measurement: In case of dispute as to the mode of measurement not covered by the contract to be adopted for any item of work, mode of measurement as per latest Indian specification shall be followed.

19. Intending tenderer is eligible to submit the bid provided he has definite proof from the appropriate authority, which shall be to the satisfaction of the competent authority, of having satisfactorily completed similar works of magnitude specified.

20. The time allowed for carrying out the work will be within 30 days from the date of work order.

21. The site for the work is available or the site for the work shall be made available in parts as specified above.

22. The contractor shall not be permitted to tender for works in the CRPF in which his near relative of CRPF is involved. If so, he shall also intimate the names of persons who are working with him in any capacity or are subsequently employed by him and who are near relatives to any CRPF officer/personnel.

23. Department will not be responsible for any kind of incident involving the labour during or after the work. The contractor must insure the workers against all contingencies and be responsible for their safety.

24. GST No. or/and Service Tax No. and Contractor's Regn. No. must be printed on the bill which is submitted for recoument/payment action.

25. The tender for the works shall remain open for acceptance for a period of **180 Days** from the date of opening of tenders. If any tenderer withdraws his tender before the said period or issue of letter of acceptance, whichever is earlier, or makes any modifications in the terms and conditions of the tender which are not acceptable to the department and then the Government shall, without prejudice to any other right or remedy, be at liberty to forfeit the earnest money as aforesaid. Further the tenderer shall not be allowed to participate in the retendering process of the work.

26. The contractor shall bear cost **of Liquidated Damage** for Delay in completion of work within the stipulated time @ of **2%** of contracted value not exceeding the 10% of contracted value in whole.

27. This Notice Inviting Tender shall form a part of the contract document.

28. Hard copies as submitted physically in the office of DIG-cum-Estate Officer GC, CRPF, Jammu (J&K), shall be only valid document for evaluation of technical specification. The DIG-cum-Estate Officer GC, CRPF, Jammu (J&K) has all rights to break contract at any time without assigning any reason.

29. The Tenderer are requested to return a copy of this Tender duly signed on each page along with other relevant documents as required with the tender for evaluation purpose. If tenderer fails to return a copy of this Tender duly signed, his offer will not be considered and it will be rejected.

30. The tenderer shall be responsible for arranging and maintaining at his own cost all materials, tools & plants, water, electricity access, facilities for executing work and all other services required for executing the work.

31. The successful tenderer shall make his own arrangement for storage and watch and ward of material whether the same brought by him or supplied by the department. He shall remain responsible for watch and ward of installation and other fittings till these are commissioned and handed over to the department.

32. Successful tenderer should be in a position to produce, after opening of the price bids, the Original Certificates in support of the self-attested copies of relevant documents submitted along with tender document. Failure to produce the original certificates at this stage in support of the attested copies of firm registration /Electrical License/any other documents etc. submitted earlier would result in disqualification and forfeiture of EMD and also liable for debarring from participation in DIG-cum-Estate Officer GC, CRPF, Jammu (J&K) tenders.

33. FINAL INSPECTION: - After completion of work as per specification the whole work will be subject to a final inspection to ensure that job has been completed as per requirement. If any defects noticed in the work are attributable to Contractor, these shall be attended by the Contractor at his own cost, as and when they are brought to his notice by the DIG-cum-Estate Officer GC, CRPF, Jammu (J&K) /Work committee/officer Commanding of Building/Engineer in charge. The DIG-cum-Estate Officer GC, CRPF, Jammu (J&K) and its representative shall have the right to have these defects rectified at the risk and cost of the contractor if he fails to attend to these defects immediately.

34. MEASUREMENTS OF WORK DONE :- Engineer-in-charge shall, except as otherwise provided, ascertain and determine by measurement, the value in accordance with the contractor of work done.

All measurement of all items having financial value shall be entered in measurement book/level field book so that a complete record is obtained of all works performed under the contract.

All measurement and levels shall be taken jointly by the Inst/ SI/civil or his authorized representative and by the contractor or his authorized from time to time during the progress of work and such measurement shall be signed and dated by the Engineer-in-charge and the contractor or their representatives in token of their acceptance. If the contractor objects to any of the measurement recorded, a note shall be made to that effect with reason and signed by both parties.

If for any reason the contractor or his authorized representative is not available and the work of recording measurement is suspended by the Insp/SI/Civil or his representative, the Engineer-in-charge and the Department shall not claim from contractor for any loss or damages on his account. If the contractor or his authorized representative does not remain present at the time of such measurements after the contractor or his authorized representative has been given a notice in writing three (3) days in advance or fails to countersign or to record objection within a week from the date of the measurement, then such measurement recorded in his absence by the Engineer-in-charge or his representative shall be deemed to be accepted by the contractor.

It is also a term of this contract that recording of measurement of any items of work in the measurement book and /or its payment in the interim, on account of final bill shall not be considered as conclusive evidence as to the sufficiency of any work or material to which it relates nor shall relieve the contractor from liabilities from any over measurement or defects noticed till completion of the liability period.

35. Work scope may be changed depending upon the priority of the work.

36. No part of the CONTRACT nor any share or interest therein shall in any manner or degree be transferred, assigned or sublet by the CONTRACTOR directly or indirectly to any person, firm or corporation whatsoever without the consent in writing of the DIG-cum-Estate Officer GC, CRPF, Jammu (J&K)

Sd-14/05/2022

(Bhanu Pratap Singh)

DIGP, GC, CRPF, Jammu

For and on behalf of President of India

A. ADDITIONAL SPECIFICATIONS FOR CIVIL WORKS:

1. All materials required to be used on works shall be got approved from the DIG-cum-Estate Officer GC, CRPF, Jammu (J&K) / Officer Commanding of Building in advance. In case of doubt on any material, DIGP GC-CRPF, Jammu wears the right to get the material test from Govt. approved labs/NABL
2. The quoted rate should be inclusive of all taxes, levies, works contract taxes, duties etc.
3. All items to be used in this work should be branded and ISI. In this case CPWD approved list of material for similar work may be followed.

Sd-14/05/2022
(Bhanu Pratap Singh)
DIGP, GC, CRPF, Jammu
For and on behalf of President of India

B. Details of work :-

Name of Work	Repair and Renovation of 03 Nos VVIP Security post size-6'x6'x9' at GC CRPF Jammu.
Scope of Work	<ol style="list-style-type: none"> 1. Earth work in excavation. 2. Providing and laying in position of cement concrete. 3. Centering and shuttering. 4. 12 mm cement plaster. 5. D.P.C work. 6. Earh filling work. 7. Brick masonry. 8. Putty work. 9. Painting Work.. 10. Cement concrete flooring work. 11. Floor tiles work. 12. ACP sheet work. 13. Complete electrical work.

S.N.	Description of work/items	Unit	Qty.
1	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m.		
1.1	All kinds of soil.	CUM	5.62
2	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level :		
2.1	1:4:8 (1 Cement : 4 coarse sand (zone-III) : 8 graded stone aggregate 40 mm nominal size)	CUM	0.62
3	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in:		
3.1	Cement mortar 1:6 (1 cement : 6 coarse sand)	CUM	10.10
4	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in :		
4.1	Cement mortar 1:6 (1 cement : 6 coarse sand)	CUM	2.89
5	Providing and laying damp-proof course 50mm thick with cement concrete 1:2:4 (1 cement : 2 coarse sand(zone-III) : 4 graded stone aggregate 20mm nominal size).	Sqm	2.08
6	12 mm cement plaster of mix :		
6.1	1:6 (1 cement: 6 coarse sand)	Sqm	11.88
7	15 mm cement plaster on rough side of single or half brick wall of mix:		
7.1	1:4 (1 cement: 4 coarse sand)	Sqm	24.00
8	Supplying and filling in plinth with sand under floors, including watering, ramming, consolidating and dressing complete.	CUM	0.97
9	62 mm thick cement concrete flooring with concrete hardener topping, under layer 50 mm thick cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size) and top layer 12mm thick cement hardener consisting of mix 1:2 (1 cement hardener mix : 2 graded stone aggregate, 6mm nominal size) by volume, hardening compound mixed @ 2 litre per 50 kg of cement or as per manufacture's specifications. This includes cost of cement slurry, but excluding the cost of nosing of steps etc. complete.	Sqm	0.19
10	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete.		
10.1	Size of Tile 600x600 mm	Sqm	1.93
11	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours,	Sqm	6.67

	shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.		
12	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	Kg	120
13	Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineerin-charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	Sqm	4.84
14	Providing and fixing precoated galvanised steel sheet roofing accessories 0.50 mm (+0.05 %) total coated thickness, Zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws complete		
14.1	Ridges plain (500 - 600mm)	Metre	4.8
15	Providing and fixing false ceiling at all height including providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25 mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound , jointing tapes , finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of the Engineer in Charge but excluding the cost of painting with :		
15.1	Fully Perforated Gypsum Plaster Board of size 1200 x 2400x12.5 mm having approx. 15 % perforated area with perforation size and pattern as approved by the Engineerin-charge and as per manufacturer's specification, with all 4 side tapered and backed by acoustical tissue with NRC value not less than 0.60 sqm	Sqm	1.93
16	Designing, fabricating, testing, installing and fixing in position Curtain Wall with Aluminium Composite Panel Cladding, with open grooves for linear as well as curvilinear portions of the building , for all heights and all levels etc. including:		
16.1	(a) Structural analysis & design and preparation of shop drawings for pressure equalisation or rain screen principle as required, proper drainage of water to make it watertight including checking of all the structural and functional design		
16.2	(b) Providing, fabricating and supplying and fixing panels of aluminium composite panel cladding in pan shape in metallic colour of approved shades made out of 4mm thick aluminium composite panel material consisting of 3mm thick FR grade mineral core sandwiched between two Aluminium sheets (each 0.5mm thick). The aluminium composite panel cladding sheet shall be coil coated, with Kynar 500 based PVDF / Lumiflon based fluoropolymer resin coating of approved colour and shade on face # 1 and polymer (Service) coating on face # 2 as specified using stainless steel screws,		

	nuts, bolts, washers, cleats, weather silicone sealant, backer rods etc.		
16.3	(c) The fastening brackets of Aluminium alloy 6005 T5 / MS with Hot Dip Galvanised with serrations and serrated washers to arrest the wind load movement, fasteners, SS 316 Pins and anchor bolts of approved make in SS 316, Nylon separators to prevent bi-metallic contacts all complete required to perform as per specification and drawing The item includes cost of all material & labour component, the cost of all mock ups at site, cost of all samples of the individual components for testing in an approved laboratory, field tests on the assembled working curtain wall with aluminium composite panel cladding, cleaning and protection of the curtain wall with aluminium composite panel cladding till the handing over of the building for occupation. Base frame work for ACP cladding is payable under the relevant aluminium item.s The Contractor shall provide curtain wall with aluminium composite panel cladding, having all the performance characteristics all complete , as per the Architectural drawings, as per item description, as specified, as per the approved shop drawings and as directed by the Engineer-in-Charge. However, for the purpose of payment, only the actual area on the external face of the curtain wall with Aluminium Composite Panel Cladding (including width of groove) shall be measured in sqm. up to two decimal places. sqm 4309.80	Sqm	24.48
17	Renewing glass panes and refixing existing wooden fillets.		
17.1	Float glass panes of nominal thickness 5 mm (Weight not less than 12.5 kg/sqm)	Sqm	4.8
18	Providing and fixing factory made uPVC door frame made of uPVC extruded sections having an overall dimension as below (tolerance ± 1 mm), with wall thickness 2.0 mm (± 0.2 mm), corners of the door frame to be Jointed with galvanized brackets and stainless steel screws, joints mitred and Plastic welded. The hinge side vertical of the frames reinforced by galvanized M.S. tube of size 19 X 19 mm and 1mm (± 0.1 mm) wall thickness and 3 nos. stainless steel hinges fixed to the frame complete as per manufacturer's specification and direction of Engineerin- charge		
18.1	Extruded section profile size 42x50 mm metre 267.45	Metre	12.60
19	Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface :		
19.1	Water thinnable cement primer.	Sqm	11.2
20	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	Sqm	11.2
21	Distempering with 1st quality acrylic distemper (ready mixed) having VOC content less than 50 gms/litre, of approved manufacturer, of required shade and colour complete, as per manufacturer's specification.		
21.1	Two or more coats on new work	Sqm	11.2
23	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with piano type switch, phenolic laminated sheet, suitable size MS box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required		
23.1	Group C	Points	3.00
24	Wiring for light/ power plug with 2X4 sq. mm FRLS PVC insulated copper conductor single core cable in surface/ recessed medium class PVC conduit alongwith 1 No. 4 sq. mm FRLS PVC insulated copper conductor single core cable for loop earthing as required	Mtrs	20.00
25	Supplying and fixing DP sheet steel enclosure on surface/ recess along with 25/32 A 240 V "C" curve DP MCB complete with connections, testing and commissioning etc. as required.	each	1.00
26	Supplying and fixing following way, horizontal type three pole and neutral, sheet steel, MCB distribution board, 415 V, on surface/ recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator)		
26.1	8 way (4 + 24), Double door	each	1.00

Note: - Lowest Contractor (L-1) will be decided on overall lowest rates basis

PROFORMA OF BANK GUARANTEE FOR SUBMITTING EARNEST MONEY

(On banks letter head with adhesive stamp)

To

The Deputy Inspector General of Police,
Group Centre, C.R.P.F., Jammu (J&K)

Dear Sir,

In accordance with your invitation to Tender No-----

M/s. _____ (here in after called "The tenderer")

With the following Directors on their Board of Directors/Partners of the firm.

- 1. _____ 2. _____
- 3. _____ 4. _____

Wish to participate in the said tender enquiry for the supply/work of (Repair and Renovation of 03 Nos VVIP Security post size-6'x6'x9' at GC CRPF Jammu) to you (here in after called "The purchaser"). Whereas a bank guarantee against Earnest Money for a sum of Rs. _____ (in words) _____ - _____ Valid for 180 days from the date of tender opening viz. up to _____ is required to be submitted by "the tenderer" as a precondition for the participation, this bank hereby guarantees and undertakes to pay the purchaser up to the above amount upon receipt of its first written demand, without the purchaser/contractor having to substantiate its demand, provided that in its demand the purchaser/contractor will note that the amount claimed by it is due to it owing to the occurrence of any one of the three conditions mentioned below, specifying the occurred condition or conditions during the above said period of 180 days without any reservation and recourse.

- 1. If the tenderer withdraws or amends, impairs or derogates from the tender in any respect within the period of its validity.
- 2. If the tenderer after submitting his tender, modifies the rates or any of the terms and conditions thereof, except with the previous written consent of the purchaser.
- 3. If the tenderer having been notified of the acceptance of this tender by the purchaser during the period its validity and
 - (a) If the tenderer fails to furnish the performance security for the due performance of the contract.
 - (b) If the tenderer fails or refuses to accept and or execute the contract as provided in the general conditions of the contract.

The guarantee shall be irrevocable and shall remain valid up to **180** days from the date of opening of tender. If further extension to this guarantee is required, the same shall be extended to such period on receiving instructions from the tenderer on whose behalf this guarantee is issued and any demand in respect thereof should reach the Bank not later than the above date.

Date. _____

Signature of authorized officer of the bank _____

Place _____

Printed Name. _____

Designation _____

Name and address of the bank _____

Banker's Common Seal

PROFORMA OF BANK GUARANTEE FOR FURNISHING PERFORMANCE SECURITY DEPOSIT

To

The President of India,

WHEREAS M/S-----
(Name and address of the supplier) (hereinafter called “the supplier”) has undertaken, in pursuance of contract no.....dated..... to supply (Repair and Renovation of 03 Nos VVIP Security post size-6’x6’x9’ at GC CRPF Jammu) (Hereinafter called “the contract”)

And whereas it has been stipulated by you in the said contract that the supplier shall furnish you with a bank guarantee by a nationalized or scheduled commercial bank of good repute and record recognized by you for the sum specified therein as security for compliance with its obligations in accordance with the contract:

And whereas we have agreed to give the contractor such a bank guarantee:

Now therefore we hereby affirm that we are the guarantors and responsible to you, on behalf of the supplier/contractor, up to a total of
(amount of the guarantee in words and figures), and we undertake to pay you, upon your first written demand declaring the supplier to be in default under the contract and without cavil or argument, any sum or sums within the limits of (amount of guarantee) as aforesaid, without your needing to prove or to show grounds or reasons for your demand or the sum specified therein.

We hereby waive the necessity of your demanding the said debt from the supplier before presenting us with the demand.

We further agree that no change or addition to or other modification of the terms of the contract to be performed there under or of any of the contract documents which may be made between you and the supplier/contractor shall in any way release us from any liability under this guarantee and we hereby waive notice of any such change, addition or modification.

This guarantee shall be valid until the..... day of2020

(Sig. of the authorized officer of the Bank)

Name and designation of the officer

Name and address of the Bank

.....

Banker’s common seal

PERFORMANCE STATEMENT

(Must be filled in all respect)

1	Name & Location of work		
2	Cost of work		
3	Name of Client		
4	Full address of the firm		
5	Contact No. of the contact person of the Client for whom works was executed		
6	E-mail id of the contact person (Mandatory)		
7	Completion period	Stipulated (Date of work started)	
		Actual (Date of Completion work)	
8	Whether the work was left incomplete (reason if any for delay in completion of work) or contract was terminated from either side (give full details)		
9	Any other relevant information		

LIST NO-1
(Must be filled in all respect)

TENDERERS SHOULD FURNISH SPECIFIC ANSWERS TO ALL THE QUESTIONS GIVEN BELOW. TENDERERS MAY PLEASE NOTE THAT IF THE ANSWER SO FURNISHED ARE NOT CLEAR AND / OR ARE EVASIVE, THE TENDER WILL BE LIABLE TO BE IGNORED.

1. Tender No. _____
2. Name and address of firm/contractor :
3. What is your permanent Income Tax A/C NO. :
4. Status.
 - a) Indicate whether you are Govt. registered or not :
 - b) TIN No. :
5. Please indicate name & full address of your banker in the following format -
 - a) Bank Name, Branch and Bank Account No. (Core bank account)
 - b) IFSC Code :
 - c) Whether bank branch is NEFT/RTGS enables or not:
6. State whether your firm with you have been banned by any Govt. /CPWD authority? :
7. Please confirm that you have read all the instructions carefully and have complied with accordingly. :

Signature of Witness

(Full Name and address of witness in Block letters)

Signature of Tenderer with seal

(Full Name and address of the persons signing in Block letters)

Whether signing as
 Proprietor/Partner/Constituted
 Attorney/duly authorized by the Company

Questionnaire/Check List (must be filled in all respect)

01	Whether firm/Contractor is registered for the tendered work or not	
02	Registration No. and Date	
03	Registration issued by	
04	Registration valid up to	
05	Copy of Registration submitted or not	
06	GST registration No	
07	Whether Copy of GST registration certificate submitted or not with tender	
08	PAN No.	
09	Whether Copy of PAN No submitted or not with tender	
10	Whether Copy of replacement Warranty period of new fittings enclosed or not	
11	Whether EMD enclosed, if yes details of EMD	
12	Whether offer is valid up to 180 days or otherwise.	
13	Complete details of Banker with IFSC code, Account No. Name of Bank, Name of Branch, Bank Code, Swift code etc.	
14	Whether past performance Performa submitted along with copies of award of contracts or not	
15	Whether tender specification / work scope accepted by the firm/contractor or not	
16	Whether all pages of tender has been signed by the authorized signatory or not and returned with offer of not.	
17	Whether all the terms and condition of the Tender Enquiry including payment terms are acceptable or not	
18	Any other specific condition of the firm/contractor	

Signature _____
 (Name of the firm/Contractor)
 With seal/stamp

TENDER ACCEPTANCE LETTER

(The bidder must submit on Company Letter Head.)

Date:

To,

Sub: Acceptance of Terms & Conditions of Tender.

Tender Reference No: _____

Name of Tender / Work::- _____

Dear Sir,

1. I/ We have downloaded / obtained the tender document(s) for the above mentioned 'Tender/Work' from the web site(s) namely:

as per your advertisement, given in the above mentioned website(s).

2. I / We hereby certify that I / we have read the entire terms and conditions of the tender documents from Page No. _____ to _____ (including all documents like annexure(s), schedule(s), etc .), which form part of the contract agreement and I / we shall abide hereby by the terms / conditions / clauses contained therein.

3. The corrigendum(s) issued from time to time by your department/ organizations too have also been taken into consideration, while submitting this acceptance letter.

4. I / We hereby unconditionally accept the tender conditions of above mentioned tender document(s) / Corrigendum in its totality /entirety.

5. In case any provisions of this tender are found violated , then your department/ organization shall without prejudice to any other right or remedy be at liberty to reject this tender/bid including the forfeiture of the full said earnest money deposit absolutely.

Yours Faithfully,

(Signature of the Bidder, with Official Seal)

Form 68-A

Tender No. _____

Full name and address of the Tenderer in addition Contractor's telegraphic Address

To post box No. if any should be quoted in all _____

Communication to this Office _____

Telephone No. _____

Fax No. _____ From.

Dear Sir, _____

1. I/We hereby offer to supply the stores detailed in the schedule here to or such portion thereof as you may specify in the acceptance of tender at the price given in the said schedule and agree to hold this offer open till _____ I/we shall be bound by a communication of acceptance within the prescribed time.

2. I/We have understood the instructions to Tenderers in the booklet DGS&D-229 and conditions of contract in the Form No-68 (Revised) including in the pamphlet entitling conditions of contract governing contracts placed by the Central Purchases Organization of the Government of India read with the amendments annexed herewith and have thoroughly examined the specification drawing and/or pattern quoted in the schedule hereto and am/are fully aware of the nature of the stores required and my/our offer is to supply stores strictly in accordance with the requirements.

Signature of the Tenderer with seal

The following pages have been added to and form part of this tender _____

Here paste coupon in case where coupons are supplied to contractors on payment
--

Yours faithfully,
 (Signature of the Tenderer with
 seal)

Address _____

(Signature of the Witness)

Address _____

Dated _____

Appendix-“J”**(Must be filled in all respect.)**

Sl. No.	Requirement	(Firm Should correctly fill following column.)	(Indicate page number of tender documents where related information is shown/available it can be verified columns should be highlighted)
1	Whether Regd with CPWD/PWD		
	Validity of registration		
2	Whether EMD enclosed (Reqd. Rs. /- Should be valid up to 180 Days from the date of opening of tender)		
	Whether specification of work confirmed or not		
3	Terms of work start and finish (Our requirement is start within 07 Days and finished within 30 Days)		
4	Validity of offer (Our requirement is 180 days from the date of opening)		
5	Past performance (attached or not)		
6	Arbitration Clause (agreed or not)		
7	Warranty Clause (agreed or not)		
8	GSTIN NO. (attached or not)		
9	Liquidated damage clause (agreed or not)		
10	Partnership agreement (attached or not)		
11	Name & Add. Of Bankers.		
12	Whether business dealing banned or not		
13	Whether tender signed properly		
14	Pan Card Details		
15	GSTIN		

Signature of Tenderer

Date.....

Name of Tenderer.

APPENDIX-H

FORMAT FOR PRICE BID

S N.	DETAILS OF WORK	A/U	QTY	RATE	AMT	Basics rates in figured to be entered by the bidder in Rs. P	Total amount without taxes/other charges in Rs. P	Total amount with taxes/other charges in Rs. P	Total amount in words
1	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m.								
1.1	All kinds of soil.	CUM	5.62						
2	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level :								
2.1	1:4:8 (1 Cement : 4 coarse sand (zone-III) : 8 graded stone aggregate 40 mm nominal size)	CUM	0.62						
3	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in:								
3.1	Cement mortar 1:6 (1 cement : 6 coarse sand)	CUM	10.10						
4	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in :								
4.1	Cement mortar 1:6 (1 cement : 6 coarse sand)	CUM	2.89						
5	Providing and laying damp-proof course 50mm thick with cement concrete 1:2:4 (1 cement : 2 coarse sand(zone-III) : 4 graded stone aggregate 20mm nominal size).	Sqm	2.08						
6	12 mm cement plaster of mix :								
6.1	1:6 (1 cement: 6 coarse sand)	Sqm	11.88						
7	15 mm cement plaster on rough side of single or half brick wall of mix:								
7.1	1:4 (1 cement: 4 coarse sand)	Sqm	24.00						
8	Supplying and filling in plinth with sand under floors, including watering, ramming, consolidating and dressing complete.	CUM	0.97						

9	62 mm thick cement concrete flooring with concrete hardener topping, under layer 50 mm thick cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size) and top layer 12mm thick cement hardener consisting of mix 1:2 (1 cement hardener mix : 2 graded stone aggregate, 6mm nominal size) by volume, hardening compound mixed @ 2 litre per 50 kg of cement or as per manufacture's specifications. This includes cost of cement slurry, but excluding the cost of nosing of steps etc. complete.	Sqm	0.19						
10	Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete.								
10.1	Size of Tile 600x600 mm	Sqm	1.93						
11	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	Sqm	6.67						
12	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	Kg	120						
13	Providing and fixing pre-coated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineerin-charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	Sqm	4.84						

14	Providing and fixing precoated galvanised steel sheet roofing accessories 0.50 mm (+0.05 %) total coated thickness, Zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws complete								
14.1	Ridges plain (500 - 600mm)	Metre	4.8						
15	Providing and fixing false ceiling at all height including providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS : 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25 mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound , jointing tapes , finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of the Engineer in Charge but excluding the cost of painting with :								

15.1	Fully Perforated Gypsum Plaster Board of size 1200 x 2400x12.5 mm having approx. 15 % perforated area with perforation size and pattern as approved by the Engineer-in-charge and as per manufacturer's specification, with all 4 side tapered and backed by acoustical tissue with NRC value not less than 0.60 sqm	Sqm	1.93						
16	Designing, fabricating, testing, installing and fixing in position Curtain Wall with Aluminium Composite Panel Cladding, with open grooves for linear as well as curvilinear portions of the building , for all heights and all levels etc. including:								
16.1	(a) Structural analysis & design and preparation of shop drawings for pressure equalisation or rain screen principle as required, proper drainage of water to make it watertight including checking of all the structural and functional design								
16.2	(b) Providing, fabricating and supplying and fixing panels of aluminium composite panel cladding in pan shape in metallic colour of approved shades made out of 4mm thick aluminium composite panel material consisting of 3mm thick FR grade mineral core sandwiched between two Aluminium sheets (each 0.5mm thick). The aluminium composite panel cladding sheet shall be coil coated, with Kynar 500 based PVDF / Lumiflon based fluoropolymer resin coating of approved colour and shade on face # 1 and polymer (Service) coating on face # 2 as specified using stainless steel screws, nuts, bolts, washers, cleats, weather silicone sealant, backer rods etc.								

16.3	(c) The fastening brackets of Aluminium alloy 6005 T5 / MS with Hot Dip Galvanised with serrations and serrated washers to arrest the wind load movement, fasteners, SS 316 Pins and anchor bolts of approved make in SS 316, Nylon separators to prevent bi-metallic contacts all complete required to perform as per specification and drawing The item includes cost of all material & labour component, the cost of all mock ups at site, cost of all samples of the individual components for testing in an approved laboratory, field tests on the assembled working curtain wall with aluminium composite panel cladding, cleaning and protection of the curtain wall with aluminium composite panel cladding till the handing over of the building for occupation. Base frame work for ACP cladding is payable under the relevant aluminium item.s The Contractor shall provide curtain wall with aluminium composite panel cladding, having all the performance characteristics all complete , as per the Architectural drawings, as per item description, as specified, as per the approved shop drawings and as directed by the Engineer-in-Charge. However, for the purpose of payment, only the actual area on the external face of the curtain wall with Aluminum Composite Panel Cladding (including width of groove) shall be measured in sqm. up to two decimal places. sqm 4309.80	Sqm	24.48						
17	Renewing glass panes and refixing existing wooden fillets.								
17.1	Float glass panes of nominal thickness 5 mm (Weight not less than 12.5 kg/sqm)	Sqm	4.8						
18	Providing and fixing factory made uPVC door frame made of uPVC extruded sections having an overall dimension as below (tolerance ± 1 mm), with wall thickness 2.0 mm (± 0.2 mm), corners of the door frame to be Jointed with galvanized brackets and stainless steel screws, joints mitred and Plastic welded. The hinge side vertical of the framesreinforced by galvanized M.S. tube of size 19 X 19 mm and 1mm (± 0.1 mm) wall thickness and 3 nos. stainless steel hinges fixed to the frame complete as per manufacturer's specification and direction of Engineerin-charge								
18.1	Extruded section profile size 42x50 mm metre 267.45	Metre	12.60						
19	Applying one coat of water thinnable cement primer of approved brand and manufacture on wall surface :								
19.1	Water thinnable cement primer.	Sqm	11.2						

20	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	Sqm	11.2						
21	Distempering with 1st quality acrylic distemper (ready mixed) having VOC content less than 50 gms/litre, of approved manufacturer, of required shade and colour complete, as per manufacturer's specification.								
21.1	Two or more coats on new work	Sqm	11.2						
23	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with piano type switch, phenolic laminated sheet, suitable size MS box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required								
23.1	Group C	Points	3.00						
24	Wiring for light/ power plug with 2X4 sq. mm FRLS PVC insulated copper conductor single core cable in surface/ recessed medium class PVC conduit alongwith 1 No. 4 sq. mm FRLS PVC insulated copper conductor single core cable for loop earthing as required	Mtrs	20.00						
25	Supplying and fixing DP sheet steel enclosure on surface/ recess along with 25/32 A 240 V "C" curve DP MCB complete with connections, testing and commissioning etc. as required.	each	1.00						
26	Supplying and fixing following way, horizontal type three pole and neutral, sheet steel, MCB distribution board, 415 V, on surface/ recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator)								
26.1	8 way (4 + 24), Double door	each	1.00						

SIGNATURE OF TENDERER WITH DATE AND SEAL

Instructions for Online Bid Submission Instructions to the Bidders to submit the bids online through the Central Public Procurement Portal for e Procurement at <http://eprocure.gov.in/eprocure/app>.

- 1) Possession of valid Digital Signature Certificate (DSC) and enrollment/registration of the contractors/bidders on the e-procurement/e-tender portal is a prerequisite for e-tendering.
- 2) Bidder should do the enrollment in the e-Procurement site using the “Click here to Enroll” option available on the home page. Portal enrollment is generally free of charge. During enrollment/registration, the bidders should provide the correct/true information including valid email_id. All the correspondence shall be made directly with the contractors/bidders through email_id provided.
- 3) Bidder need to login to the site through their user ID/ password chosen during enrollment/registration.
- 4) Then the Digital Signature Certificate (Class II or Class III Certificates with signing key usage) issued by SIFY/TCS/nCode/eMudra or any Certifying Authority recognized by CCA India on eToken/Smartcard, should be registered.
- 5) The DSC that is registered only should be used by the bidder and should ensure safety of the same.
- 6) Contractor/Bidder may go through the tenders published on the site and download the required tender documents/schedules for the tenders he/she is interested.
- 7) After downloading / getting the tender document/schedules, the Bidder should go through them carefully and then submit the documents as asked, otherwise bid will be rejected.
- 8) If there are any clarifications, this may be obtained online through the tender site, or through the contact details. Bidder should take into account the corrigendum published before submitting the bids online.
- 9) Bidder then logs in to the site through the secured log in by giving the user id/ password chosen during enrolment/registration and then by giving the password of the eToken/Smartcard to access DSC.
- 10) Bidder selects the tender which he/she is interested in by using the search option & then moves it to the ‘my tenders’ folder.
- 11) From my tender folder, he selects the tender to view all the details indicated.
- 12) It is construed that the bidder has read all the terms and conditions before submitting their offer. Bidder should go through the tender schedules carefully and upload the documents as asked; otherwise, their bid will be rejected.
- 13) Bidder, in advance, should get ready the bid documents to be submitted as indicated in the tender document/schedule and generally, they can be in PDF/xls/rar/zip/dwf formats. If there is more than one document, they can be clubbed together and can be provided in the requested format. Each document to be uploaded through online for the tenders should be less than 2 MB. If any document is more than 2MB, it can be reduced through zip/rar and the same can be uploaded, if permitted. Bidders Bid documents may be scanned with 100

dpi with black and white option. However if the file size is less than 1 MB the transaction uploading time will be very fast.

- 14) If there are any clarifications, this may be obtained through the site, or during the pre-bid meeting if any. Bidder should take into account the corrigendum published from time to time before submitting the online bids.
- 15) The Bidders can update well in advance, the documents such as certificates, annual report details etc., under My Space option and these can be selected as per tender requirements and then send along with bid documents during bid submission. This will facilitate the bid submission process faster by reducing upload time of bids.
- 16) Bidder should submit the Tender Fee/ EMD as specified in the tender. The original should be posted/couriered/given in person to the Tender Inviting Authority, within the bid submission due date & time for the tender. Scanned copy of the instrument should be uploaded as part of the offer.
- 17) While submitting the bids online, the bidder reads the terms & conditions and accepts the same to proceed further to submit the bid packets.
- 18) The bidder has to select the payment option as offline to pay the Tender Fee/ EMD as applicable and enter details of the instruments.
- 19) The details of the DD/any other accepted instrument, physically sent, should tally with the details available in the scanned copy and the data entered during bid submission time. Otherwise submitted bid will not be acceptable.
- 20) The bidder has to digitally sign and upload the required bid documents one by one as indicated. Bidders to note that the very act of using DSC for downloading the bids and uploading their offers shall be deemed to be a confirmation that they have read all sections and pages of the bid document including General conditions of contract without any exception and have understood the entire document and are clear about the requirements of the tender requirements.
- 21) The bidder has to upload the relevant files required as indicated in the cover content. In case of any irrelevant files, the bid will be rejected.
- 22) If the price bid format is provided in a spread sheet file like BoQ_xxxx.xls, the rates offered should be entered in the allotted space only and uploaded after filling the relevant columns. The Price Bid/BOQ template must not be modified/replaced by the bidder, else the bid submitted is liable to be rejected for this tender.
- 23) The bidders are requested to submit the bids through online e-tendering system to the Tender Inviting Authority(TIA) well before the bid submission end date & time (as per Server System Clock). The TIA will not be held responsible for any sort of delay or the difficulties faced during the submission of bids online by the bidders at the eleventh hour.
- 24) After the bid submission (ie after Clicking "Freeze Bid Submission" in the portal), the acknowledgement number, given by the system should be printed by the bidder and kept as a record of evidence for online submission of bid for the particular tender and will also act as an entry pass to participate in the bid opening date.

- 25) The time settings fixed in the server side & displayed at the top of the tender site, will be valid for all actions of requesting, bid submission, bid opening etc., in the e-tender system. The bidders should follow this time during bid submission.
- 26) All the data being entered by the bidders would be encrypted using PKI encryption techniques to ensure the secrecy of the data. The data entered will not be viewable by unauthorized persons during bid submission & not be viewable by any one until the time of bid opening.
- 27) Any bid document that is uploaded to the server is subjected to symmetric encryption using a system generated symmetric key. Further this key is subjected to asymmetric encryption using buyers/bid opener's public keys. Overall, the uploaded tender documents become readable only after the tender opening by the authorized bid openers.
- 28) The confidentiality of the bids is maintained since the secured Socket Layer 128 bit encryption technology is used. Data storage encryption of sensitive fields is done.
- 29) The bidder should logout of the tendering system using the normal logout option available at the top right hand corner and not by selecting the (X) exit option in the browser.
- 30) For any queries regarding e-tendering process, the bidders are requested to contact as provided in the tender document. Parallely for any further queries, the bidders are asked to contact over phone: 1800-3070-2232 or send a mail over to – cppp-doe@nic.in, cppp-nic@nic.in.

Sd-14/05/2022

(BHANU PRATAP SINGH)

DIGP, GC, CRPF, JAMMU.

For and on behalf of the President of India

Signature of the tenderer with seal